

PAVEMENT MARKING SCHEDULE			
STATION	TYPE	PAINT PVT MKG - LINE 5"	
		WHITE	YELLOW
LOCATION #1			
LT & RT 160+61 TO 168+11	EDGE LINE	1,500 FT	
160+61 TO 168+11	SKIP DASH		188 FT
LOCATION #2			
LT 270+18.75 TO 277+68.75	EDGE LINE	750 FT	
LT 279+62.83 TO 287+12.83	EDGE LINE	750 FT	
270+18.75 TO 272+26.75	SKIP DASH		52 FT
RT 272+26.75 TO 277+68.75	SKIP DASH		136 FT
LT 272+26.75 TO 277+68.75	NO PASS		542 FT
LT 279+62.83 TO 284+15.75	NO PASS		453 FT
RT 279+62.83 TO 283+29.75	SKIP DASH		92 FT
RT 283+29.75 TO 287+12.83	NO PASS		383 FT
LT 284+15.75 TO 287+12.83	SKIP DASH		74 FT
LOCATION #3			
LT 403+06 TO 421+56	EDGE LINE	1,850 FT	
LT 403+06 TO 413+11	NO PASS		1,005 FT
LT 413+11 TO 421+56	SKIP DASH		211 FT
LOCATION #4			
LT & RT 15+89.5 TO 20+00	EDGE LINE	821 FT	
15+89.5 TO 20+00	SKIP DASH		103 FT
STA. EQ. 20+00bk=447+14.5ah			
447+14.5 TO 456+28	EDGE LINE	1,827 FT	
447+14.5 TO 455+81	SKIP DASH		216 FT
LT & RT 455+81 TO 456+28	NO PASS		94 FT
STA. EQ. 456+28bk=10+00ah			
LT & RT 10+00 TO 28+74	EDGE LINE	3,748 FT	
LT & RT 10+00 TO 28+74	NO PASS		3,748 FT
DEDUCT FOR S.R.	SKIP DASH	(430)	
TOTALS		10,816 FT	7,297 FT

MIXTURE REQUIREMENTS	
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT	
MIXTURE USE(S):	POLY. H.M.A. SURF. CRSE., MIX D, N70
AC/PG	SBS PG 70-22
DESIGN AIR VOIDS:	4.0% @ N DESIGN = 70
MIXTURE COMP:	IL 9.5 OR 12.5
FRICITION AGG:	MIX "D"

NOTES:

1. STATIONS ARE APPROXIMATE.
2. SEE SHEET 7 FOR STATION EQUATIONS.

SCHEDULES
FAP 325 (IL 16)
SECTION (2)I-5
MONTGOMERY COUNTY