

ENTRANCE & SIDEROAD SCHEDULE				
STATION	TYPE	INC BIT SURFACING	AGG. SURF. CRSE., TY. B	SECTION
LT 544+21	BITUMINOUS SIDEROAD	22.4 TON		C-C
RT 545+51	AGG. P.E.	1.4 TON	1.4 TON	A-A
RT 546+38	AGG. P.E.	1.4 TON	1.4 TON	A-A

PAVEMENT MARKING SCHEDULE			
STATION	TYPE	PAINT PVT MK LINE 5"	
		WHITE	YELLOW
LT & RT 553+70 TO 547+80	EDGE LINE	2,820 FT	
LT & 140+53 TO 147+90	NO PASS		353 FT
DEDUCT FOR SIDEROADS		(214 FT)	
TOTALS		2,606 FT	353 FT

NOTES:

ENTRANCES AND SIDEROADS SHALL BE CONSTRUCTED ACCORDING TO THE SECTION INDICATED AS SHOWN ON SHEET 8.

STATIONS ARE APPROXIMATE.

MIXTURE REQUIREMENTS			
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT			
MIXTURE USE(S):	POLYMERIZED H.M.A S.C., MIX D, N70	H.M.A. B.C., IL-19.0, N70	INC. H.M.A. SURF.
AC/PG	SBS PG 70-22	PG 64-22	PG 64-22
DESIGN AIR VOIDS:	4.0% @ N DESIGN = 70	4.0% @ N DESIGN = 70	4.0% @ N DESIGN = 50
MIXTURE COMP:	IL 9.5 OR 12.5	IL 19.0	IL 9.5 OR 12.5
FRICITION AGG:	MIX "D"	N/A	MIX "C"

SCHEDULES  
FAS 1771 (OAK STREET)  
SECTION 25RS-8  
SANGAMON COUNTY