

PART OF THE NW 1/4 OF SECTION 22, TWP. 41 N., R.8 E. OF THE 3RD. P.M., IN KANE COUNTY, ILLINOIS.


COORDINATE TABLE

STATION	OFFSET	PT#	NORTH	EAST
76+76.41	80.02	5208	1951355.689	990119.865
76+76.41	80.02	5209	1951515.171	990104.594
76+77.34	64.47	5210	1951357.488	990104.396
76+77.34	64.47	5211	1951515.521	990127.443
76+80.90	80.00	5224	1951640.756	990133.380
76+80.90	80.00	5225	1951640.460	990113.889
76+84.78	-115.03	5350	1951533.578	989933.332
76+84.78	-115.03	5364	1951597.732	989876.154
76+86.96	-175.08	5368	1951657.832	989876.201
76+86.96	-175.08	5372	1951681.042	989975.875
76+86.96	-175.08	5373	1951681.536	989990.915
76+86.96	-175.08	8123	1951369.986	990040.494
77+16.00	79.86	8143	1951395.570	990121.760
77+15.43	71.79	8144	1951395.400	990113.670
77+25.94	71.05	8145	1951405.960	990113.460
77+25.94	71.05	8146	1951405.810	990105.960
77+40.85	62.48	8147	1951421.310	990113.140
77+41.37	69.96	8148	1951432.100	990112.920
77+41.37	69.21	8149	1951432.100	990112.920
77+42.70	79.77	8150	1951432.310	990123.500
79+10.87	-118.08	8151	1951599.610	989933.300
79+14.20	-118.34	8152	1951602.837	989933.180
77+53.82	51.91	9164	1951434.803	990005.724
79+03.29	61.33	9166	1951583.912	990112.181
79+33.90	-78.37	9229	1951620.689	989973.979
76+85.65	-75.90	9308	1951373.178	989964.658
77+44.58	-65.77	9309	1951431.387	989977.736
78+30.84	-78.35	9310	1951517.973	989969.324
76+86.53	-65.90	9312	1951374.548	989954.715
77+44.70	-75.90	9313	1951432.008	989967.625
77+44.70	-117.50	9314	1951434.067	989926.076
78+44.59	-117.50	9315	1951533.496	989930.859
77+60.00	52.28	9374	1951440.968	990096.405

SEE CONTINUATION ON SHEET 33

LEGEND

- SECTION LINE
- QUARTER SECTION LINE
- QUARTER QUARTER SECTION LINE
- PLATTED LOT LINES
- PROPERTY (DEED) LINE
- APPARENT PROPERTY LINE
- CENTERLINE
- EXISTING RIGHT OF WAY LINE
- PROPOSED RIGHT OF WAY LINE
- PROPOSED EASEMENT
- MEASURED DIMENSION
- COMPUTED DIMENSION
- RECORDED DIMENSION
- EXISTING BUILDING
- LIGHT POLE
- IRON PIPE OR ROD FOUND
- CUT CROSS FOUND OR SET
- THESE STAKES REFERENCE FOUND OR SET MONUMENTATION. SET 5/8 INCH IRON ROD FLUSH WITH GROUND TO THE FOUND IRON STAKE IDENTIFIED BY COLORED PLASTIC CAP BEARING SURVEYORS REGISTRATION NUMBER.
- THESE STAKES, IN CULTIVATED AREAS, REFERENCE FOUND OR SET MONUMENTATION. BURIED 5/8 INCH IRON ROD 20 INCHES BELOW GROUND TO THE FOUND IRON STAKE. IDENTIFIED BY COLORED PLASTIC CAP BEARING SURVEYORS REGISTRATION NUMBER.
- STAKING OF PROPOSED RIGHT OF WAY. SET DIVISION OF HIGHWAYS SURVEY MARKER TO MONUMENT THE POSITION SHOWN, IDENTIFIED BY INSCRIPTION DATA AND SURVEYORS REGISTRATION NUMBER.
- STAKING OF PROPOSED RIGHT OF WAY IN CULTIVATED AREAS. BURIED 5/8 INCH METAL ROD 20 INCHES BELOW GROUND TO MARK FUTURE SURVEY MARKER POSITION IDENTIFIED BY COLORED PLASTIC CAP BEARING SURVEYORS REGISTRATION NUMBER.
- PERMANENT SURVEY MARKER, I.D.O.T. STANDARD 2135 (TO BE SET BY OTHERS)
- RIGHT OF WAY STAKING PROPOSED TO BE SET
- Light Pole



Bearings are referenced to the Illinois Coordinate System, NAD83, East Zone, as provided by the Illinois Department of Transportation.

- "MAG" NAIL SET
- 5/8" REBAR SET

STATE OF ILLINOIS )  
 COUNTY OF Will )  
 THIS IS TO CERTIFY THAT I, RONALD F. HODGEN, AN ILLINOIS PROFESSIONAL LAND SURVEYOR, (WE, RUETTIGER, TONELLI & ASSOCIATES, AN ILLINOIS PROFESSIONAL DESIGN FIRM LAND SURVEYING CORPORATION, NUMBER 89,) HAVE SURVEYED THE PLAT OF HIGHWAYS SHOWN HEREON IN SECTION 22, TOWNSHIP 41 NORTH, RANGE 8 EAST OF THE THIRD PRINCIPAL MERIDIAN, KANE COUNTY, THAT THE SURVEY IS TRUE AND COMPLETE AS SHOWN TO THE BEST OF MY KNOWLEDGE AND BELIEF, THAT THE PLAT CORRECTLY REPRESENTS SAID SURVEY, THAT ALL MONUMENTS FOUND AND ESTABLISHED ARE OF PERMANENT QUALITY AND OCCUPY THE POSITIONS SHOWN THEREON AND THAT THE MONUMENTS ARE SUFFICIENT TO ENABLE THE SURVEY TO BE RETRACED, MADE FOR THE DEPARTMENT OF TRANSPORTATION, STATE OF ILLINOIS.

DATED AT Joliet, ILLINOIS THIS 11th DAY OF May 2011 A.D.  
 [Signature]  
 ILLINOIS PROFESSIONAL LAND SURVEYOR NO. 2630  
 LICENSE EXPIRATION DATE: 11-30-2012  
 THIS PROFESSIONAL SERVICE CONFORMS TO THE CURRENT ILLINOIS MINIMUM STANDARDS FOR A BOUNDARY SURVEY.



RUETTIGER, TONELLI & ASSOCIATES, INC.  
 Land Surveyors/Engineers/Planners/Landscape Architects/G.I.S. Consultants  
 2174 ONEIDA STREET  
 JOLIET, ILLINOIS 60435  
 PH. (815) 744-6600 FAX (815) 744-0101

RECEIVED  
 MAY 12 2011  
 PLATS & LEGALS

PLAT OF HIGHWAYS  
 STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION  
 FAP 345 (US 20)

SECTION: COUNTY: KANE  
 PROJECT JOB NO.: R-91-017-01  
 STATION 76+00 TO STATION 80+00  
 SCALE: 1" = 20' SHEET 32 OF 41

BUREAU OF LAND ACQUISITION  
 201 WEST CENTER COURT  
 SCHALMBURG, ILLINOIS 60196

SEE CONTINUATION ON SHEET 31

PROP. CURVEP-MCLEAN-3  
 PI STA. = 83+39.95  
 Δ = 2° 10' 44" (L.T)  
 D = 0° 10' 00"  
 R = 34,370.62'  
 T = 653.59'  
 L = 1,307.03'  
 E = 6.21'  
 e = -----  
 T.R. = -----  
 S.E. RUN = -----  
 P.C. STA = 76+86.36  
 P.T. STA = 89+93.39

FROM	BEARING/ANGLE	DISTANCE	TO	DESCRIPTION
5210	NW 59 52'50"	180.25	890	CUT CROSS IN CONCRETE
5210	NE 61 14'24"	67.68	904	CUT CROSS IN INLET
5210	NE 02 03'29"	35.38	905	CUT CROSS IN CURB
5350	SW 02 07'06"	56.86	887	CUT CROSS IN CONCRETE
5350	SE 07 13'31"	39.46	896	CUT CROSS IN CONCRETE
5350	NW 14 34'36"	36.87	891	CUT CROSS IN SANITARY MANHOLE RIM
5364	SE 07 10'35"	99.73	887	CUT CROSS IN CONCRETE
5364	SE 21 19'23"	108.32	888	CUT CROSS IN CONCRETE
5364	NE 41 47'33"	134.91	893	CUT CROSS IN CONCRETE
5368	SE 03 44'43"	159.38	887	CUT CROSS IN CONCRETE
5368	SE 13 03'27"	165.28	888	CUT CROSS IN CONCRETE
5368	NE 65 15'43"	96.74	893	CUT CROSS IN CONCRETE
5373	SW 32 09'12"	192.23	887	CUT CROSS IN CONCRETE
5373	SW 24 35'23"	181.13	888	CUT CROSS IN CONCRETE
5373	NW 34 03'01"	44.39	893	CUT CROSS IN CONCRETE
8123	NW 49 43'44"	120.60	890	CUT CROSS IN CONCRETE
8123	NE 60 45'08"	124.65	904	CUT CROSS IN INLET
8123	NE 37 30'14"	133.04	906	CUT CROSS IN CURB
9164	NW 84 54'05"	147.83	890	CUT CROSS IN CONCRETE
9164	SE 13 19'53"	43.12	905	CUT CROSS IN CURB
9164	NE 32 19'19"	48.30	906	CUT CROSS IN CURB
9166	SW 85 32'43"	188.70	891	CUT CROSS IN SANITARY MANHOLE RIM
9166	SE 16 27'24"	46.58	907	CUT CROSS IN INLET RIM
9166	NE 23 22'26"	35.75	908	CUT CROSS IN INLET RIM
9308	NW 12 16'03"	124.07	899	CUT CROSS IN CONCRETE
9308	NW 12 12'35"	76.49	890	CUT CROSS IN CONCRETE
9308	NE 82 03'36"	142.37	905	CUT CROSS IN CURB
9309	NW 52 02'10"	74.35	889	CUT CROSS IN CONCRETE
9309	NW 59 29'50"	33.61	890	CUT CROSS IN CONCRETE
9309	SE 73 14'02"	133.61	905	CUT CROSS IN CURB
9310	SW 76 37'45"	82.96	887	CUT CROSS IN CONCRETE
9310	SW 52 47'31"	38.96	888	CUT CROSS IN CONCRETE
9310	SW 16 34'27"	73.07	890	CUT CROSS IN CONCRETE

COORDINATES SHOWN HEREON ARE ILLINOIS STATE PLANE EAST ZONE NAD 83 (2007) GRID BASED ON NGS STATION 0120 WITH PUBLISHED COORDINATES OF NORTH 1930566.76, EAST 1004454.55.

FAP 345 (US 20)