

GIRDER 5

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10918.59	-69.83	807.97	807.97
⊕ Brg. N. Abut.	10924.20	-68.82	807.98	807.98
A	10934.04	-67.06	807.99	808.08
B	10943.89	-65.30	808.00	808.18
C	10953.73	-63.54	808.00	808.26
D	10963.58	-61.78	807.99	808.32
E	10973.42	-60.02	807.98	808.37
F	10983.26	-58.26	807.96	808.40
G	10993.11	-56.51	807.93	808.40
H	11002.95	-54.75	807.89	808.38
I	11012.80	-52.99	807.86	808.34
J	11022.64	-51.23	807.81	808.27
K	11032.48	-49.47	807.76	808.18
L	11042.33	-47.71	807.70	808.07
M	11052.17	-45.95	807.63	807.94
N	11062.02	-44.19	807.56	807.79
O	11071.86	-42.43	807.48	807.63
P	11081.70	-40.67	807.39	807.45
⊕ Brg. S. Abut.	11088.06	-39.53	807.34	807.34
Bk. S. Abut.	11093.67	-38.53	807.28	807.28

GIRDER 6

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10907.12	-63.24	808.08	808.08
⊕ Brg. N. Abut.	10912.73	-62.24	808.09	808.09
A	10922.58	-60.48	808.11	808.20
B	10932.42	-58.72	808.12	808.30
C	10942.26	-56.96	808.13	808.39
D	10952.11	-55.20	808.13	808.46
E	10961.95	-53.44	808.12	808.52
F	10971.80	-51.68	808.11	808.55
G	10981.64	-49.92	808.09	808.56
H	10991.48	-48.16	808.06	808.55
I	11001.33	-46.40	808.03	808.52
J	11011.17	-44.64	807.99	808.46
K	11021.02	-42.88	807.95	808.37
L	11030.86	-41.12	807.89	808.27
M	11040.70	-39.36	807.84	808.15
N	11050.55	-37.60	807.77	808.00
O	11060.39	-35.84	807.70	807.85
P	11070.24	-34.08	807.62	807.68
⊕ Brg. S. Abut.	11076.60	-32.95	807.57	807.57
Bk. S. Abut.	11082.21	-31.94	807.52	807.52

GIRDER 7

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10895.65	-56.66	808.17	808.17
⊕ Brg. N. Abut.	10901.26	-55.65	808.19	808.19
A	10911.11	-53.89	808.22	808.31
B	10920.95	-52.13	808.24	808.41
C	10930.80	-50.37	808.25	808.51
D	10940.64	-48.61	808.26	808.59
E	10950.48	-46.85	808.26	808.65
F	10960.33	-45.09	808.25	808.70
G	10970.17	-43.34	808.24	808.72
H	10980.02	-41.58	808.22	808.71
I	10989.86	-39.82	808.20	808.68
J	10999.70	-38.06	808.17	808.63
K	11009.55	-36.30	808.13	808.56
L	11019.39	-34.54	808.08	808.46
M	11029.24	-32.78	808.03	808.34
N	11039.08	-31.02	807.98	808.21
O	11048.92	-29.26	807.91	808.06
P	11058.77	-27.50	807.84	807.90
⊕ Brg. S. Abut.	11065.13	-26.36	807.79	807.79
Bk. S. Abut.	11070.74	-25.36	807.75	807.75

GIRDER 8

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10884.18	-50.07	808.26	808.26
⊕ Brg. N. Abut.	10889.80	-49.07	808.28	808.28
A	10899.64	-47.31	808.31	808.40
B	10909.49	-45.55	808.34	808.52
C	10919.33	-43.79	808.36	808.62
D	10929.17	-42.03	808.38	808.71
E	10939.02	-40.27	808.39	808.78
F	10948.86	-38.51	808.39	808.83
G	10958.71	-36.75	808.38	808.86
H	10968.55	-34.99	808.37	808.86
I	10978.39	-33.23	808.36	808.84
J	10988.24	-31.47	808.33	808.80
K	10998.08	-29.71	808.30	808.73
L	11007.93	-27.95	808.26	808.64
M	11017.77	-26.19	808.22	808.53
N	11027.61	-24.43	808.17	808.40
O	11037.46	-22.67	808.11	808.26
P	11047.30	-20.91	808.05	808.11
⊕ Brg. S. Abut.	11053.66	-19.78	808.01	808.01
Bk. S. Abut.	11059.27	-18.77	807.97	807.97

GIRDER 9

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10872.72	-43.49	808.33	808.33
⊕ Brg. N. Abut.	10878.33	-42.48	808.36	808.36
A	10888.17	-40.72	808.40	808.49
B	10898.02	-38.96	808.44	808.62
C	10907.86	-37.20	808.47	808.73
D	10917.71	-35.44	808.49	808.82
E	10927.55	-33.68	808.51	808.90
F	10937.39	-31.92	808.51	808.96
G	10947.24	-30.17	808.52	808.99
H	10957.08	-28.41	808.51	809.00
I	10966.93	-26.65	808.50	808.99
J	10976.77	-24.89	808.49	808.95
K	10986.61	-23.13	808.47	808.89
L	10996.46	-21.37	808.44	808.81
M	11006.30	-19.61	808.40	808.71
N	11016.15	-17.85	808.36	808.59
O	11025.99	-16.09	808.31	808.46
P	11035.83	-14.33	808.25	808.31
⊕ Brg. S. Abut.	11042.19	-13.19	808.22	808.22
Bk. S. Abut.	11047.81	-12.19	808.18	808.18

CONST. JT. - NORTH EDGE OF WESTBOUND CLOSURE POUR

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10869.34	-41.55	808.36	808.36
⊕ Brg. N. Abut.	10874.96	-40.55	808.38	808.38
A	10884.80	-38.79	808.43	808.52
B	10894.65	-37.03	808.46	808.64
C	10904.49	-35.27	808.50	808.76
D	10914.33	-33.51	808.52	808.85
E	10924.18	-31.75	808.54	808.93
F	10934.02	-29.99	808.55	808.99
G	10943.87	-28.23	808.56	809.03
H	10953.71	-26.47	808.55	809.04
I	10963.55	-24.71	808.55	809.03
J	10973.40	-22.95	808.53	809.00
K	10983.24	-21.19	808.51	808.94
L	10993.08	-19.43	808.48	808.86
M	11002.93	-17.67	808.45	808.76
N	11012.77	-15.91	808.41	808.64
O	11022.62	-14.15	808.36	808.51
P	11032.46	-12.39	808.31	808.37
⊕ Brg. S. Abut.	11038.82	-11.26	808.27	808.27
Bk. S. Abut.	11044.43	-10.25	808.24	808.24