

SUMMARY OF QUANTITIES					CONSTRUCTION TYPE CODE
S.I.	CODE NO.	PAY ITEM	UNIT	QUAN	0005
	20101700	SUPPLEMENTAL WATERING	UNIT	2	2
	21101615	TOPSOIL FURNISH AND PLACE, 4"	SQ YD	115	115
	25200110	SODDING, SALT TOLERANT	SQ YD	115	115
	40600100	BITUMINOUS MATERIALS (PRIME COAT)	GALLON	1750	1750
	40600300	AGGREGATE (PRIME COAT)	TON	18	18
	40600827	POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL-4.75, N50	TON	370	370
	40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	SQ YD	455	455
	40603335	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50	TON	740	740
	42300300	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 7 INCH	SQ YD	120	120
	42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	690	690
	42400800	DETECTABLE WARNINGS	SQ FT	288	288
	44000157	HOT-MIX ASPHALT SURFACE REMOVAL, 2"	SQ YD	8720	8720
	44000200	DRIVEWAY PAVEMENT REMOVAL	SQ YD	120	120
	44000600	SIDEWALK REMOVAL	SQ FT	690	690
	44201725	CLASS D PATCHES, TYPE I, 7 INCH	SQ YD	10	10
	44201729	CLASS D PATCHES, TYPE II, 7 INCH	SQ YD	95	95
	44201733	CLASS D PATCHES, TYPE III, 7 INCH	SQ YD	56	56
	60250200	CATCH BASINS TO BE ADJUSTED	EACH	10	10
	67100100	MOBILIZATION	L SUM	1	1
	70102620	TRAFFIC CONTROL AND PROTECTION, STANDARD 701501	L SUM	1	1
	70102640	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM	1	1
	70300100	SHORT TERM PAVEMENT MARKING	FOOT	580	580
	* 78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT	556	556
	* 78000400	THERMOPLASTIC PAVEMENT MARKING - LINE 6"	FOOT	513	513
	* 78000650	THERMOPLASTIC PAVEMENT MARKING - LINE 24"	FOOT	280	280
	Z0004562	COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT	FOOT	490	490

* - INDICATES SPECIALTY ITEMS

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION THE CONTRACTOR SHALL CALL "J.U.L.I.E." AT (800) 892-0123 AND (312) 744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES. (48 HOUR NOTIFICATION REQUIRED)
- UTILITIES INDICATED ON THE PLANS ARE PROVIDED FOR THE CONTRACTORS USE AND ARE BASED UPON INFORMATION AVAILABLE AT THE TIME OF THE ADVERTISEMENT FOR BIDS. THE OWNER AND ENGINEER DO NOT GUARANTEE THE ACCURACY OF UTILITY INFORMATION.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.
- THE THICKNESS OF HMA MIXTURE STATED IN THE SPECIFICATIONS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA SURFACE IS PLACED.
- ACCESS TO DRIVEWAYS SHALL BE MAINTAINED AT ALL TIMES BY LIMITING CURB AND GUTTER REPAIR TO ONE-HALF THE DRIVEWAY WIDTH AT ONE TIME AS WELL AS TEMPORARY AGGREGATE.
- THE REMOVAL AND/OR REPLACEMENT OF ANY DRIVEWAYS, PAVEMENT, CURB, SIDEWALK, ETC. SHALL BE ACCOMPLISHED BY MEANS OF A SAW CUT JOINT, AT THE DIRECTION OF THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE UNIT PRICE FOR THE VARIOUS ITEMS.
- ANY LOOSE MATERIAL DEPOSITED IN THE FLOW LINE OF DITCHES, GUTTERS OR OTHER DRAINAGE STRUCTURES SHALL BE REMOVED BY THE END OF EACH DAY BY THE CONTRACTOR AT THEIR EXPENSE.
- FOR WORK OUTSIDE THE LIMITS OF BRIDGE APPROACH PAVEMENT, ALL REFERENCES IN THE HIGHWAY STANDARDS AND STANDARD SPECIFICATIONS FOR REINFORCEMENT, DOWEL BARS AND TIE BARS IN PAVEMENT, SHOULDERS, CURB, GUTTER, COMBINATION CURB AND GUTTER AND MEDIAN, AND CHAIR SUPPORTS FOR CRC PAVEMENT, SHALL BE EPOXY COATED, UNLESS OTHERWISE NOTED ON THE PLAN.

FILE NAME = 11428-QUAN-01 -DOT QUAN01

USER NAME =	DESIGNED -- DWS	REVISED --
	CHECKED -- JH/PB	REVISED --
PLOT SCALE =	DRAWN -- MED	REVISED --
PLOT DATE = 1-31-12	CHECKED -- AG	REVISED --

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

MINERVA AVENUE
MINERVA AVENUE RESURFACING
SUMMARY OF QUANTITIES & GENERAL NOTES

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1071	11-00053-00-RS	COOK	9	2
CONTRACT NO. 63678				
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT M-9003(905)				

SCALE: NONE SHEET NO. 2 OF 9 SHEETS STA. TO STA.