

FOR INFORMATION ONLY

U.S. 36 WHITETOPPING CORES E. OF TUSCOLA								
CORE	STATION	LANE	O/S FROM CL	WHITETOPPING (INCHES)	HMA (INCHES)	PCC (INCHES)	BRICK (INCHES)	BRICK BASE (INCHES)
1	66+75	EBL	7.0' RT	5 3/8	3 1/2	-	-	-
2	71+11	EBL	5.5' RT	4 1/4	7	6 1/4	-	-
3	82+86	EBL	7.0' RT	4 1/2	7 1/2	7 1/2	-	-
4A	92+87	EBL	7.5' RT	4 3/8	6	6 3/4	-	-
4B*	92+87	EBL	11.0' RT	4 1/4	-	-	-	-
5A	97+56	EBL	6.5' RT	4 1/4	7	7	-	-
5B*	97+56	EBL	2.0' RT	4 7/8	-	-	-	-
5C*	97+56	EBL	11.0' RT	4 1/8	-	-	-	-
6A	102+81	EBL	10.5' RT	3 3/4	3 5/8	9 3/4	-	-
6B*	102+81	EBL	6.5' RT	3 7/8	-	-	-	-
6C*	102+81	EBL	1.5' RT	4 1/8	-	-	-	-
7A	98+70	WBL	9.0' LT	5 1/2	6 3/4	-	4	2 1/2
7B*	98+70	WBL	2.5' LT	5 3/4	-	-	-	-
8A	94+27	WBL	6.5' LT	8	6	9	-	-
8B*	94+27	WBL	2.0' LT	8 1/8	-	-	-	-
9	90.43	WBL	6.5' LT	4 3/4	6 1/2	Broken into Pieces	-	-
10	86+46	WBL	9.0' LT	4 3/4	7	-	4	3 1/2
11A	75+24	WBL	7.0' LT	4 7/8	5 1/2	9 1/2	-	-
11B*	75+24	WBL	2.0' LT	5 1/8	-	-	-	-
11C*	75+24	WBL	11.0' LT	4 3/4	-	-	-	-
12A	69+50	WBL	7.0' LT	4 5/8	4	-	-	-
12B*	69+50	WBL	1.0' LT	4 7/8	-	-	-	-
12C*	69+50	WBL	11.0' LT	4 3/8	-	-	-	-

* A CORE AT THIS LOCATION WAS TAKEN TO DETERMINE WHITETOPPING THICKNESS ONLY. THE UNDERLYING PAVEMENTS WERE NOT CORED.