







NOTES:

- 1. Drilling and grouting of #4 h20(E) bars shall be in accordance with Section 584 of the Standard Specifications.
- 2. The cost of drilling holes, furnishing and placing Epoxy Grout and setting #4 h20(E) bars shall be included in the cost for Concrete Structures.
- 3. Provide joints in facing to match those in the existing barrier. See Sht B1 for joint details.
- 4. For Refaced Barrier details, see Sheet B2.
- 5. For Sections A-A thru H-H see Sheet B7.
- 6. For locations of Transition, see Roadway Plans.

RILL OF MATERIAL

	DILL OF MATERIAL								
	Bar	No.	Size	Length	Shape				
	d3(E)	16	#4	4'-9"					
	d6(E)	34	#4	3'-11"					
	h4(E)	6	#4	9'-6"					
	h5(E)	12	#4	22'-1"					
	h20(E)	63	#4	1'-6"					
-	Item	Unit	Quantity						
	Reinforcement Ba								
	Epoxy Coated	Pound	420						
*	Concrete Structur	Cu. Yd.	8						
	Protective Coat	Sq. Yd.	31						
	Concrete Removal	Cu. Yd.	1						

The pay items for the soldier pile wall are included in the quantities on Sheet B2.

* Coarse Aggregate shall meet the requirements of Article 1004.01-1004.02 of the Standard Specifications except the gradation will be limited to CA-11 or CA-14.

SHEET B4 OF 8

CHECKED BY: SP

				011221 01 01 0		
REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION				
NAME	DATE	ILLINOIS DEI AINT	MENT OF TRAINS	ONTATION		
		F.A.I. 94 (DAN	I RYAN EXPI	RESSWAY)		
		CTA STATION BAR	RIER WALL MO	DIFICATIONS		
		79TH STREET STATION				
		REFACED BARRIE	ER TO PIER TI	RANSITION		
		DETAILS. PI	LAN AND ELEV	ATTON		
		DETAILS: IT	LAN AND ELEV	AITON		
		SCALE: NONE	DRAWN BY	: MPG		

DATE: MARCH 1, 2006

TYLININTERNATIONAL