


RTE. SECTION COUNTY SHEETS NO.

338 E-1-14-1-2 DUPAGE 12 10

FED. MOND DIST. NO. 1 |LLINOIS | FED. AID PROJECT







SECTION THRU WELDED RAIL EXP. JOINT

(445 Studs Required) (297 Anchor Plates Required)

Edge Rails.

be allowed.


shall be followed.

and stage construction joints.


SECTION THRU ROLLED RAIL EXP. JOINT

(742 Studs Required)


Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs.. automatically end welded.




TYPICAL END TREATMENTS



LOCKING EDGE RAILS




LOCKING EDGE RAIL SPLICE The inside of the locking edge rail proove shall be free of weld residue.



ROLLED (EXTRUDED) RAIL

AT CURB. PARAPET, OR WALL



AT SIDEWALK OR MEDIAN

Sharter plotes with a single row of studs at 12" centers may be necessary on medians which ore shallower than 9". See manufacturer's

BRIDGE JOINT SYSTEM - EXPANSION (STRIP SEAL)

GENERAL NOTES The strip seal shall be made continuous and shall have a minimum thickness of 4". The configuration of the

strip seal shall match the configuration of the Locking

The height and thickness of the Locking Edge Rails shown are minimum dimensions. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not

Locking Edge Rails may be spliced at slope discontinuities

The manufacturer's recommended installation methods

The joint opening and deck dimensions detailed on the superstructure are based on a preformed joint seal. If the contractor elects to use the alternate strip seal joint, the opening and deck dimensions shall be modified according to the dimensions detailed on this sheet. Required modifications shall be made at no additional cost to the State.

REVISIONS ILLINOIS DEPARTMENT OF TRANSPORTATION IL 59 OVER I-88 BRIDGE STRIP SEAL DETAILS SN 022-9900 SCALE: NONE DRAWN BY: SHE DATE: 2/10/06

CHECKED BY:

MODIFIED EJ-BJS

10-22-04