

April 19, 2006

SUBJECT: Various Routes Section D4 Sign Truss Repair 2006 Knox County Contract No. 68597 Item No. 139, 4-28-2006 Letting Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

- 1. Revised page 6 of the Special Provisions.
- 2. Revised sheet 7 of the plans.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

Michael L. Hine Engineer of Design and Environment

Tette aluchagen A.E.

By: Ted B. Walschleger, P. E. Engineer of Project Management

cc: J. E. Crowe, Region 3, District 4; Roger Driskell; R. E. Anderson Estimates; Design & Environment File

RS/sar

DISCONNECT AND RECONNECT ELECTRIC SERVICE

This work shall consist of disconnecting and reconnecting electrical service to the sign lighting for an overhead sign structure to be removed. Disconnect the electric cable to the sign lighting, pulling and coiling the cable so it will not be damaged during the removal of the overhead sign structure.

For those locations where the end supports are to be removed, the electric cable shall be removed from the end support and coiled so it will not be damaged during the removal of the end support.

Once the replacement end supports or overhead sign structure has been erected, the electric cable shall be reinstalled and connected to the sign lighting. After all connections have been completed to the satisfaction of the Engineer, electric service shall be restored to the overhead sign structure.

<u>Basis of Payment</u>: This work will be paid for at the contract unit price each for DISCONNECT AND RECONNECT ELECTRIC SERVICE, which price shall be payment in full for completing the work described above and providing all necessary traffic control.

OVERHEAD SIGN STRUCTURE – END SUPPORT

This work shall consist of furnishing all necessary labor and materials to replace deteriorated or damaged end support(s) and washers for an overhead sign structure-span or cantilever. Any existing sign panel(s) attached to the end support shall be removed and reinstalled and a structure number shall be installed on the new end support when required.

The Contractor shall carefully remove the existing anchor bolt nuts so as not to damage the existing anchor rods, since these will be reused to install the new overhead sign structure end support(s).

This work shall be done in accordance with the applicable requirements of Section 733 and as specified herein.

Materials shall conform to the requirements of the sign structure detail sheets submitted for each location and the applicable requirements of Section 733.

Shop drawings for the replacement end supports will be provided by the Contractor and approved in writing before any new materials are ordered.

The removed damaged or deteriorated end support shall become the property of the Contractor and shall be completely removed from the right-of-way.

6