



**GENERAL NOTES**

Type III Barricades and R11-2 signs shall be positioned as shown in "Road Closed To All Traffic" detail on Highway Standard 702001.

Two Type A Low Intensity Flashing Lights shall be used on each approach in advance of the work area during hours of darkness. One light shall be installed above the barricades and the other above the first advance warning sign.

All signs shall be post mounted if the closure time exceeds four days.

All warning signs shall have minimum dimensions of 36" by 36" and have a black legend on an orange reflectorized background.

All work zone signs are required to meet, as a minimum, Type B reflectivity requirements of Table 1091-2 in Article 1091.02 of the Standard Specifications.

Longitudinal dimensions may be adjusted to fit field conditions.

When the distance between the barricade and the intersection is between 1500' and 2000', the advance sign shall be placed at the intersection. When the distance between the barricade and the intersection is over 2000', an additional sign shall be placed at the intersection. The additional sign shall give the distance to the barricade in miles or fractions of a mile.

When fluorescent signs are used, orange flags are not required.

**LEGEND**

- WORK AREA
- TYPE III BARRICADE WITH FLASHING LIGHT
- SIGN WITH 18-IN BY 18-IN (minimum) ORANGE FLAG ATTACHED

NOTE: SEE SPECIAL PROVISIONS FOR TRAFFIC CONTROL INFORMATION

**MAINTENANCE OF TRAFFIC PLAN  
FELL AVENUE  
BRIDGE REPLACEMENT**

DRAWN MH 10-6-03      DESIGNED MH 10-6-04  
 CHECKED LDK 10-25-04      CHECKED LDK 10-25-04  
 FILE: 03S2019      DATE: 2-2-05