



PROPOSED HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"  
 PROPOSED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70, 1 1/2"  
 PROPOSED POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL-4.75, N50, 3/4"

**LEGEND**

- ① THERMOPLASTIC PAVEMENT MARKING  
EDGE LINE, 4" SOLID WHITE
- ② THERMOPLASTIC PAVEMENT MARKING  
12" SOLID WHITE DIAGONALS
- ③ THERMOPLASTIC PAVEMENT MARKING  
6" WHITE TURN LANE LINE
- ④ THERMOPLASTIC PAVEMENT MARKING  
4" YELLOW SOLID CENTERLINE
- ⑤ THERMOPLASTIC PAVEMENT MARKING  
4" YELLOW NO PASSING LINE
- ⑥ THERMOPLASTIC PAVEMENT MARKING  
6" WHITE SOLID CROSSWALK LINE
- ⑦ THERMOPLASTIC PAVEMENT MARKING  
24" WHITE STOP BAR
- ⑧ THERMOPLASTIC PAVEMENT MARKING  
LETTERS AND SYMBOLS, WHITE
- ⑨ THERMOPLASTIC PAVEMENT MARKING  
8" WHITE MEDIAN BORDER
- ⑩ THERMOPLASTIC PAVEMENT MARKING, 6"  
2'-6' WHITE DOTTED

\* REFER TO RAISED REFLECTIVE PAVEMENT MARKER  
(SNOW PLOW RESISTANT) DETAIL FOR LOCATION AND  
SPACING OF LANE LINE, CENTERLINE AND  
CHANNELIZATION PAVEMENT MARKERS.

**NOTE:**

1. ALL PAVEMENT MARKING SHALL BE THERMOPLASTIC UNLESS OTHERWISE NOTED. SEE DISTRICT DETAIL TC-13, TC-24
2. RAISED REFLECTIVE PAVEMENT MARKERS SHALL BE USED THROUGH THE IMPROVEMENT LIMITS. DOUBLE LANE LINE MARKERS SHALL BE INSTALLED. SEE DISTRICT DETAIL TC-11

FILE NAME =	USER NAME = bgunsh	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>US 30 ROADWAY &amp; PAVEMENT MARKING PLAN</b>		F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
ca:\pwork\p1001\BYUNSH\dms92972\sh...		DRAWN -	REVISED -		SCALE: 1"=50'	SHEET NO. OF SHEETS	STA. 0+00 TO STA. 30+00	349	15 RS-11	WILL	25	7
		CHECKED -	REVISED -									
		DATE -	REVISED -									
							CONTRACT NO. 60E68					
							ILLINOIS FED. AID PROJECT					