

ROUTE		SECTION	COUNTY	SHEET	
F.A.P.	VAR.	*	PEORIA	TOTAL	NO.
MKD.	IL 90			100	83

\* (108X, 130, 102)RS-3; 129RS-4, 101RS-2

	STATION	TYPE OF ENTRANCE	INCIDENTAL HMA SURFACE COURSE, 1 1/2"				HMA SURFACE REMOVAL BUTT JOINT		POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)	AGGREGATE SURFACE COURSE, 1 1/2"			
			WIDTH (FT)	LENGTH (FT)	AREA (SQ. YD)	TONS	AREA	(SQ. YD)	TONS	WIDTH (FT)	LENGTH (FT)	AREA (SQ. YD)	TONS
RT	54 + 50	PE	20	5	11.1	0.9	11.1		14	5	7.8	0.7	
LT	54 + 85	FE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
LT	60 + 32	FE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
LT	74 + 00	FE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
RT	85 + 95	PE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
LT	86 + 42	PE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
RT	89 + 51	FE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
RT	101 + 07	FE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
RT	101 + 87	PE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
LT	102 + 23	PE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
LT	114 + 58	FE	20	5	11.1	0.9	11.1	0.005	14	5	7.8	0.7	
<b>TR 58</b>													
LT	53 + 44		50	30	166.7	14.0	166.7	0.069					
RT	53 + 44		31.5	30	105.0	8.8	105.0	0.044					
<b>CH 59</b>													
LT	107 + 20		72	20	160.0	13.4	160.0	0.067					
RT	107 + 20		74	20	164.4	13.8	164.4	0.068					
<b>TR 76</b>													
LT	159 + 54		30	20	66.7	5.6	66.7	0.028					
RT	159 + 54		30	20	66.7	5.6	66.7	0.028					
<b>TWP RD.</b>													
LT	210 + 94		37.5	20	83.3	7.0	83.3	0.035					
RT	210 + 94		37.5	20	83.3	7.0	83.3	0.035					
<b>TR 126</b>													
LT	261 + 93		40	20	88.9	7.5	88.9	0.037					
RT	261 + 93		35	20	77.8	6.5	77.8	0.032					
<b>Ch 31</b>													
RT	288 + 30		60	40	266.7	22.4	266.7	0.111					
<b>TR 130</b>													
LT	310 + 57		35	20	77.8	6.5	77.8	0.032					
RT	310 + 57		52	20	115.6	9.7	115.6	0.048					
<b>TR 40</b>													
LT	46 + 90		65	20	144.4	12.1	144.4	0.060					
RT	46 + 90		30	20	66.7	5.6	66.7	0.028					
<b>MAILBOX TURNOUTS</b>					8 LOCATIONS SEE HIGHWAY STANDARD		25.6	17.2	204.4	0.085			
<b>SUB-TOTALS</b>							1882	173	2061	0.9			7
<b>TOTAL =</b>							228	2716 *	1.1 *				47

\* Subtotal for incidental HMA surface course areas, for additional quantities see sheet 15

**APPLICATION RATE (POLY PRIME)**

0.1 Gal./Sq. Yd. on Cold Milled Surface

.05 Gal./Sq. Yd. on Shoulder Overlay

.03 Gal./Sq. Yd. Fog Coat on New Binder

**TABULATION OF  
RESURFACING  
QUANTITIES  
(SHEET 6 OF 6)**