

SCHEDULE OF QUANTITIES

PROPOSED GUARDRAIL SCHEDULE																								
STRUCTURE	STATION	SIDE	APP/DEP.	63100087		63100087				78201000	63000005			63000001			63000025				782000410			
				TRAFFIC BARRIER TERMINAL, TYPE 6A		TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT				TERMINAL MARKER DIR. APPLIED	STEEL PLATE BEAM GUARDRAIL, TYPE B			STEEL PLATE BEAM GUARDRAIL TYPE A, 6 FOOT POSTS			STEEL PLATE BEAM GUARDRAIL ATTACH TO STRUCTURE				GUARDRAIL MARKER			
				STATION	(EACH)	STATION	TO	STATION	(EACH)	(EACH)	STATION	TO	STATION	LENGTH (FOOT)	STATION	TO	STATION	LENGTH (FOOT)	STATION	TO	STATION	LENGTH (FOOT)	TYPE A EACH	
S.N. 057-8214	1676+43.00	RT	APP			1675+43.00	TO	1674+93.00	1.0	1.0	1676+30.50	TO	1676+05.50	25.0	1675+43.00	TO	1676+05.50	62.5	1676+30.50	TO	1676+55.50	2.0		
	1676+43.00	RT	DEP			1676+80.50	TO	1677+30.50	1.0	1.0	1676+55.50	TO	1676+80.50	25.0								2.0		
	1676+43.00	LT	APP			1677+43.00	TO	1677+93.00	1.0	1.0	1676+55.50	TO	1676+80.50	25.0	1677+43.00	TO	1676+80.50	62.5	1676+30.50	TO	1676+55.50	2.0		
	1676+43.00	LT	DEP			1676+05.50	TO	1675+55.50	1.0	1.0	1676+30.50	TO	1676+05.50	25.0								2.0		
S.N. 057-8165	1716+57.00	RT	APP			1716+19.50	TO	1715+69.50	1.0	1.0	1716+44.50	TO	1716+19.50	25.0					1716+44.50	TO	1716+69.50	2.0		
	1716+57.00	RT	DEP			1716+82.00	TO	1717+32.00	1.0	1.0	1716+69.50	TO	1716+82.00	12.5								2.0		
	1716+57.00	LT	APP			1716+94.50	TO	1717+44.50	1.0	1.0	1716+69.50	TO	1716+94.50	25.0					1716+44.50	TO	1716+69.50	2.0		
	1716+57.00	LT	DEP			1716+32.00	TO	1715+82.00	1.0	1.0	1716+44.50	TO	1716+32.00	12.5								2.0		
S.N. 057-8164	1722+88.00	RT	APP			1722+00.50	TO	1721+50.50	1.0	1.0	1722+75.50	TO	1722+50.50	25.0	1722+00.50	TO	1722+50.50	50.0	1722+75.50	TO	1723+00.50	2.0		
	1722+88.00	RT	DEP			1723+50.50	TO	1724+00.50	1.0	1.0	1723+00.50	TO	1723+25.50	25.0	1723+50.50	TO	1723+25.50	25.0				2.0		
	1722+88.00	LT	APP			1723+75.50	TO	1724+25.50	1.0	1.0	1723+00.50	TO	1723+25.50	25.0	1723+75.50	TO	1723+25.50	50.0	1722+75.50	TO	1723+00.50	2.0		
	1722+88.00	LT	DEP			1722+25.50	TO	1721+75.50	1.0	1.0	1722+75.50	TO	1722+50.50	25.0	1722+25.50	TO	1722+50.50	25.0				2.0		
S.N. 057-8213	1741+62.00	RT	APP			1740+62.00	TO	1740+12.00	1.0	1.0	1741+49.50	TO	1741+24.50	25.0	1740+62.00	TO	1741+24.50	62.5	1741+49.50	TO	1741+74.50	2.0		
	1741+62.00	RT	DEP			1741+99.50	TO	1742+49.50	1.0	1.0	1741+74.50	TO	1741+99.50	25.0								2.0		
	1741+62.00	LT	APP			1742+62.00	TO	1743+12.00	1.0	1.0	1741+74.50	TO	1741+99.50	25.0	1742+62.00	TO	1741+99.50	62.5	1741+49.50	TO	1741+74.50	2.0		
	1741+62.00	LT	DEP			1741+24.50	TO	1740+74.50	1.0	1.0	1741+49.50	TO	1741+24.50	25.0								2.0		
S.N. 057-0076	1917+38.00	RT	APP	1916+57.75	1.0	1914+70.25	TO	1914+20.25	1.0	1.0	1916+57.75	TO	1916+57.75		1914+70.25	TO	1916+57.75	187.5				4.0		
	1917+38.00	RT	DEP	1918+14.01	1.0	1918+89.01	TO	1919+39.01	1.0	1.0	1918+14.01	TO	1918+14.01		1918+89.01	TO	1918+14.01	75.0				4.0		
	1917+38.00	LT	APP	1917+73.18	1.0	1919+60.68	TO	1920+10.68	1.0	1.0	1917+73.18	TO	1917+73.18		1919+60.68	TO	1917+73.18	187.5				4.0		
	1917+38.00	LT	DEP	1916+14.29	1.0	1915+39.29	TO	1914+89.29	1.0	1.0	1916+14.29	TO	1916+14.29		1915+39.29	TO	1916+14.29	75.0				4.0		
S.N. 057-2046	1955+65.00	RT	APP			1954+65.00	TO	1954+15.00	1.0	1.0	1955+52.50	TO	1955+27.50	25.0	1954+65.00	TO	1955+27.50	62.5	1955+52.50	TO	1955+77.50	2.0		
	1955+65.00	RT	DEP			1956+02.50	TO	1956+52.50	1.0	1.0	1955+77.50	TO	1956+02.50	25.0								2.0		
	1955+65.00	LT	APP			1956+02.50	TO	1956+52.50	1.0	1.0	1955+77.50	TO	1956+02.50	25.0					1955+52.50	TO	1955+77.50	2.0		
	1955+65.00	LT	DEP			1955+27.50	TO	1954+77.50	1.0	1.0	1955+52.50	TO	1955+27.50	25.0								2.0		
S.N. 057-2045	1962+55.00	RT	APP			1961+48.75	TO	1960+98.75	1.0	1.0	1962+36.25	TO	1962+11.25	25.0	1961+48.75	TO	1962+11.25	62.5	1962+36.25	TO	1962+73.75	2.0		
	1962+55.00	RT	DEP			1962+98.75	TO	1963+48.75	1.0	1.0	1962+73.75	TO	1962+98.75	25.0								2.0		
	1962+55.00	LT	APP			1963+61.25	TO	1964+11.25	1.0	1.0	1962+73.75	TO	1962+98.75	25.0	1963+61.25	TO	1962+98.75	62.5	1962+36.25	TO	1962+73.75	2.0		
	1962+55.00	LT	DEP			1962+11.25	TO	1961+61.25	1.0	1.0	1962+36.25	TO	1962+11.25	25.0								2.0		
S.N. 057-8212	1981+21.00	RT	APP			1980+21.00	TO	1979+71.00	1.0	1.0	1981+08.50	TO	1980+83.50	25.0	1980+21.00	TO	1980+83.50	62.5	1981+08.50	TO	1981+33.50	2.0		
	1981+21.00	RT	DEP			1981+58.50	TO	1982+08.50	1.0	1.0	1981+33.50	TO	1981+58.50	25.0								2.0		
	1981+21.00	LT	APP			1982+21.00	TO	1982+71.00	1.0	1.0	1981+33.50	TO	1981+58.50	25.0	1982+21.00	TO	1981+58.50	62.5	1981+08.50	TO	1981+33.50	2.0		
	1981+21.00	LT	DEP			1980+83.50	TO	1980+33.50	1.0	1.0	1981+08.50	TO	1980+83.50	25.0								2.0		
				TOTALS =	4.0					32.0	32.0				675.0				1,237.5				375.0	72.0
				USE =	4.0					32.0	32.0				675.0				1,238.0				375.0	72.0