

LOOP DESIGNATION ELF ERF ELE ERE NAP WLT WLB WRE WLE WRF	OF TURNS 4 4 4 4 2-4-2 2-4-2 2 4 4 4 4	CALCI #7 141 138 141 138 141 138 141 138 141 138 141 138	ULATED	MET μη	IERED &	CALCL #1 175 172 162 159 262 391 165 167 178 180	LATED 0 5.38 5.32 3.41 3.35 0.83 3.33 2.90 4.17 4.23 6.08 6.15	METE μη	ERED S
ERF ELE ERE NAP WLT WLB WRE WLE	4 4 4 2-4-2 2-4-2 2 4 4 4	141 138 141 138 261 377 187 138 141	0. 35 0. 29 0. 35 0. 29 0. 79 1. 17 0. 74 0. 29 0. 35 0. 29	μη		175 172 162 159 262 391 201 165 167	5. 38 5. 32 3. 41 3. 35 0. 83 3. 33 2. 90 4. 17 4. 23 6. 08	μη	
ERF ELE ERE NAP WLT WLB WRE WLE	4 4 2-4-2 2-4-2 2 4 4	138 141 138 261 377 187 138 141 138	0. 29 0. 35 0. 29 0. 79 1. 17 0. 74 0. 29 0. 35 0. 29			172 162 159 262 391 201 165 167	5. 32 3. 41 3. 35 0. 83 3. 33 2. 90 4. 17 4. 23 6. 08		
ELE ERE NAP WLT WLB WRE WLE	4 4 2-4-2 2-4-2 2 4 4 4	141 138 261 377 187 138 141 138	0. 35 0. 29 0. 79 1. 17 0. 74 0. 29 0. 35 0. 29			162 159 262 391 201 165 167 178	3. 41 3. 35 0. 83 3. 33 2. 90 4. 17 4. 23 6. 08		
ERE NAP WLT WLB WRE WLE WRF	2-4-2 2-4-2 2 4 4	138 261 377 187 138 141 138	0. 29 0. 79 1. 17 0. 74 0. 29 0. 35 0. 29			159 262 391 201 165 167 178	3. 35 0. 83 3. 33 2. 90 4. 17 4. 23 6. 08		
NAP WLT WLB WRE WLE WRF	2-4-2 2-4-2 2 4 4	261 377 187 138 141 138	0. 79 1. 17 0. 74 0. 29 0. 35 0. 29			262 391 201 165 167 178	0. 83 3. 33 2. 90 4. 17 4. 23 6. 08		
NAP WLT WLB WRE WLE WRF	2-4-2 2 4 4	261 377 187 138 141 138	0. 79 1. 17 0. 74 0. 29 0. 35 0. 29			262 391 201 165 167 178	0. 83 3. 33 2. 90 4. 17 4. 23 6. 08		
WLT WLB WRE WLE WRF	2-4-2 2 4 4	377 187 138 141 138	1. 17 0. 74 0. 29 0. 35 0. 29			391 201 165 167 178	3. 33 2. 90 4. 17 4. 23 6. 08		
WLB WRE WLE WRF	2 4 4 4	187 138 141 138	0. 74 0. 29 0. 35 0. 29			201 165 167 178	2. 90 4. 17 4. 23 6. 08		
WRE WLE WRF	4 4 4	138 141 138	0. 29 0. 35 0. 29			165 167 178	4. 17 4. 23 6. 08		
WLE WRF	4	141 138	0. 35 0. 29			167 178	4. 23 6. 08		
WRF	4	138	0. 29			178	6.08		
	· ·								
WLF		141	0. 35			180	6. 15		
									H
									L_
			_						
						H			
	ı I					H			+
	,					Н			+
									_
						H			
						H			1
						H			+
									-
									_
						Ш			
						LL			L _
						П			
						H			1
						H			_
	 					\vdash			+
	├					H			-
	↓					Н			1
	l					Щ			\perp
						╙ ̄			
	1					l I			
						H			1
	 					\vdash			+
	 					Н			-
						Ц			_
	<u> </u>					Щ			\perp
						1			
	1 1					H			
						Н			+
	├		_			Н	_		+
						Н			_
						Ш			
						l			
						H	_		+
						Н			+
	↓					Ц			_
	<u> </u>					Ш			L
						П			
						H			
	 					\vdash			1
	 					Н			-
						ш_			_
						1			
						H			
			_			\vdash	_		+
						Н	_		+





INSTALLING THE LOOP WIRE:
THE NEGATIVE LEAD SHALL BE CONNECTED TO THE BLACK CONDUCTOR
OF A PAIR OF CONDUCTORS IN THE LEAD-IN CABLE AND THE POSITIVE
LEAD SHALL BE CONNECTED TO THE COLOR-CODED CONDUCTOR OF
THE CABLE PAIR.

DETECTOR LOOP WIRE INSTALLATION

DETECTOR NOTES:

- 1. THE DETECTOR LOOP SHALL BE CENTERED IN THE LANE IN WHICH IT IS SHOWN.
 ANY ADJUSTMENTS ARE TO BE MADE ONLY AT THE DIRECTION OF THE ENGINEER.
 2. THE DETECTOR LOOPS SHALL CONSIST OF THE NUMBER OF TURNS AS SHOWN
 IN THE PLANS OR AS DIRECTED BY THE ENGINEER.
 3. ACCEPTANCE OF THE LOOPS AS METERED SHALL BE DETERMINED BY THE ENGINEER.
- 4. ALL DETECTOR WIRES SHALL BE MARKED WITH WATERPROOF LABELS USING THE WIRING IDENTIFICATION SHOWN ON THE PLANS. THE + AND OF EACH LOOP MUST BE USED TO IDENTIFY CURRENT FLOW. ALWAYS CONNECT THE BLACK WIRE OF EACH PAIR TO THE NEGATIVE (-) LOOP WIRE.
- 5. ALL QUADRAPOLE LOOPS SHALL BE 2-4-2 DESIGN.

* - (107Z)RS-8, (B-19)RS-4

FILE NAME =	USER NAME = laughlinrl	DESIGNED -	REVISED -				[1	F.A.P.	SECTION	COUNTY	TOTAL SH SHEETS N	įΕΠ
c:\pw_work\PWIDOT\LAUGHLINRL\dma21748\D	672C98-sht-ts.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS		TRAFFIC SIGNAL DETECTOR LOOP DETAILS		67	•	Sanaamon	28	. 7
	PLOT SCALE = 40.00000 '/ IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION				CONTRACT			NO. 720	98
	PLOT DATE = Apr-10-2009 01:46:13PM	DATE -	REVISED -		SCALE:	SHEET NO. 3 OF 4 SHEETS STA. TO STA		FED. ROAD DIST. NO				