

RESURFACING SCHEDULE			LENGTH	AVERAGE PAVEMENT WIDTH	AREA	HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH	HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"	HOT-MIX ASPHALT SURFACE REMOVAL, 3 3/4"	BITUMINOUS MATERIALS (PRIME COAT)	AGGREGATE (PRIME COAT)	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N90	LEVELING BINDER (MACHINE METHOD), N70	LEVELING BINDER (MACHINE METHOD), N90	HOT-MIX ASPHALT SHOULDERS	AGGREGATE SHOULDERS, TYPE B	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	TEMPORARY RAMP
151+00.00	TO 151+35.00	35.0	26.0	910.0	25.6	0.0	0.0	0.0	17.9	0.4	8.5	0.0	2.1	0.0	9.8	2.3	153.3	25.6	
151+35.00	TO 154+00.00	265.0	26.0	6890.0	1354.4	0.0	0.0	0.0	135.4	2.7	64.3	0.0	32.2	0.0	74.2	17.6	0.0	0.0	
154+00.00	TO 157+15.00	315.0	26.0	8190.0	1435.0	0.0	0.0	0.0	143.5	2.9	76.4	0.0	38.2	0.0	66.2	20.9	0.0	0.0	
157+15.00	TO 157+50.00	35.0	26.0	910.0	0.0	0.0	140.0	0.0	14.0	0.3	8.5	0.0	4.2	0.0	4.9	2.3	0.0	0.0	
157+50.00	TO 172+50.00	1500.0	26.0	39000.0	0.0	1666.7	6000.0	0.0	600.0	12.0	364.0	0.0	182.0	0.0	140.0	0.0	0.0	9.8	
172+50.00	TO 172+85.00	35.0	26.0	910.0	0.0	0.0	140.0	0.0	14.0	0.3	8.5	0.0	4.2	0.0	4.9	1.6	0.0	0.0	
172+85.00	TO 178+65.00	580.0	26.0	15080.0	2320.0	0.0	0.0	0.0	232.0	4.6	140.7	0.0	70.4	0.0	81.2	19.9	0.0	0.0	
178+65.00	TO 179+00.00	35.0	26.0	910.0	20.0	0.0	0.0	0.0	14.0	0.3	8.5	0.0	4.2	0.0	4.9	1.6	120.0	20.0	
179+00.00	TO 182+99.20	399.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
182+99.20	TO 203+18.00	2018.8	26.0	52488.8	0.0	2243.1	8075.2	0.0	807.5	16.2	489.9	0.0	244.9	0.0	188.4	0.0	0.0	62.0	
203+18.00	TO 220+65.00	1747.0	26.0	45422.0	0.0	1941.1	6988.0	0.0	698.8	14.0	423.9	0.0	212.0	0.0	163.1	0.0	0.0	47.1	
220+65.00	BK= 219+77.00 AH	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
219+77.00	TO 220+12.00	35.0	26.0	910.0	0.0	0.0	101.1	0.0	10.1	0.2	8.5	0.0	4.2	0.0	0.0	2.3	0.0	0.0	
220+12.00	TO 239+82.00	1970.0	26.0	51220.0	5691.1	0.0	0.0	0.0	569.1	11.4	478.1	0.0	239.0	0.0	0.0	121.5	0.0	0.0	
239+82.00	TO 244+25.00	443.0	36.0	15948.0	1772.0	0.0	0.0	0.0	177.2	3.5	148.8	0.0	74.4	0.0	0.0	29.4	0.0	0.0	
244+25.00	TO 250+45.00	620.0	42.0	26040.0	2893.3	0.0	0.0	0.0	289.3	5.8	243.0	0.0	121.5	0.0	0.0	33.0	0.0	0.0	
250+45.00	TO 253+84.00	339.0	36.0	12204.0	1356.0	0.0	0.0	0.0	135.6	2.7	113.9	0.0	57.0	0.0	0.0	22.5	0.0	0.0	
253+84.00	TO 357+22.00	10338.0	26.0	268788.0	29865.3	0.0	0.0	0.0	2986.5	59.7	2508.7	0.0	1254.3	0.0	0.0	666.0	0.0	0.0	
357+22.00	TO 368+67.00	1145.0	26.0	29770.0	3562.2	0.0	0.0	0.0	356.2	7.1	277.9	0.0	138.9	0.0	32.1	75.0	0.0	0.0	
368+67.00	TO 379+00.00	1033.0	26.0	26858.0	2984.2	0.0	0.0	0.0	298.4	6.0	250.7	0.0	125.3	0.0	0.0	65.8	0.0	0.0	
379+00.00	TO 388+52.00	952.0	26.0	24752.0	2961.8	0.0	0.0	0.0	296.2	5.9	231.0	0.0	115.5	0.0	26.7	59.5	0.0	0.0	
388+52.00	TO 407+85.00	1933.0	26.0	50258.0	5584.2	0.0	0.0	0.0	558.4	11.2	469.1	0.0	234.5	0.0	0.0	120.5	0.0	0.0	
407+85.00	TO 408+50.00	65.0	26.0	1690.0	0.0	0.0	0.0	187.8	18.8	0.4	15.8	0.0	7.9	0.0	0.0	4.3	0.0	0.0	
408+50.00	TO 412+60.00	410.0	26.0	10660.0	0.0	0.0	0.0	1184.4	118.4	2.4	99.5	0.0	49.7	0.0	0.0	0.0	0.0	29.6	
412+60.00	TO 413+25.00	65.0	26.0	1690.0	0.0	0.0	0.0	187.8	18.8	0.4	15.8	0.0	7.9	0.0	0.0	4.3	0.0	0.0	
413+25.00	TO 439+30.00	2605.0	26.0	67730.0	7525.6	0.0	0.0	0.0	752.6	15.1	632.1	0.0	316.1	0.0	0.0	169.4	0.0	0.0	
439+30.00	TO 440+85.00	155.0	26.0	4030.0	585.6	0.0	0.0	0.0	58.6	1.2	37.6	0.0	18.8	0.0	17.4	9.3	0.0	0.0	
440+85.00	TO 441+50.00	65.0	26.0	1690.0	0.0	0.0	0.0	245.6	24.6	0.5	15.8	0.0	7.9	0.0	7.3	4.3	0.0	0.0	
441+50.00	TO 442+56.00	106.0	26.0	2756.0	0.0	0.0	0.0	353.3	35.3	0.7	25.7	0.0	12.9	0.0	5.9	0.0	0.0	0.0	
442+56.00	TO 445+70.00	314.0	26.0	8164.0	0.0	0.0	0.0	907.1	90.7	1.8	76.2	0.0	38.1	0.0	0.0	0.0	0.0	0.0	
445+70.00	TO 453+88.00	818.0	26.0	21268.0	0.0	0.0	0.0	2363.1	236.3	4.7	198.5	0.0	99.3	0.0	0.0	0.0	0.0	42.9	
453+88.00	TO 454+53.00	65.0	26.0	1690.0	0.0	0.0	0.0	187.8	18.8	0.4	15.8	0.0	7.9	0.0	0.0	4.3	0.0	0.0	
454+53.00	TO 467+85.00	1332.0	26.0	34632.0	3848.0	0.0	0.0	0.0	384.8	7.7	323.2	0.0	161.6	0.0	0.0	88.5	0.0	0.0	
467+85.00	TO 468+50.00	65.0	26.0	1690.0	0.0	0.0	0.0	187.8	18.8	0.4	15.8	0.0	7.9	0.0	0.0	4.3	0.0	0.0	
468+50.00	TO 472+30.00	380.0	26.0	9880.0	0.0	0.0	0.0	1097.8	109.8	2.2	92.2	0.0	46.1	0.0	0.0	0.0	0.0	0.0	
472+30.00	TO 472+95.00	65.0	26.0	1690.0	0.0	0.0	0.0	187.8	18.8	0.4	15.8	0.0	7.9	0.0	0.0	4.3	0.0	0.0	
472+95.00	TO 504+86.00	3191.0	26.0	82966.0	9218.4	0.0	0.0	0.0	921.8	18.4	774.3	0.0	387.2	0.0	0.0	208.9	0.0	0.0	

FILE NAME =
 USER NAME = swartzrw
 DRAWN -
 CHECKED -
 DATE -
 PLOT SCALE = 20.0000" / IN.
 PLOT DATE = 4/10/2009

DESIGNED -
 REVISIONS -
 REVISIONS -
 REVISIONS -
 REVISIONS -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

SCHEDULE OF QUANTITIES
 SCALE: NA SHEET NO. 3 OF 5 SHEETS STA. TO STA.

• COLES AND CUMBERLAND COUNTIES
 F.A.P. RTE. SECTION COUNTY TOTAL SHEETS SHEET NO.
 116 (111,112,113-1)RS-6 20 13
 CONTRACT NO. 74262
 ILLINOIS FED. AID PROJECT