




NOTE: MEDIANS WITH BARRIER CURB DO NOT REQUIRE AN EDGE LINE


TYPICAL LANE AND EDGE LINE MARKING




TYPICAL CROSSWALK MARKING



MEDIANS OVER 4' (1.2 m) WIDE





TYPICAL PAINTED MEDIAN MARKING



FULL SIZE LETTERS 8' (2.4 m) AND ARROWS SHALL BE USED.  
 \* TURN LANES IN EXCESS OF 400' (120 m) IN LENGTH MAY HAVE AN ADDITIONAL SET OF ARROW - "ONLY" INSTALLED MIDWAY BETWEEN THE OTHER TWO SETS OF ARROW - "ONLY".

TYPICAL LEFT (OR RIGHT) TURN LANE

TYPICAL TURN LANE MARKING



TYPICAL ISLAND MARKING

| TYPE OF MARKING   | WIDTH OF LINE  | PATTERN                 | COLOR   | SPACING / REMARKS  |
|---|--|-------------------------|---|--|
| CENTERLINE ON 2 LANE PAVEMENT   | 4 (100)  | SKIP-DASH               | YELLOW  | 10' (3 m) LINE WITH 30' (9 m) SPACE  |
| CENTERLINE ON MULTI-LANE UNDIVIDED PAVEMENT   | 2 @ 4 (100)  | SOLID                   | YELLOW  | 11 (280) C-C   |
| NO PASSING ZONE LINES: FOR ONE DIRECTION  | 4 (100)  | SOLID                   | YELLOW  | 5 1/2 (140) C-C FROM SKIP-DASH CENTERLINE  |
| NO PASSING ZONE LINES: FOR BOTH DIRECTIONS  | 2 @ 4 (100)  | SOLID                   | YELLOW  | 11 (280) C-C OMIT SKIP-DASH CENTERLINE BETWEEN   |
| LANE LINES  | 4 (100)  | SKIP-DASH               | WHITE   | 10' (3 m) LINE WITH 30' (9 m) SPACE  |
| DOTTED LINES (EXTENSIONS OF CENTER, LANE OR TURN LANE MARKINGS)                                   | 5 (125) ON FREEWAYS  | SKIP-DASH               | WHITE   |  |
| EDGE LINES  | 4 (100)  | SOLID                   | YELLOW-LEFT<br>WHITE-RIGHT                              | 2' (600) LINE WITH 6' (1.8 m) SPACE  |
| TURN LANE MARKINGS  | 6 (150) LINE; FULL SIZE LETTERS & SYMBOLS 18" (2.4m)                                       | SOLID                   | WHITE   | OUTLINE MOUNTABLE MEDIANS IN YELLOW; EDGE LINES ARE NOT USED NEXT TO BARRIER CURB  |
| TWO WAY LEFT TURN MARKING   | 2 @ 4 (100) EACH DIRECTION   | SKIP-DASH AND SOLID     | YELLOW  | SEE TYPICAL TURN LANE MARKING DETAIL   |
|   | 8' (2.4m) LEFT ARROW   | IN PAIRS                | WHITE   | SEE TYPICAL TWO-WAY LEFT TURN MARKING DETAIL   |
| CROSSWALK LINES (PEDESTRIAN)<br>A. DIAGONALS (BIKE & EQUESTRIAN)<br>B. LONGITUDINAL BARS (SCHOOL) | 2 @ 6 (150)<br>12 (300) @ 45°<br>12 (300) @ 90°  | SOLID<br>SOLID<br>SOLID | WHITE<br>WHITE<br>WHITE                                 | NOT LESS THAN 6' (1.8 m) APART<br>2' (600) APART<br>2' (600) APART<br>SEE TYPICAL CROSSWALK MARKING DETAILS.   |
| STOP LINES  | 24 (600)   | SOLID                   | WHITE   | PLACE 4' (1.2 m) IN ADVANCE OF AND PARALLEL TO CROSSWALK, IF PRESENT. OTHERWISE, PLACE AT DESIRED STOPPING POINT, PARALLEL TO CROSSROAD CENTERLINE, WHERE POSSIBLE |
| PAINTED MEDIANS   | 2 @ 4 (100) WITH 12 (300) DIAGONALS @ 45°<br>NO DIAGONALS USED FOR 4' (1.2 m) WIDE MEDIANS | SOLID                   | YELLOW:<br>TWO WAY TRAFFIC<br>WHITE:<br>ONE WAY TRAFFIC | 11 (280) C-C FOR THE DOUBLE LINE<br>SEE TYPICAL PAINTED MEDIAN MARKING.  |
| GORE MARKING AND CHANNELIZING LINES   | 8 (200) WITH 12 (300) DIAGONALS @ 45°  | SOLID                   | WHITE   | DIAGONALS:<br>15' (4.5 m) C-C (LESS THAN 30MPH (50 km/h))<br>20' (6 m) C-C (30MPH (50 km/h) TO 45MPH (70 km/h))<br>30' (9 m) C-C (OVER 45MPH (70 km/h))            |
| RAILROAD CROSSING   | 24 (600) TRANSVERSE LINES; "RR" 15' (4.5 m) LETTERS; 16 (400) LINE FOR "X"                 | SOLID                   | WHITE   | SEE STATE STANDARD 780001<br>AREA OF:<br>"R"=3.6 SQ. FT. (0.33 m²) EACH<br>"X"=54.0 SQ. FT. (5.0 m²)   |
| SHOULDER DIAGONALS  | 12 (300) @ 45°   | SOLID                   | WHITE - RIGHT<br>YELLOW - LEFT                          | 50' (15 m) C-C (LESS THAN 30MPH (50 km/h))<br>75' (25 m) C-C (30 MPH (50 km/h) TO 45MPH (70 km/h))<br>150' (45 m) C-C (OVER 45MPH (70 km/h))                       |

FOR FURTHER DETAILS ON PAVEMENT MARKING REFER TO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND STATE STANDARD 780001.

All dimensions are in inches (millimeters) unless otherwise shown.

|   |                           |                  |                                 |
|---|---------------------------|------------------|---------------------------------|
| FILE NAME =                                       | USER NAME = drivakosgn    | DESIGNED - EVERS | REVISED - T. RAMMACHER 10-27-94 |
| c:\pwwork\pwwork\drivakosgn\10108315\10108315.dgn |                           | DRAWN -          | REVISED - C. JUCCIUS 09-09-09   |
|   | PLOT SCALE = 50.000 / IN. | CHECKED -        | REVISED -                       |
|   | PLOT DATE = 9/9/2009      | DATE - 03-19-90  | REVISED -                       |

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

|                           |                         |              |  |
|---------------------------|-------------------------|--------------|--|
| DISTRICT ONE              |                         |              |  |
| TYPICAL PAVEMENT MARKINGS |                         |              |  |
| SCALE: NONE               | SHEET NO. 1 OF 1 SHEETS | STA. TO STA. |  |

|  |                |                    |              |           |
|--|----------------|--------------------|--------------|-----------|
| F.A. RTE.  | SECTION        | COUNTY             | TOTAL SHEETS | SHEET NO. |
| *  | 09-00058-00-CH | MCHENRY            | 53           | 41        |
| TC-13  |                | CONTRACT NO. 63381 |              |           |
| FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT ARA-9003 (635) |                |                    |              |           |