

GENERAL NOTES

The final top four inches of soil in any right-of-way area disturbed by the Contractor must be capable of supporting vegetation. The soil must be from the A horizon (zero to 2' deep) of soil profiles of local soils.

All Borrow/Waste/Use sites must be approved by the Department prior to removing any material from the project or initiating any earthmoving activities, including temporary stockpiling outside the limits of construction.

The Contractor shall seed all disturbed areas within the project limits. Seeding Class 4 or 2A shall be used, except in front of properties where the grass will be mowed, then use Seeding, Class 1. Class 2A shall be used on front slopes and ditch bottoms. Class 4 shall be used behind Type A gutter, on all backslopes and areas behind the backslope, and beyond the toe of front slope on fill sections without ditches. This work will be included in the contract unit price per Cubic Yard for CONCRETE REMOVAL.

Fertilizer shall be applied to all disturbed areas and incorporated into the seedbed prior to seeding or placement of sod at the rate specified in Sections 250 and 252 of the Standard Specifications. This work shall be included in the cost of CONCRETE REMOVAL.

Mulch Method II shall be applied over all seeded areas. This shall be included in the cost of the CONCRETE REMOVAL.

At bridge expansion joints, if temporary expansion joint bulkheads are attached to adjacent deck slabs or abutments for support, the Contractor shall cut the attachments as soon as the concrete has set to prevent joint damage due to horizontal contraction or expansion.

The Contractor shall be responsible for protecting utility property during construction operations as outlined in Article 107.31 of the Standard Specifications. A minimum of 48 hours advance notice is required for non-emergency work. The JULIE number is 800-892-0123.

INDEX OF SHEETS

1. Cover Sheet
2. Summary of Quantities
3. General Notes, Index of Sheets, Standards
4. - 7. Traffic Control Plan
8. - 10. Bridge Repairs Structure No. 071-0015
11. - 15. Bridge Repairs Structure No. 071-0072
16. To Activate Signal Sign Detail

STANDARDS

- 701006-03 Off-Road Operations, 2L, 2W, 4.5 m (15') to 600 mm (24") From Pavement Edge
- 701201-03 Lane Closure, 2L, 2W, Day Only, for Speeds > 45 MPH
- 701301-03 Lane Closure, 2L, 2W, Short Time Operations
- 701321-10 Lane Closure, 2L, 2W, Bridge Repair with Barrier
- 701901-01 Traffic Control Devices
- 704001-06 Temporary Concrete Barrier
- 720001-01 Sign Panel Mounting Details
- 720006-02 Sign Panel Erection Details
- 720011-01 Metal Posts for Signs, Markers and Delineators
- 728001-01 Telescoping Steel Sign Support
- 729001-01 Applications of Types A and B Metal Posts (For Signs & Markers)

FILE NAME = G:\BR\CADD plans\Various Counties\64G13				USER NAME = linkdj				DESIGNED - ---				REVISED - ---				STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION				GENERAL NOTES, INDEX OF SHEETS, STANDARDS				F.A. RTE.:		SECTION		COUNTY		TOTAL SHEETS		SHEET NO.	
				DRAWN - ---				REVISED - ---				*		(102BRIM & (39BRIM										OGLE		19		3					
				PLDT SCALE = 50.0000' / IN.				CHECKED - ---				REVISED - ---												CONTRACT NO. 64G13									
				PLDT DATE = Tue Mar 16 08:27:17 2010				DATE - ---				REVISED - ---												ILLINOIS FED. AID PROJECT									
																SCALE: _____ SHEET NO. ___ OF ___ SHEETS STA. _____ TO STA. _____																	

* FAP 17 (IL 64) & FAP 742 (IL 2)