

GENERAL NOTES

THE ENGINEER WILL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE MICRO-SURFACING LIFT.

FOR STABILIZATION, ALL TYPE III BARRICADES SHALL REQUIRE A MINIMUM OF FOUR SAND BAGS PER BARRICADE.

SHORT TERM PAVEMENT MARKING SHALL BE USED TO OUTLINE THE SHOULDERS WHENEVER THE EDGE LINE IS NOT IN PLACE. THE SHORT-TERM PAVEMENT MARKING SHALL BE PLACED AS SPECIFIED IN ARTICLE 709.04 OF THE STANDARD SPECIFICATIONS.

ON EXISTING PAVEMENT WHICH MAY BE SUPERELEVATED, THE NEW MICRO-SURFACING SHALL BE BUILT WITH THE SAME SUPERELEVATION UNLESS NEW SUPERELEVATION RATES ARE GIVEN ON THE PLANS.

ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION AS INDICATED BY THE SUBNUMBER SHOWN IN THE LIST OF STANDARDS OR THE COPY INCLUDED IN THESE PLANS.

THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN CALCULATING PLAN QUANTITIES:

MICRO-SURFACING, SINGLE PASS, TYPE II	20	LBS / SQ YD MIXTURE D
SHORT TERM PAVEMENT MARKING	4	FT /100 FT OF APPLICATION

DATE: 4/1/10

PREPARED BY: Tom Brown
ACTING DISTRICT STUDIES & PLANS ENGINEER

EXAMINED BY: Herbert K. Long
DISTRICT CONSTRUCTION ENGINEER

Wayne J. Phillips
DISTRICT MATERIALS ENGINEER

Bruce A. Huesler
DISTRICT OPERATIONS ENGINEER