

INDEX OF SHEETS

GENERAL NOTES

- ① WHERE SECTION OR SUBSECTION MONUMENTS ARE ENCOUNTERED, THE ENGINEER SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL PROPERTY MARKS, MONUMENTS, AND PERMANENT SURVEY MARKERS UNTIL THE OWNER, AND AUTHORIZED SURVEYOR OR AGENT HAS WITNESSES OR OTHERWISE REFERENCED THEIR LOCATION.
- ② THE NOMINAL THICKNESS FOR BASE AND SURFACE COURSES ARE SHOWN ON THE TYPICAL SECTIONS, STANDARDS, SCHEDULES, OR SPECIAL DETAILS. THE CONSTRUCTED THICKNESS OF THE ABOVE ITEM SHALL NOT BE LESS THAN 90 PERCENT OF THE NOMINAL THICKNESS AT ANY LOCATION.
- ③ THE THICKNESS OF BITUMINOUS MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATION OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.
- ④ ANY REFERENCE TO A STANDARD IN THE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION, AS INDICATED BY THE SUB-NUMBER LISTED IN THE INDEX OF SHEETS, OR THE COPY OF THE STANDARD INCLUDED IN THE PLANS.
- ⑤ THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE:

Location(s):	
Mixture Use(s):	Leveling Binder
PG:	PG 64-22
Design Air Voids:	4.0% @ N70
Mixture Composition:	IL 9.5
Friction Aggregate:	N/A

Location(s):	
Mixture Use(s):	Polymer HMA Surface
PG:	SBS PG70-22
Design Air Voids:	4.0% @ N70
Mixture Composition:	IL 9.5 or 12.5
Friction Aggregate:	Mix D

Location(s):	Incidental HMA Surfacing
Mixture Use(s):	& HMA Shoulders
PG:	PG 64-22
Design Air Voids:	4.0% @ N50
Mixture Composition:	IL 9.5 or 12.5
Friction Aggregate:	Mix C

Location(s):	
Mixture Use(s):	HMA Shoulders 8"
PG:	PG 58-22
Design Air Voids:	2.0% @ N30
Mixture Composition:	Other (BAM)
Friction Aggregate:	N/A

Location(s):	
Mixture Use(s):	Patching
PG:	PG 64-22
Design Air Voids:	4.0% @ N70
Mixture Composition:	IL 19.0
Friction Aggregate:	N/A

RATES OF APPLICATION TABLES

THE FOLLOWING RATES OF APPLICATION HAVE BEEN ASSUMED IN CALCULATING PLAN QUANTITIES.

BITUMINOUS MATERIALS (PRIME COAT): 0.00038 TON / SQ YD
 AGGREGATE MATERIALS (PRIME COAT): 0.002 TON / SQ YD
 HOT-MIX ASPHALT SURFACE LEVELING BINDER (112 LBS): 0.056 TON / SQ YD • 1in
 HOT-MIX ASPHALT SURFACE MIX D (112 LBS): 0.056 TON / SQ YD • 1in
 AGGREGATE MATERIALS: 2.05 TON / CU YD

COMMITMENTS

(NONE)

DISTRICT SIX	
EXAMINED <u>March 5</u> 20 <u>10</u>	
<u>Air Wells</u>	
OPERATIONS ENGINEER	
EXAMINED <u>MARCH 4</u> 20 <u>10</u>	
<u>Jimmy Felt</u>	
PROGRAM IMPLEMENTATION ENGINEER	
EXAMINED <u>March 11</u> 20 <u>10</u>	
<u>ARMU</u>	
PROGRAM DEVELOPMENT ENGINEER	

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

-----**GENERAL NOTE AND
INDEX OF SHEETS**-----

FILE NAME =
c:\pwwork\pwwork\voorte\dms62291\067204

USER NAME = ooxte
sht-coover.dgn
PLOT SCALE = 100.0000' / IN.
PLOT DATE = Mar-10-2010 03:10:38PM

DESIGNED -	---	REVISED -	-----
DRAWN -	---	REVISED -	-----
CHECKED -	---	REVISED -	-----
DATE -	-----	REVISED -	-----

SCALE: _____ SHEET NO. ____ OF ____ SHEETS STA. _____ TO STA. _____

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
32L	106RS-5.18RS-U	PIKE	41	2
			CONTRACT NO.	72C43
ILLINOIS FED. AID PROJECT				