

LOCATION	DIRECTION	STATION	TO	STATION	CONCRETE CURB REMOVAL (FOOT)	CONCRETE MEDIAN SURFACE REM. (SQ FT)	CCC & G TYPE M-6.06 (FOOT)	CCC & G TYPE M-6.06 VAR. WIDTH (FOOT)	CONCRETE MEDIAN SURFACE 4" (SQ FT)	CONCRETE MEDIAN TYPE SM-6.06 (SQ FT)	CCC & G TYPE B-6.24 (FOOT)	CCC & G TYPE B-6.24 VAR. WIDTH (FOOT)	REMARKS
44002000					CONCRETE CURB REMOVAL								FOOT
44002020					CONCRETE MEDIAN SURFACE REMOVAL								SQ FT
60608600					COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.06								FOOT
60609100					COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.06 (VARIABLE WIDTH GUTTER FLAG)								FOOT
60618300					CONCRETE MEDIAN SURFACE, 4 INCH								SQ FT
60622400					CONCRETE MEDIAN, TYPE SM-6.06								SQ FT
60605000					COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24								FOOT
60605500					COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24 (VARIABLE WIDTH GUTTER FLAG)								FOOT
ML	EB	23+77.22	TO	27+72.32	395.0	4544.6	-	-	-	-	-	-	
ML	WB	23+77.22	TO	27+72.32	397.0		-	-	-	-	-	-	
ML	EB	23+77.22	TO	24+50.00	-	-	-	-	-	413.6	-	-	
ML	WB	23+77.22	TO	24+50.00	-	-	-	-	-	-	-	-	
ML	EB	24+50.00	TO	27+50.00	-	-	293.0	-	4416.3	-	-	-	
ML	WB	24+50.00	TO	27+50.00	-	-	294.0	-	-	-	-	-	
ML	EB	27+50.00	TO	27+61.00	-	-	-	15.0	-	-	-	-	
ML	WB	27+50.00	TO	27+61.00	-	-	-	15.0	-	-	-	-	
ML	WB	219+77.00	TO	219+79.00	5.0	-	-	-	-	-	-	-	
ML	WB	220+53.00	TO	220+64.00	12.3	-	-	-	-	-	-	-	
ML	WB	228+34.00	TO	228+54.00	-	-	-	-	-	-	-	20.0	
ML	WB	228+54.00	TO	229+56.00	-	-	-	-	-	-	102.0	-	
ML	WB	229+27.00	TO	229+57.00	30.0	-	-	-	-	-	-	-	
ML	WB	229+95.00	TO	229+99.00	7.5	-	-	-	-	-	-	-	
ML	WB	230+55.00	TO	230+62.00	10.4	-	-	-	-	-	-	-	
ML	WB	2+86.00	TO	2+98.00	18.0	-	-	-	-	-	-	-	
TOTAL					875.2	4544.6	587.0	30.0	4416.3	413.6	102.0	20.0	