

**ELECTRICAL GENERAL NOTES**

- ALL VEHICLE AND PEDESTRIAN SIGNAL HEADS SHALL HAVE 12" L.E.D. SECTIONS. ALL MOUNTING HARDWARE, SIGNAL POSTS, AND BASES SHALL BE UNPAINTED ALUMINUM. ALL BOLTS, SCREWS, NUTS AND WASHERS SHALL BE STAINLESS STEEL. ANTI-SEIZE PASTE COMPOUND SHALL BE USED ON ALL MOUNTING HARDWARE FIELD CONNECTIONS.
- BACKPLATES SHALL BE ABS PLASTIC.
- THE LOCATION OF MAST ARM SUPPORTS SHALL BE APPROVED BY THE ENGINEER BEFORE FOUNDATIONS ARE CONSTRUCTED. MAST ARM POLES SHALL BE LOCATED A MINIMUM OF 10 FEET FROM THE EDGE OF PAVEMENT OR 2 FEET FROM THE EDGE OF SHOULDER, WHICHEVER DISTANCE IS GREATER. IN CURBED SECTIONS, THE MAST ARM POLES SHALL BE LOCATED A MINIMUM OF 5 FEET FROM THE FACE OF THE CURB. THESE DISTANCES ARE TO THE NEAR FACE OF THE MAST ARM POLE. ALL MAST ARMS AND POLES SHALL BE GALVANIZED.
- ACTUAL DEPTHS OF THE CONCRETE FOUNDATIONS FOR THE SIGNAL POLES AND MAST ARM SUPPORT POLES ARE AS FOLLOWS:

**STANDARDS**

- 720001
- 720016
- 805001
- 814001
- 814006
- 857001
- 873001
- 877001
- 877011
- 878001
- 880006
- 886001
- 886006

**ILLINOIS ROUTE 3 AND PROPOSED RAMP P5LT**

- NORTHEAST CORNER MAST ARM: 11'-0" DEEP
- NORTHEAST POLE: 3'-0" DEEP
- WEST SIDE MAST ARM: 15'-0" DEEP
- SOUTHWEST CORNER MAST ARM: 13'-0" DEEP
- SOUTHEAST CORNER POLE: 3'-0" DEEP

THESE DEPTHS ARE DETERMINED FROM THE SOIL BORING DATA.

- ALL TRAFFIC SIGNAL CABLES SHALL BE #14 AWG STRANDED COPPER UNLESS OTHERWISE SPECIFIED.
- THE LOCATION OF ALL DETECTOR LOOPS SHALL BE APPROVED BY THE ENGINEER BEFORE ANY SLOTS ARE SAWED IN THE PAVEMENT.
- DETECTOR LOOP LEAD-IN SPLICES SHALL BE MADE IN A HANDHOLE PER ARTICLE 873.03 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND STANDARD DRAWING 886001. CONDUCTORS SHALL BE SPLICED IN A RIGID MOLD. ROSIN-CORE SOLDER SHALL BE USED.
- CALL DELAY SHALL NOT FUNCTION WHEN THE RELATED PHASES ARE IN THE GREEN MODE.
- ALL HANDHOLES SHALL BE CAST-IN-PLACE PORTLAND CEMENT CONCRETE (PER ARTICLE 814.03(B)). THE CAST IN PLACE LEGEND IN THE COVER SHALL BE "TRAFFIC SIGNALS". SLOPE HANDHOLE COVERS TO MATCH PROPOSED GRADE ELEVATIONS.
- ALL UTILITIES SHALL BE LOCATED IN THE FIELD PRIOR TO ANY ATTEMPT TO CONSTRUCT ANY COMPONENT OF THE VARIOUS TRAFFIC SIGNAL INSTALLATION. AGENCIES KNOWN TO HAVE UNDERGROUND FACILITIES WITHIN THE LIMITS OF THIS IMPROVEMENT ARE THE FOLLOWING: MEMBER OF J.U.L.I.E. PHONE (800) 892-0123 ARE INDICATED BY • (CALL ONE WEEK BEFORE YOU PLAN TO DIG).
  - EXPLORER
  - BUCKEYE
  - LEVEL 3
  - AT&T
- ALL INDUCTIVE LOOP DETECTORS SUPPLIED FOR THIS PROJECT SHALL HAVE THE CAPACITY OF OPERATING WITH BOTH DELAY AND EXTENSION MODES ACTIVE, IF A TIME SETTING IS PROGRAMMED. THEY SHALL BE RACK MOUNTED.
- CABLE MARKING TAPE SHALL BE INCLUDED WITH THE PAY ITEM "TRENCH AND BACKFILL FOR ELECTRICAL WORK" AND INSTALLED PER ARTICLE 815.03(D) OF THE STANDARD SPECIFICATION FOR ROAD AND BRIDGE CONSTRUCTION.
- A 1/4" NYLON PULL ROPE SHALL BE FURNISHED AND INSTALLED IN ALL SIGNAL CONDUITS, THIS WORK SHALL BE INCLUDED WITH THE CONDUIT PAY ITEM.
- THE QUANTITIES FOR DETECTOR LOOPS INCLUDE TWO (2) 6' X 6' CALL CARRY OVER LOOPS FOR THE SOUTHBOUND ILLINOIS ROUTE 3 APPROACH TO THE INTERSECTION OF ILLINOIS ROUTE 3 AND CHAIN OF ROCKS ROAD, WHICH MAY NEED TO BE REPLACED DUE TO THE EXTENTS OF THE HOT-MIX ASPHALT OVERLAY.
- SEE SPECIAL PROVISIONS FOR TRAFFIC CONTROL AND CONSTRUCTION STAGING REQUIREMENTS.

**DETECTOR LOOP REQUIREMENTS AND CALCULATIONS FOR ILLINOIS ROUTE 3 AND RAMP 5 LT**

LOOP	PHASE (Ø)	LOOP SIZE(FT)	REQUIRED # OF TURNS	CALCULATED INDUCTANCE MICROHENRIES (µH)	CALCULATED RESISTANCE OHMS (Ω)
1. WB LT CD	7	6'X50' (Ø)	3-6-3	798.8	1.88
2. WB CCO	7	6'X6'	7	440.4	2.11
3. SB CCO A	2	6'X6'	7	515.0	3.81
4. SB CCO B	2	6'X6'	7	517.6	3.87
5. SB CCO A	6	6'X6'	7	482.0	3.06
6. NB CCO B	6	6'X6'	7	479.1	2.99

THE ABOVE VALUES ARE CALCULATED OF COMBINED LOOP AND LEAD-IN INDUCTANCE AND RESISTANCE. ACTUAL MEASURED VALUES SHOULD BE WITHIN +/- 20% OF THESE VALUES.

**DETECTOR LOOP REQUIREMENTS FOR ILLINOIS ROUTE 3 AND CHAIN OF ROCKS ROAD**


LOOP	PHASE (Ø)	LOOP SIZE(FT)	REQUIRED # OF TURNS	CALCULATED INDUCTANCE MICROHENRIES (µH)	CALCULATED RESISTANCE OHMS (Ω)
7. SB CCO A	EX	6'X6'	EX	EX	EX
8. SB CCO B	EX	6'X6'	EX	EX	EX

**TRAFFIC SIGNAL TURN-ON NOTES**

- PRIOR TO TRAFFIC SIGNAL TURN-ON, CHANGEABLE MESSAGE SIGNS SHALL BE PLACED ON NB IL ROUTE 3, SB IL ROUTE 3 AND RAMP P5LT PRIOR TO THE NEW SIGNALIZED INTERSECTION. A MESSAGE SIMILAR TO THIS EXAMPLE OR AS DIRECTED BY THE ENGINEER SHALL BE DISPLAYED ON ALL SIGNS FOR A PERIOD OF 72 HOURS PRIOR TO THE TRAFFIC SIGNAL TURN-ON.



- AFTER THE TRAFFIC SIGNAL TURN-ON, A MESSAGE SIMILAR TO THIS EXAMPLE OR AS DIRECTED BY THE ENGINEER SHALL BE DISPLAYED ON ALL SIGNS FOR A PERIOD OF 72 HOURS.



- ALL MESSAGES TO BE DISPLAYED ON THE CHANGEABLE MESSAGE SIGNS SHALL BE APPROVED BY THE ENGINEER.

**STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION**

**HORNER & SHIRIN, INC. ENGINEERS**

**TRAFFIC SIGNAL DETAILS**  
IL 3 AT PROPOSED RAMP P5LT  
ELECTRICAL NOTES

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
270	60-2RS-3	MADISON	231	72
				CONTRACT NO. 76D87

SCALE: NONE SHEET NO. 2 OF 7 SHEETS STA. TO STA.

ILLINOIS FED. AID PROJECT

LAST SAVED = 4/19/2010 10:05:50 AM  
FILE NAME = \\09066602\09066601\Cad\T\Plans\055\_087\087-Sh-TS-RampP5LT-02.dgn  
PLOT DATE = 4/21/2010 10:05:50 AM

FILE NAME	USER NAME	DESIGNED	REVISED
\\09066602\09066601\Cad\T\Plans\055_087\087-Sh-TS-RampP5LT-02.dgn	bereschmann	-	-
		DRAWN	REVISED
		-	-
		CHECKED	REVISED
		-	-
		DATE	REVISED
		-	-