



* 6.90% RAMP G, VARIES RAMP A (SEE SUPERELEVATION TABLE THIS SHEET)
 ** VARIES RAMP G STATION 118+60.51 TO STATION 121+35.41 (33' TO 26.7')

TO BE USED
 RAMPS - A, G

RAMP A: STA. 19+91.58 TO STA. 41+21.02
 RAMP G: STA. 111+00.00 TO STA. 114+39.94
 STA. 118+60.51 TO STA 121+35.41

- ① HOT-MIX ASPHALT PAVEMENT (FULL DEPTH), 14 3/4"
 -POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 1 1/2"
 -POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N105 2 1/4"
 -HOT-MIX ASPHALT BINDER COURSE, N90, 11"
- ② PROCESSING LIME MODIFIED SOILS 12"
- ③ HOT-MIX ASPHALT SHOULDERS, 8"
- ④ SUB-BASE GRANULAR MATERIAL, TYPE C
- ⑤ AGGREGATE SHOULDERS, TYPE A, 8"
- ⑥ THERMOPLASTIC PAVEMENT MARKING - LINE 4"
- ⑦ PIPE UNDERDRAINS 4"
- ⑧ PIPE UNDERDRAINS 4" (SPECIAL)
- ⑨ CONCRETE HEADWALL FOR PIPE DRAINS (SEE PLANS FOR LOCATIONS)

RAMP A SUPERELEVATION TRANSITION TABLE

STATION TO STATION	CROSS SLOPE (%)
STA 19+91.58	8.00%
STA 24+50.00	8.00%
STA 25+00.00	6.72%
STA 25+50.00	5.53%
STA 26+00.00	4.35%
STA 26+50.00	3.18%
STA 27+00.00	2.00%
STA 43+25.07	2.00%