

INLET AND PIPE PROTECTION

| EACH | LOCATION | | | |
|----------|---------------|-----------|--|----|
| | IL 72 | | | |
| 1 | Sta | 1782 + 93 | | RT |
| 1 | Sta | 1784 + 58 | | RT |
| 1 | Sta | 1785 + 31 | | LT |
| 1 | Sta | 1787 + 52 | | LT |
| 1 | Sta | 1788 + 46 | | RT |
| 1 | Sta | 1788 + 64 | | LT |
| | IL 251 | | | |
| 1 | Sta | 786 + 73 | | LT |
| 1 | Sta | 789 + 75 | | RT |
| 8 | TOTAL | | | |

STONE RIPRAP CLASS A4

| SQ YD | LOCATION | | | |
|-------------|---------------|-----------|---|---------------|
| | IL 72 | | | |
| 10 | Sta | 1788 + 78 | | LT (18' X 5') |
| | IL 251 | | | |
| 5.6 | Sta | 785 + 75 | - | 785 + 85 |
| 5.6 | Sta | 786 + 11 | - | 786 + 21 |
| 21.2 | TOTAL | | | |

FILTER FABRIC

| SQ YD | LOCATION | | | |
|-------------|---------------|-----------|---|---------------|
| | IL 72 | | | |
| 10 | Sta | 1788 + 78 | | LT (18' X 5') |
| | IL 251 | | | |
| 5.6 | Sta | 785 + 75 | - | 785 + 85 |
| 5.6 | Sta | 786 + 11 | - | 786 + 21 |
| 21.2 | TOTAL | | | |

SUB-BASE GRANULAR MATERIAL, TYPE A 12"

| SQ YD | LOCATION | | | |
|----------------|--------------|-----------|---|-----------|
| | IL 72 | | | |
| 548.1 | Sta | 1782 + 84 | - | 1786 + 08 |
| 547.5 | Sta | 1783 + 31 | - | 1786 + 08 |
| 421.1 | Sta | 1786 + 36 | - | 1787 + 64 |
| 429.8 | Sta | 1786 + 36 | - | 1788 + 18 |
| 1,946.5 | TOTAL | | | |

HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT

| SQ YD | LOCATION | | | |
|--------------|---------------|-----------|---|-----------|
| | IL 72 | | | |
| 72.2 | Sta | 1782 + 34 | - | 1782 + 84 |
| 72.7 | Sta | 1788 + 81 | - | 1789 + 31 |
| | IL 251 | | | |
| 75.3 | Sta | 789 + 93 | - | 790 + 43 |
| 220.2 | TOTAL | | | |

TEMPORARY RAMP

| SQ YD | LOCATION | | | |
|-------------|---------------|-----------|--|----------------|
| | IL 72 | | | |
| 21.7 | Sta | 1782 + 34 | | (26' x 7.5') |
| 21.8 | Sta | 1789 + 31 | | (26.2' x 7.5') |
| | IL 251 | | | |
| 20.8 | Sta | 780 + 86 | | (25' x 7.5') |
| 22.6 | Sta | 790 + 43 | | (27.1' x 7.5') |
| 86.9 | TOTAL | | | |

HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"

| SQ YD | LOCATION | | | |
|----------------|---------------|----------|---|----------|
| | IL 251 | | | |
| 930.1 | Sta | 780 + 86 | - | 784 + 25 |
| 135.2 | Sta | 784 + 25 | - | 784 + 75 |
| 1,065.3 | TOTAL | | | |

PAVEMENT REMOVAL

| SQ YD | LOCATION | | | |
|-------------|---------------|-----------|---|-----------|
| | IL 72 | | | |
| 21.1 | Sta | 1785 + 79 | - | 1785 + 95 |
| 17.8 | Sta | 1786 + 50 | - | 1786 + 65 |
| | IL 251 | | | |
| 18.5 | Sta | 786 + 83 | - | 786 + 98 |
| 21.4 | Sta | 787 + 52 | - | 787 + 68 |
| 78.8 | TOTAL | | | |

GUTTER REMOVAL

| FOOT | LOCATION | | | |
|------------|---------------|----------|---|----------|
| | IL 251 | | | |
| 422 | Sta | 781 + 78 | - | 785 + 98 |
| 412 | Sta | 781 + 77 | - | 785 + 90 |
| 834 | TOTAL | | | |