

**RUMBLE RESURFACING**

SQ YD	LOCATION	OFFSET	REMARKS
33.3	19+20.7 TO 19+25.7	EB - LT	<b>PERMANENT LANE CLOSURE PROPOSED SHOULDER</b>
33.3	21+40.8 TO 21+45.8	EB - LT	
33.3	23+60.8 TO 23+65.8	EB - LT	
33.3	25+80.8 TO 25+85.8	EB - LT	
33.3	28+00.8 TO 28+05.8	EB - LT	
33.3	30+20.8 TO 30+25.8	EB - LT	
33.3	32+40.9 TO 32+45.9	EB - LT	
<b>233.1</b>	<b>TOTAL</b>		

**COMBINATION CONCRETE CURB & GUTTER, TYPE M-4.24**

FOOT	LOCATION	OFFSET	REMARKS
278.8	35+94.4 TO 37+33.8		AROUND LT TURNLANE MEDIAN
278.6	39+27.3 TO 42+05.9	RT	CENTER MEDIAN
<b>557.4</b>	<b>TOTAL</b>		

**COMBINATION CONCRETE CURB & GUTTER, TYPE M-4.06**

FOOT	LOCATION	OFFSET	REMARKS
425.5	38+50.8 TO 40+63.5		LANE MEDIAN
262.4	39+27.3 TO 41+89.7	LT	CENTER MEDIAN - INCLUDES TRANSITION
<b>687.9</b>	<b>TOTAL</b>		

**SOLAR-POWERED FLASING BEACON ASSEMBLY (COMPLETE)**

FOOT	LOCATION	OFFSET	REMARKS
2	N Weldon Rd		1-Yellow-Stop Ahead 1-Red-Stop Sign
2	S Weldon Rd		1-Yellow-Stop Ahead 1-Red-Stop Sign
<b>4</b>	<b>TOTAL</b>		