SHEET NO. 70 86 SHEETS

Contract #72A76

<u>MOTES</u>
Bar splicer assemblies shall be of an approved type and shall develop in tension at least 125 percent of the yield strength of the lapped reinforcement bars.

Splicer rods shall be of minimum 60 ksi yield strength, threaded or coiled full length. All reinforcement bars shall be lapped and tied to the splicer rods or dowel bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars.


Other systems of similar design may be submitted to the Engineer for approval. Approval shall be based on certified test results from an approved testing laboratory that the proposed bar splicer assembly satisfies the following requirements:

(Tension III Kips)
Minimum *Pull-out Strength = 0.66 x fy x A, (Tension in kips)

Where fy = Yield strength of lapped reinforcement bars in ksi.

A_t = Tensile stress area of lapped reinforcement bars.
* = 28 day concrete

BAR SPLICER ASSEMBLIES					
Bar Size to be Spliced	Splicer Rod or Dowel Bar Length	Strength Requirements			
		Min. Capacity kips - tension	Min. Pull-Out Strength kips - tension		
#4	1′-8′′	14.7	7 . 9		
#5	2'-0"	23.0	12.3		
#6	2'-7"	33.1	17.4		
#7	3′-5′′	45.1	<i>23.8</i>		
#8	4′-6′′	58 . 9	31.3		
#9	5′-9′′	75.0	39.6		
#10	7′-3′′	95.0	50.3		
#11	9'-0''	117.4	61.8		




Bar Size	No. Assemblies Required	Location

BAR SPLICER - DETAILS F.A.P. 614 (IL 78) OVER SANGAMON RIVER PUBLIC WATERS CASS & MASON COUNTIES SECTION 144 (B-1) STA. 913+26.00 STRUCTURE NUMBER 009-0510

PROFESSIONAL DESIGN FIRM LICENSE #184-001084






** ONE PIECE -Wire Connector णःणः। णःणः। WELDED SECTIONS

BAR SPLICER ASSEMBLY ALTERNATIVES


**Heavy Hex Nuts conforming to ASTM A 563, Grade C, D or DH may be used.



INSTALLATION AND SETTING METHODS


"A": Set bar splicer assembly by means of a template bolt. "B": Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E): Indicates epoxy coating.



FOR INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

Bar Splicer for #5 bar
Min. Capacity = 23.0 kips - tension
Min. Pull-out Strength = 12.3 kips - tension
No. Required =



No. Assemblies Location Size Required #5 41 No. Abut. #5 41 So. Abut.

07\$2026

03/27/09