

EARTHWORK TABLE					
	FROM STATION	TO STATION	CUT VOLUME CU YD	FILL VOLUME CU YD	CU YD WIDENING EXCAVATION VOLUME
CH 29	27+62	69+70	4,012	2	0
TEMP HMA BASE COURSE 8" REMOVAL	25+87	58+57	408	0	0
JACKSON STREET	66+66.94 / 12' RT	66+66.94 / 220' RT	0	0	65
TOTAL			4,420	2	65

(CH 29 BRIDGE OMISSION STATION 48+52.5 TO STATION 51+47.5)
 TOTAL EARTH EXCAVATION = 4,420 CU YD
 TOTAL FILL = 2 CU YD
 TOTAL EARTH EXCAVATION WIDENING = 65 CU YD
 TOTAL WASTE = 4,483 CU YD

SEEDING TABLE								
STATION	TO STATION	SIDE	NITROGEN FERTILIZER NUTRIENT POUND	PHOSPHORUS FERTILIZER NUTRIENT POUND	POTASSIUM FERTILIZER NUTRIENT POUND	SEEDING, CLASS 1 ACRE	MULCH, METHOD 1 ACRE	EROSION CONTROL BLANKET SQ YD
25+87	27+62	LT	1.8	1.8	1.8	0.02	0.02	-
27+62	42+44	LT	18.0	18.0	18.0	0.20	0.20	-
43+70	SBL RAMP	LT	0.45	0.45	0.45	0.005	0.005	-
43+86	48+52.5	LT	5.4	5.4	5.4	0.06	0.06	-
51+47.5	55+98	LT	5.4	5.4	5.4	0.06	0.06	-
57+00	NBL RAMP	LT	0.9	0.9	0.9	0.01	0.01	-
57+21.9	66+44	LT	11.7	11.7	11.7	0.13	0.13	-
66+88	69+70	LT	2.7	2.7	2.7	0.03	0.03	-
25+87	27+62	RT	1.8	1.8	1.8	0.02	0.02	-
27+62	32+80	RT	6.3	6.3	6.3	0.07	0.07	-
33+00	TR2000N	RT	0.45	0.45	0.45	0.005	0.005	-
33+58	42+60.5	RT	10.8	10.8	10.8	0.12	0.12	-
43+92	48+52.5	RT	5.4	5.4	5.4	0.06	0.06	-
51+47.5	56+20.8	RT	5.4	5.4	5.4	0.06	0.06	-
57+58.7	66+24	RT	10.8	10.8	10.8	0.12	0.12	-
66+66.9	JACKSON ST.	RT	4.5	4.5	4.5	0.05	0.05	-
67+84	69+70	RT	4.5	4.5	4.5	0.05	0.05	-
27+72 TO 68+65 @ PIPE UNDERDRAINS 10" END SECTIONS	LT & RT		2.7	2.7	2.7	0.03	0.03	111
TOTALS			99.0	99.0	99.0	1.1	1.1	111

TEMPORARY EROSION CONTROL TABLE				
LOCATION	SIDE	INLET AND PIPE PROTECTION EACH	PERIMETER EROSION BARRIER FOOT	
27+72	LT	-	30	
27+72	RT	-	30	
32+00	RT	-	30	
32+06	RT	1	-	
37+50	RT	-	30	
38+50	RT	-	30	
44+50	RT	-	30	
55+50	RT	-	30	
61+50	RT	-	30	
62+50	RT	-	30	
66+90	RT	1	-	
68+25	LT	-	30	
TOTAL		2	300	

ENTRANCES					
LOCATION	SIDE	AGGREGATE FOR TEMPORARY ACCESS TON	AGGREGATE SURFACE COURSE, TYPE B TON	DRIVEWAY PAVEMENT REMOVAL SQ YD	P. C. CONCRETE DRIVEWAY 8" SQ YD
TR2000N 33+29.2	RT	61	-	-	-
F. E. 33+32.53	LT	61	72	-	-
F. E. 66+66.34	LT	61	58	-	-
JACKSON ST. 66+66.94	RT	61	-	-	-
CE 67+61.42	RT	61	-	105	95
TOTAL		305	130	105	95

SUBBASE GRANULAR & P. C. CONCRETE PAVEMENT								
STATION	TO STATION	SIDE	GEOTECH FABRIC FOR GROUND STABILIZATION SQ YD	SUBBASE GRANULAR MATERIAL (SPECIAL) TON	SUBBASE GRANULAR MATERIAL, TYPE A TON	P. C. CONCRETE PAVEMENT, 9" SQ YD	BRIDGE APPROACH PAVEMENT (SPECIAL) SQ YD	REINFORCEMENT BARS, EPOXY COATED POUND
27+62	35+00	LT	984	336	336	984	-	-
35+00	37+25	LT	344	117	117	344	-	-
37+25	48+32.5	LT	2,282	780	780	2,282	-	-
48+32.5	48+52.5	LT	-	-	-	-	31	2,770
51+47.5	51+67.5	LT	-	-	-	-	31	2,770
51+67.5	62+69.3	LT	1,780	608	608	1,780	-	-
62+69.3	69+70	LT	1,456	498	497	1,456	-	-
41+45	43+54.93	MEDIAN	-	-	198	-	-	-
56+46.83	58+57	MEDIAN	-	-	198	-	-	-
27+62	35+00	RT	984	336	336	984	-	-
35+00	37+25	RT	344	117	117	344	-	-
37+25	48+32.5	RT	1,738	594	594	1,738	-	-
48+32.5	48+52.5	RT	-	-	-	-	31	2,770
51+47.5	51+67.5	RT	-	-	-	-	31	2,770
51+67.5	62+69.3	RT	2,236	764	764	2,236	-	-
62+69.3	69+70	RT	1,157	395	395	1,157	-	-
CONTINGENCY FOR UNDERCUTS			400	-	275	-	-	-
TOTAL			13,705	4,545	5,215	13,305	124	11,080

HOT-MIX ASPHALT											
STATION	TO STATION	SIDE	TEMPORARY HMA BASE COURSE, 8" SQ YD	TEMPORARY RAMP SQ YD	HMA SURFACE REMOVAL 2" SQ YD	HMA SURFACE REMOVAL BUTT JOINT SQ YD	BITUMINOUS MATERIALS (PRIME COAT) GAL	AGGREGATE (PRIME COAT) TON	HMA BASE COURSE WIDENING 9" SQ YD	HMA SURFACE COURSE MIX D, N50 TON	INCIDENTAL HMA SURFACING TON
25+87	27+62	LT	107	-	-	-	-	-	-	-	-
43+47.10	SBL RAMP	LT	75	77	158	-	16	0.3	-	-	19
48+18	BRG. APPR. SHLDR.	LT	-	-	18	-	-	-	-	-	-
51+50	BRG. APPR. SHLDR.	LT	-	-	13	-	-	-	-	-	-
56+53.85	NBL RAMP	LT	117	80	138	-	14	0.3	-	-	16
41+45	43+54.93	MEDIAN	395	-	-	-	-	-	-	-	-
56+46.83	58+57	MEDIAN	395	-	-	-	-	-	-	-	-
25+87	27+62	RT	107	-	-	-	-	-	-	-	-
27+62	29+00	RT	123	-	-	-	-	-	-	-	-
29+00	32+69.2	RT	246	-	-	-	-	-	-	-	-
33+29.2	TR2000N	RT	75	44	-	-	-	-	-	-	-
33+73	36+00	RT	126	-	-	-	-	-	-	-	-
36+00	38+00	RT	56	-	-	-	-	-	-	-	-
43+31.28	SBL RAMP	RT	-	80	146	-	15	0.3	-	-	17
48+60	BRG. APPR. SHLDR.	RT	-	-	13	-	-	-	-	-	-
51+84	BRG. APPR. SHLDR.	RT	-	-	18	-	-	-	-	-	-
56+70.19	NBL RAMP	RT	78	67	153	-	16	0.3	-	-	18
66+66.94	JACKSON ST.	RT	-	92	93	150	84	1.8	250	95	-
TOTAL			1,900	440	750	150	145	3	250	95	70

MISCELLANEOUS CONCRETE								
LOCATION	SIDE	COMBINATION CURB & GUTTER REMOVAL FOOT	SIDEWALK REMOVAL SQ FT	MEDIAN REMOVAL SQ FT	P. C. CONCRETE SIDEWALK 4" SQ FT	COMBINATION CURB & GUTTER TYPE M-6.06 FOOT	CONCRETE MEDIAN SURFACE 4" SQ FT	CORRUGATED MEDIAN SQ FT
37+50	MEDIAN	-	-	65	-	-	-	65
38+50	MEDIAN	27	-	88	-	27	36	52
41+45 TO 43+54.93	MEDIAN	420	-	3,089	-	420	3,089	-
44+50	MEDIAN	29	-	36	-	29	36	-
55+50	MEDIAN	30	-	52	-	30	52	-
56+46.83 TO 58+57	MEDIAN	420	-	3,092	-	420	3,092	-
61+50	MEDIAN	29	-	100	-	29	45	55
62+50	MEDIAN	-	-	43	-	-	-	48
68+90	LT	-	-	-	32	-	-	-
69+19	LT	-	170	-	-	-	-	-
69+55	RT	-	50	-	48	-	-	-
TOTAL		955	220	6,565	80	955	6,350	220

PAVED SHOULDER REMOVAL			
STATION	TO STATION	SIDE	SQ YD
27+76	30+00	LT	100
30+00	32+00	LT	100
21+00	35+00	LT	167
35+00	36+25	LT	104
36+25	42+44	LT	688
43+86.4	48+36.5	LT	480
51+59.5	55+98.3	LT	507
57+21.9	68+40	LT	1,203
27+81	32+69.2	RT	271
33+73	35+00	RT	71
35+00	37+25	RT	188
37+25	42+60.5	RT	595
43+92	48+40.5	RT	520
51+63.5	56+20.8	RT	485
57+58.7	66+20	RT	957
67+04	67+35	RT	34
67+92	68+95	RT	115
TOTAL			6,585

REMOVAL ITEMS					
STATION	TO STATION	SIDE	PAVEMENT REMOVAL SQ YD	REMOVAL OF EXISTING STRUCTURES EACH	WOOD FENCE TO BE REMOVED AND RE-ERECTED FOOT
27+62	35+00	LT	984	-	-
35+00	37+25	LT	344	-	-
37+25	48+32.5	LT	2,282	-	-
48+32.5	48+52.5	LT	-	1 BRIDGE APPROACH	-
51+47.5	51+67.5	LT	-	1 BRIDGE APPROACH	-
51+67.5	62+69.3	LT	1,780	-	-
62+69.3	69+70	LT	1,174	-	-
27+62	35+00	RT	984	-	-
35+00	37+25	RT	344	-	-
37+25	48+32.5	RT	1,740	-	-
48+32.5	48+52.5	RT	-	1 BRIDGE APPROACH	-
51+47.5	51+67.5	RT	-	1 BRIDGE APPROACH	-
51+67.5	62+69.3	RT	2,236	-	-
61+69.3	69+70	RT	1,112	-	-
68+30	68+90	LT	-	-	80
TOTAL			12,980	4	80

McLEAN COUNTY, ILLINOIS
MFT SECTION 05-00071-04-RS

SCHEDULE OF QUANTITIES

DRAWN BY DRR	 2700 McGraw Drive Bloomington, Illinois 61704 309.883-8488 / fax 309.883-1871	FILE NO. 24-8051
DATE 01/20/09		BOOK NO. 2416
CHECKED BY RGD		SHEET NO. 5 OF 37