

INDEX OF SHEETS

1	COVER
2	INDEX OF SHEETS, GENERAL NOTES AND HIGHWAY STANDARDS
3	SUMMARY OF QUANTITIES
4	DETOUR PLAN
5	ROADWAY PLAN
6	ROADWAY SECTIONS
7	PAVEMENT MARKING PLAN
8-21	BRIDGE PLANS SN 049-0118
22	BUTT JOINT AND HMA TAPER DETAILS
23	HOT-MIX ASPHALT TAPER AT EDGE OF P.C.C. PAVEMENT
24	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
25	FREEWAY ENTRANCE AND EXIT RAMP CLOSURE DETAILS
26	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS

HIGHWAY STANDARDS

NO.	DESCRIPTION
000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
701901	TRAFFIC CONTROL DEVICES
780001-01	TYPICAL PAVEMENT MARKINGS

GENERAL NOTES

1. THE STRUCTURE WILL RETAIN EXISTING BRIDGE NUMBER.
3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY DURING CONSTRUCTION OPERATIONS AS OUTLINED IN ARTICLE 107.31 OF THE STANDARD SPECIFICATIONS. A MINIMUM OF 48 HOURS ADVANCE NOTICE IS REQUIRED FOR NON-EMERGENCY WORK. THE J.U.L.I.E. NUMBER IS 800-892-0123.
3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT PERMISSION FROM THE DEPARTMENT.
4. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
5. FOR PAVEMENT MARKING, REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS NOT SHOWN.
6. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
7. THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISER AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
8. HOT-MIX ASPHALT TAPERS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

HOT MIX ASPHALT MIXTURE REQUIREMENTS

OPERATION	MIXTURE TYPE	AC TYPE	AIR VOIDS
ROADWAY	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", IL 9.5 mm, N70	PG 64-22	4% @ 70 GYR
PARTIAL DEPTH PATCHING	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", IL 9.5 mm, N70, 1 1/2" MIN.	PG 64-22	4% @ 70 GYR

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURES IS 112 LBS/SQ YD/IN

H:\Jobs\2006\20063028-43\CAD\DOT Trans\dgn\00\index-43\_V8.dgn 3/31/2008 11:48:25 AM



GRAEF, ANHALT, SCHLOEMER & ASSOCIATES, INC.  
CHICAGO, ILLINOIS

FILE NAME =	USER NAME = .USER.	DESIGNED - MW	REVISED -
*FILE*		DRAWN - EUB	REVISED -
	PLOT SCALE = 10.0000 "/ IN.	CHECKED - RJS	REVISED -
	PLOT DATE = 3/31/2008	DATE - 3/27/08	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**INDEX OF SHEETS, GENERAL NOTES  
AND HIGHWAY STANDARDS**

SCALE: NTS	SHEET NO. OF 26 SHEETS	STA. TO STA.	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
			541	9 HB-1-1	LAKE	26	2
			FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		
			CONTRACT NO. 60D90				

H:\Jobs\2006\20063028-43\CAD\DOT Trans\dgn\00\index-43\_V8.dgn 3/31/2008 11:48:25 AM