



PLAT






RECORDING: RECORDED ON

ROUTE F.A.P. 338 (ILLINOIS ROUTE 59)

SECTION


COUNTY WILL

JOB NO. R-91-067-01



JOB NO. R-91-067-01

RECORDING: RECORDED ON



ROUTE F.A.P. 338 (ILLINOIS ROUTE 59)

ROW PLAT


SECTION


COUNTY WILL

JOB NO. R-91-067-01

RECORDING: RECORDED ON

AS DOCUMENT NO.






CONTRACT NO. 62417


338 (113 & 114) R-5 WILL 525 310 STA. 3204+00 TO STA. 3218+00 FED. ROAD DIST. NO. 1LLINGIS FAP 338 (IL RTE. 59)













NORTH M3-1-2412 M1-I100-24

# NOTES:


- 1. PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKINGS SHALL BE PLACED IN ACCORDANCE WITH IDOT DISTRICT 1 DETAILS TC-11 AND TC-13.
- 2. SIGN LOCATIONS MAY VARY BASED ON FIELD CONDITIONS.
- 3. EXISTING SIGN TO BE REMOVED AND RE-ERECTED.
- 4. SIGN SHALL BE MOUNTED ON A TELESCOPING STEEL SIGN SUPPORT IN ACCORDANCE WITH HIGHWAY STANDARDS 720001


ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG


> PAVEMENT MARKING AND SIGNING PLANS


SCALE AS SHOWN DATE MARCH 18, 2008 DRAWN BY REW CHECKED BY JCM/HME


Rev. 05-01-08 JCM
















CONTRACT NO. 62417 525 317 338 (113 & 114) R-5 WILL STA. 3288+00 TO STA. 3302+00 FEO. ROAD DIST. NO. ILLINOIS FAP 338 (IL RTE. 59)







## NOTES:

SCALE IN FEET


- 1. PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKINGS SHALL BE PLACED IN ACCORDANCE WITH IDOT DISTRICT 1 DETAILS TC-11 AND TC-13.
- 2. SIGN LOCATIONS MAY VARY BASED ON FIELD CONDITIONS.


ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG

PAVEMENT MARKING AND SIGNING PLANS

SCALE AS SHOWN
DATE MARCH 18, 2008

DRAWN BY REW CHECKED BY JCM/HME






CONTRACT NO. 624

417	RIE.		CTION		COUNTY					TAL EETS	SHEET		
	338	<b>{113</b>	&	114)	R-5		WI	LL		5	25	320	_
	STA.		ТО	STA,	33	335+	00			Π			
	FED. I	ROAD DIST	NO.		- ILLIN	ots	F/	٩P	338	(IL	RTE	. 59)	Ī







EXISTING SIGN EXISTING TO REMAIN ROUTE MARKERS TO REMAIN

EXISTING SIGN

TO REMAIN

NOTES:

1. PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKINGS SHALL BE PLACED IN ACCORDANCE WITH IDOT DISTRICT 1 DETAILS TC-11 AND TC-13.

> ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG

> > PAVEMENT MARKING AND SIGNING PLANS

SCALE AS SHOWN
DATE MARCH 18, 2008

DRAWN BY REW CHECKED BY JCM/HME


-¢ ILLINOIS ROUTE 59


Rev. 05-01-08 JCM

DETAIL A

17	FAP RTE.		SE	CTION		COUNTY				TAL FTS	SHEET
	338	(113	&	114)	R-5		WILL			25	320A
	STA.	3190	+0	0		TO	STA. 3	204+	00		
	FED. I		ILLINOTS		FAF	338	(IL	RTE	59)		

## SIGN LEGEND





R6-2R-1824

M3-3-2412

M1-I100-24

D3

30" X 8"


D3

30" X 8"

RIVERWALK DR.

IL ROUTE 59

(9)



DIVIDED

NO

**PARKING** 

ROLF ROAD

NORTH

ILLINOIS

**59** 

11)


R6-3A-2418


R8-3-2430

W2-2R-36

W17-I100

30" X 9"





17)

(18)

(19)

20

21)

DAYFIELD DR

WEDGEWOOD CT

NOT USED

SPEED

LIMIT


40


24" X 6"


D3


28" X 6"

R2-1-3036









PAVEMENT MARKING AND SIGNING PLANS

DISTRICT NO. 1 SCHAUMBURG

SCALE AS SHOWN Rev. 05-01-08 JCM


DATE MARCH 18, 2008


DRAWN BY REW CHECKED BY JCM/HME

CONTRACT NO. 62417 338 (113 & 114) R-5 WILL 525 321 STA. 3190+00 TO STA. 3204+00 FED. ROAD DIST. NO. | ILLINOIS | FAP 338 (IL RTE. 59) WORK TO BE COORDINATED WORK TO BE PERFORMED WITH CONTRACT NO. 62416 UNDER THIS CONTRACT TEMPORARY EROSION CONTROL SEEDING (72 LBS) AND EROSION CONTROL BLANKET (3,477 SY) -STORM SEWER TO BE CLEANED 30" - 82 FT. ---FLOW DIRECTION (TYP.) (SEE NOTE 4) TEMPORARY PAVEMENT, EXISTING EDGE OF PAVEMENT SEE MOT PLANS -¢ ILLINOIS ROUTE 59 ILLINOIS ROUTE 59 EXISTING R.O.W. S 3200+00 3195+00 | 3190+00 KI KI III KI PROPOSED R.O.W. EXISTING EDGE OF PAVEMENT EROSION CONTROL LEGEND TEMPORARY EROSION CONTROL SEEDING V V V AND EROSION CONTROL BLANKET GENERAL EROSION CONTROL NOTES: NOTES TEMPORARY PAVEMENT SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) TREE TRUNK PROTECTION, TREE ROOT PRUNING, AND TREE PRUNING WILL BE THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER REQUIRED FOR THIS PROJECT. A REPRESENTATIVE FROM IDOT'S ROADSIDE PRIOR TO COMMENCING CONSTRUCTION. DEVELOPMENT UNIT WILL DETERMINE LOCATIONS ON SITE AT THE START OF THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO С DRAINAGE STRUCTURE TO BE CLEANED CONSTRUCTION. PAY ITEMS HAVE BEEN INCLUDED IN THE SUMMARY OF PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.  $\boxtimes$ INLET FILTER 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO THE CONTRACTOR WILL BE REQUIRED TO SUBMIT CERTFICATION STATEMENT R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED (NPDES ATTACHMENT 6). FULL COMPLIANCE WITH ALL TERMS OF THE NPDES TEMPORARY DITCH CHECK BY THE ENGINEER. PERMIT MUST BE STRICTLY ADHERED TO. 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS. --∕~> FLOW DIRECTION (SEE NOTE 4) DRAINAGE STRUCTURE INLET FILTERS ARE TO BE PROVIDED AND MAINTAINED FOR ALL EXISTING AND PROPOSED DRAINAGE STRUCTURE WITHIN THE PROJECT 4. SEE PRE-STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION. PERMANENT DRAINAGE STRUCTURE NUMBER LIMITS AND ALL STRUCTURES NOTED FOR INLET AND PIPE PROTECTION AS (SEE SEE NOTE 5) DIRECTED BY THE ENGINEER. PAY ITEMS, DETAILS AND SPECIAL PROVISIONS 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION. HAVE BEEN INCLUDED IN THE SUMMARY OF QUANTITIES, SPECIAL PROVISIONS, PROPOSED STORM SEWER (SEE NOTE 5) AND PLAN DETAILS FOR THIS WORK. ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG TEMPORARY PIPE CULVERT EROSION CONTROL PLAN PRE-STAGE 1, 1A AND 1B ILLINOIS ROUTE 59 SCALE AS SHOWN DRAWN BY BSB SCALE IN FEET

DATE MARCH 18, 2008

CHECKED BY HME





TEMPORARY EROSION CONTROL SEEDING (15 LBS) AND EROSION CONTROL BLANKET (704 SY)

LINE

S

3204+00

3205+00

TEMPORARY EROSION CONTROL SEEDING (5 LB) AND EROSION CONTROL BLANKET (224 SY)

ILLINOIS ROUTE 59

PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS. 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONSTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER. 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS. 4. SEE PRE-STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.

THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER

-¢ ILLINOIS ROUTE 59

EXISTING R.O.W.

1 3210#00

NOTES

EXISTING R.O.W.

AND DESCRIPTION OF THE PARTY OF

STORM SEWER TO BE CLEANED

С


3215+00


42" - 320 FT.

8' @ 1.0% (SEE NOTE 6)


5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. TEMPORARY PIPE CULVERT SHALL BE TEMPORARILY CONNECTED TO PROPOSED MANHOLE. COST OF TEMPORARY CONNECTION SHALL BE CONSIDERED INCLUDED IN THE UNIT PRICE OF "PIPE CULVERT, CLASS C, TYPE 1, 12". (TEMPORARY)".





# EROSION CONTROL LEGEND




## NOTES

- 1. THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER
  PRIOR TO COMMENCING CONSTRUCTION.
  THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO
  PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID
  TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE PRE-STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. TEMPORARY PIPE CULVERT SHALL BE TEMPORARILY CONNECTED TO PROPOSED MANHOLE OR SEWER, COST OF TEMPORARY CONNECTION SHALL BE CONSIDERED INCLUDED IN THE UNIT PRICE OF "PIPE CULVERT, CLASS C, TYPE 1, 12". (TEMPORARY)".


7. PROPOSED STRUCTURE SHALL BE BURIED AND TEMPORARILY COVERED WITH STEEL PLATE OF 0.25 INCH MINIMUM THICKNESS OR OF THICKNESS SPECIFIED AND APPROVED BY THE ENGINEER. PAYMENT FOR THE INSTALLATION AND REMOVAL OF THE STEEL PLATE INCLUDING ANY REQUIRED EXCAVATION SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.





ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
PRE-STAGE 1, 1A AND 1B
ILLINOIS ROUTE 59


SCALE AS SHOWN
DATE MARCH 18, 2008


DRAWN BY BSB CHECKED BY HME

















#### EROSION CONTROL LEGEND

TEMPORARY EROSION CONTROL SEEDING V V V AND EROSION CONTROL BLANKET TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE PERMANENT LANDSCAPING (SEE NOTE 3) TEMPORARY PAVEMENT

DRAINAGE STRUCTURE TO BE CLEANED С SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2)

SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE

 $\boxtimes$ INLET FILTER

XINLET FILTER INSTALLED IN PREVIOUS STAGE

#### GENERAL EROSION CONTROL NOTES: TEMPORARY DITCH CHECK

TEMPORARY DITCH CHECK INSTALLED

PERMANENT DRAINAGE STRUCTURE NUMBER

PROPOSED STORM SEWER (SEE NOTE 5)

PROPOSED STORM SEWER INSTALLED

TEMPORARY PIPE CULVERT INSTALLED

FLOW DIRECTION (SEE NOTE 4)

IN PREVIOUS STAGE

(SEE SEE NOTE 5)

IN PREVIOUS STAGE

IN PREVIOUS STAGE

TEMPORARY PIPE CULVERT

-~~>

(27)

TREE TRUNK PROTECTION, TREE ROOT PRUNING, AND TREE PRUNING WILL BE REQUIRED FOR THIS PROJECT. A REPRESENTATIVE FROM IDOT'S ROADSIDE DEVELOPMENT UNIT WILL DETERMINE LOCATIONS ON SITE AT THE START OF CONSTRUCTION. PAY ITEMS HAVE BEEN INCLUDED IN THE SUMMARY OF QUANTITIES.

THE CONTRACTOR WILL BE REQUIRED TO SUBMIT CERTFICATION STATEMENT (NPDES ATTACHMENT 6). FULL COMPLIANCE WITH ALL TERMS OF THE NPDES PERMIT MUST BE STRICTLY ADHERED TO.

DRAINAGE STRUCTURE INLET FILTERS ARE TO BE PROVIDED AND MAINTAINED FOR ALL EXISTING AND PROPOSED DRAINAGE STRUCTURE WITHIN THE PROJECT LIMITS AND ALL STRUCTURES NOTED FOR INLET AND PIPE PROTECTION AS DIRECTED BY THE ENGINEER. PAY ITEMS, DETAILS AND SPECIAL PROVISIONS HAVE BEEN INCLUDED IN THE SUMMARY OF QUANTITIES, SPECIAL PROVISIONS, AND PLAN DETAILS FOR THIS WORK.

- 4. SEE STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. PROPOSED STRUCTURE SHALL BE BURIED AND TEMPORARILY COVERED WITH STEEL PLATE OF 0.25 INCH MINIMUM THICKNESS OR OF THICKNESS SPECIFIED AND APPROVED BY THE ENGINEER. PAYMENT FOR THE INSTALLATION AND REMOVAL OF THE STEEL PLATE INCLUDING ANY REQUIRED EXCAVATION SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.

- TEMPORARY PIPE CULVERT SHALL BE TEMPORARILY CONNECTED TO THE EXISTING 30" STORM SEWER AND TO THE INSTALLED PROPOSED 24" STORM SEWER. PAYMENT FOR THESE TEMPORARY CONNECTIONS SHALL BE CONSIDERED INCLUDED IN THE UNIT PRICE OF "PIPE CULVERT, CLASS C, TYPE 1, 12" (TEMPORARY)".
- PROPOSED LATERAL STORM SEWERS SHALL BE INSTALLED IN STAGE 1 AND STAGE 1A, RESPECTIVELY. SEE MOT STAGES 1 AND 1A FOR WORKZONE LIMIT INFORMATION.


DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN

STAGE 1, 1A, 1B AND 1C ILLINOIS ROUTE 59

ILLINOIS DEPARTMENT OF TRANSPORTATION

SCALE AS SHOWN DATE MARCH 18, 2008


DRAWN BY CHECKED BY HME



CONTRACT NO. 62417

17	FAP RTE.		SE	CT10N			COUNT		TAI, SETS	SHEET	
	338	(113	&	114)	R-5	WILL			52	5	332
	STA.	+0	0		TO STA. 3218+00						
	FED. 8		IU.IN	015	FAP	338	(IL.	RTE	E. 59)		





# EROSION CONTROL LEGEND

 $\boxtimes$ 

INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE

TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK AND EROSION CONTROL BLANKET TEMPORARY DITCH CHECK INSTALLED TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE --~> FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) TEMPORARY PAVEMENT PROPOSED STORM SEWER (SEE NOTE 5) PROPOSED STORM SEWER INSTALLED DRAINAGE STRUCTURE TO BE CLEANED IN PREVIOUS STAGE TEMPORARY PIPE CULVERT SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) TEMPORARY PIPE CULVERT INSTALLED SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE

AND EROSION CONTROL BLANKET (681 SQ. YDS.)

## NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. PROPOSED STRUCTURE SHALL BE BURIED AND TEMPORARILY COVERED WITH STEEL PLATE OF 0.25 INCH MINIMUM THICKNESS OR OF THICKNESS SPECIFIED AND APPROVED BY THE ENGINEER. PAYMENT FOR THE INSTALLATION AND REMOVAL OF THE STEEL PLATE INCLUDING ANY REQUIRED EXCAVATION SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.



ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
STAGE 1, 1A, 1B AND 1C
ILLINOIS ROUTE 59


SCALE AS SHOWN
DATE MARCH 18, 2008

DRAWN BY BSB
CHECKED BY HME

CONTRACT NO. 62417

| Total Section | County | Section | Section | County | Section | Section | County | Section | S





# EROSION CONTROL LEGEND

TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET

TEMPORARY EROSION CONTROL SEEDING
AND EROSION CONTROL BLANKET INSTALLED
IN PREVIOUS STAGE

PERMANENT LANDSCAPING (SEE NOTE 3)

ROL

--∕->

TEMPORARY DITCH CHECK

IN PREVIOUS STAGE

(SEE SEE NOTE 5)

IN PREVIOUS STAGE

IN PREVIOUS STAGE

TEMPORARY PIPE CULVERT

TEMPORARY DITCH CHECK INSTALLED

PERMANENT DRAINAGE STRUCTURE NUMBER

PROPOSED STORM SEWER (SEE NOTE 5)

PROPOSED STORM SEWER INSTALLED

TEMPORARY PIPE CULVERT INSTALLED

FLOW DIRECTION (SEE NOTE 4)

TEMPORARY PAVEMENT

DRAINAGE STRUCTURE TO BE CLEANED

SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2)

SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE

INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE

# NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- 6. PROPOSED STRUCTURE SHALL BE BURIED AND TEMPORARILY COVERED WITH STEEL PLATE OF 0.25 INCH MINIMUM THICKNESS OR OF THICKNESS SPECIFIED AND APPROVED BY THE ENGINEER. PAYMENT FOR THE INSTALLATION AND REMOVAL OF THE STEEL PLATE INCLUDING ANY REQUIRED EXCAVATION SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.

50 0 50 100 SCALE IN FEET

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG

EROSION CONTROL PLAN STAGE 1, 1A, 1B AND 1C ILLINOIS ROUTE 59


SCALE AS SHOWN
DATE MARCH 18, 2008

DRAWN BY BSB
CHECKED BY HME

SECTION CONTRACT NO. 62417 525 334 338 (113 & 114) R-5 WILL TA- 3232+00 TO STA. 3246+00

FED. ROAD DIST. NO. ILLINOIS FAP 338 (IL RTE. 59)





# EROSION CONTROL LEGEND


TEMPORARY EROSION CONTROL SEEDING V V V TEMPORARY DITCH CHECK AND EROSION CONTROL BLANKET TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK INSTALLED AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE --∕-> FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) TEMPORARY PAVEMENT PROPOSED STORM SEWER (SEE NOTE 5) PROPOSED STORM SEWER INSTALLED DRAINAGE STRUCTURE TO BE CLEANED C IN PREVIOUS STAGE SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) TEMPORARY PIPE CULVERT TEMPORARY PIPE CULVERT INSTALLED SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE  $\boxtimes$ INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE

## NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.


PROPOSED STRUCTURE SHALL BE BURIED AND TEMPORARILY COVERED WITH STEEL PLATE OF 0.25 INCH MINIMUM THICKNESS OR OF THICKNESS SPECIFIED AND APPROVED BY THE ENGINEER. PAYMENT FOR THE INSTALLATION AND REMOVAL OF THE STEEL PLATE INCLUDING ANY REQUIRED EXCAVATION SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.





ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGE 1, 1A, 1B AND 1C ILLINOIS ROUTE 59

SCALE AS SHOWN DATE MARCH 18, 2008

DRAWN BY CHECKED BY HME








ILLINOIS ROUTE 59


DRAWN BY BSB

CHECKED BY \_\_HME\_

SCALE AS SHOWN

DATE MARCH 18, 2008





INLET FILTER INSTALLED IN PREVIOUS STAGE


ILLINOIS DEPARTMENT OF TRANSPORTATIO
DISTRICT NO. 1 SCHAUMBURG

EROSION CONTROL PLAN
STAGE 1, 1A, 1B AND 1C
ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008

SCALE IN FEET

CHECKED BY HME




 $\boxtimes$ 

TEMPORARY EROSION CONTROL SEEDING V V V TEMPORARY DITCH CHECK AND EROSION CONTROL BLANKET TEMPORARY DITCH CHECK INSTALLED TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE --∕-> FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) TEMPORARY PAVEMENT PROPOSED STORM SEWER (SEE NOTE 5) PROPOSED STORM SEWER INSTALLED С DRAINAGE STRUCTURE TO BE CLEANED IN PREVIOUS STAGE TEMPORARY PIPE CULVERT SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) TEMPORARY PIPE CULVERT INSTALLED SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE  $\boxtimes$ INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE


- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 1 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- PROPOSED STRUCTURE SHALL BE BURIED AND TEMPORARILY COVERED WITH STEEL PLATE OF 0.25 INCH MINIMUM THICKNESS OR OF THICKNESS SPECIFIED AND APPROVED BY THE ENGINEER, PAYMENT FOR THE INSTALLATION AND REMOVAL OF THE STEEL PLATE INCLUDING ANY REQUIRED EXCAVATION SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.
- TEMPORARY PIPE CULVERT SHALL BE TEMPORARILY CONNECTED TO THE EXISTING STORM SEWER AND TO THE PROPOSED MANHOLE, PAYMENT FOR TEMPORARY CONNECTIONS SHALL BE CONSIDERED INCLUDED IN THE UNIT PRICE OF "PIPE CULVERT, CLASS C, TYPE 1, 12" (TEMPORARY)".



EROSION CONTROL PLAN STAGE 1, 1A, 1B AND 1C ILLINOIS ROUTE 59

SCALE AS SHOWN DATE MARCH 18, 2008

DRAWN BY CHECKED BY \_\_\_HME



 $\boxtimes$ 

INLET FILTER INSTALLED IN PREVIOUS STAGE

ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED


STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPARATELY
THE COST FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST
OF THE PROPOSED STRUCTURE.

50 0 50 100 SCALE IN FEET ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
STAGES 2, 2A, 2B, 2C & 2D
ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008







TEMPORARY EROSION CONTROL SEEDING V V V AND EROSION CONTROL BLANKET TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE PERMANENT LANDSCAPING (SEE NOTE 3) DRAINAGE STRUCTURE TO BE CLEANED SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE

 $\boxtimes$ INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE



### TEMPORARY DITCH CHECK

TEMPORARY DITCH CHECK INSTALLED IN PREVIOUS STAGE

FLOW DIRECTION (SEE NOTE 4)

--^->

PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5)

PROPOSED STORM SEWER (SEE NOTE 5)

PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE


TEMPORARY PIPE CULVERT

TEMPORARY PIPE CULVERT INSTALLED IN PREVIOUS STAGE

### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPERATELY. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.




ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG

> EROSION CONTROL PLAN STAGES 2, 2A, 2B, 2C & 2D ILLINOIS ROUTE 59

SCALE AS SHOWN DATE MARCH 18, 2008

CONTRACT NO. 62417 | FAB. | SECTION | COUNTY | SECTION |





### EROSION CONTROL LEGEND

TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK v v v AND EROSION CONTROL BLANKET TEMPORARY DITCH CHECK INSTALLED TEMPORARY EROSION CONTROL SEEDING IN PREVIOUS STAGE AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) DRAINAGE STRUCTURE TO BE CLEANED PROPOSED STORM SEWER (SEE NOTE 5) SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE SEDIMENT CONTROL SILT FENCE INSTALLED TEMPORARY PIPE CULVERT IN PREVIOUS STAGE TEMPORARY PIPE CULVERT INSTALLED  $\boxtimes$ INLET FILTER IN PREVIOUS STAGE INLET FILTER INSTALLED IN PREVIOUS STAGE

### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR
  TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE
  ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL
  COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED
  CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPERATELY. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.


ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGES 2, 2A, 2B, 2C & 2D ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008

SCALE IN FEET







 $\boxtimes$ 

V V V TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT SEEDING INSTALLED IN PREVIOUS STAGE

DRAINAGE STRUCTURE TO BE CLEANED SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE

SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE

TEMPORARY DITCH CHECK INSTALLED IN PREVIOUS STAGE --∕-> FLOW DIRECTION (SEE NOTE 4) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) PROPOSED STORM SEWER (SEE NOTE 5) PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE TEMPORARY PIPE CULVERT TEMPORARY PIPE CULVERT INSTALLED


IN PREVIOUS STAGE

TEMPORARY DITCH CHECK

# NOTES


- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.


6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPERATELY. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.



ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGES 2, 2A, 2B, 2C & 2D ILLINOIS ROUTE 59

SCALE AS SHOWN DATE MARCH 18, 2008





### NOTES

- . THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION..

STAGES 2,


50 50 100 ILLING

SCALE IN FEET SCALE AS SHOWN


ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG

EROSION CONTROL PLAN
STAGES 2, 2A, 2B, 2C & 2D
ILLINOIS ROUTE 59


SCALE AS SHOWN
DATE MARCH 18, 2008







### EROSION CONTROL LEGEND



### NOTES

- 1. THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.


6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPERATELY. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
STAGES 2, 2A, 2B, 2C & 2D
ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008

SCALE IN FEET


DRAWN BY REW JCM



CONTRACT NO. 62417

525 349 WILL STA: 3302+00 TO STA, 3316+00 FED. HOAD DIST. NO. RLINOIS FAP 338 (IL RTE. 59)





### EROSION CONTROL LEGEND

TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK AND EROSION CONTROL BLANKET TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK INSTALLED AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) DRAINAGE STRUCTURE TO BE CLEANED PROPOSED STORM SEWER (SEE NOTE 5) SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE SEDIMENT CONTROL SILT FENCE INSTALLED TEMPORARY PIPE CULVERT IN PREVIOUS STAGE TEMPORARY PIPE CULVERT INSTALLED INLET FILTER IN PREVIOUS STAGE

INLET FILTER INSTALLED IN PREVIOUS STAGE

# NOTES

THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.

- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION..


EROSION CONTROL PLAN STAGES 2, 2A, 2B, 2C & 2D ILLINOIS ROUTE 59 SCALE AS SHOWN


DATE MARCH 18, 2008

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT NO. 1 SCHAUMBURG







### NOTES


- 1. THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR
  TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE
  ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL
  COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED
  CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 2 CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- 6. THE COST OF PLUGGING TEMPORARY PIPE SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR PIPE CULVERT (TEMPORARY) OF THE CLASS, TYPE AND SIZE SPECIFIED.

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
STAGES 2, 2A, 2B, 2C & 2D
ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008

SCALE IN FEET

CHECKED BY JCM



TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK AND EROSION CONTROL BLANKET TEMPORARY DITCH CHECK INSTALLED TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (27) (SEE SEE NOTE 5) С DRAINAGE STRUCTURE TO BE CLEANED PROPOSED STORM SEWER (SEE NOTE 5) SEDIMENT CONTROL. SILT FENCE (SEE NOTE 2) PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE TEMPORARY PIPE CULVERT  $\boxtimes$ TEMPORARY PIPE CULVERT INSTALLED INLET FILTER IN PREVIOUS STAGE

INLET FILTER INSTALLED IN PREVIOUS STAGE

# GENERAL EROSION CONTROL NOTES:

TREE TRUNK PROTECTION, TREE ROOT PRUNING, AND TREE PRUNING WILL BE REQUIRED FOR THIS PROJECT. A REPRESENTATIVE FROM IDOT'S ROADSIDE DEVELOPMENT UNIT WILL DETERMINE LOCATIONS ON SITE AT THE START OF CONSTRUCTION. PAY ITEMS HAVE BEEN INCLUDED IN THE SUMMARY OF

THE CONTRACTOR WILL BE REQUIRED TO SUBMIT CERTFICATION STATEMENT (NPDES ATTACHMENT 6). FULL COMPLIANCE WITH ALL TERMS OF THE NPDES PERMIT MUST BE STRICTLY ADHERED TO.

DRAINAGE STRUCTURE INLET FILTERS ARE TO BE PROVIDED AND MAINTAINED FOR ALL EXISTING AND PROPOSED DRAINAGE STRUCTURE WITHIN THE PROJECT LIMITS AND ALL STRUCTURES NOTED FOR INLET AND PIPE PROTECTION AS DIRECTED BY THE ENGINEER. PAY ITEMS, DETAILS AND SPECIAL PROVISIONS HAVE BEEN INCLUDED IN THE SUMMARY OF QUANTITIES, SPECIAL PROVISIONS, AND PLAN DETAILS FOR THIS WORK.

### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 3 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPARATELY. THE COST FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.

ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGES 3, 3A, AND 3B ILLINOIS ROUTE 59

SCALE AS SHOWN DATE MARCH 18, 2008 DRAWN BY \_\_REW CHECKED BY JCM


WILL 525 351

TO STA. 3204+00

CONTRACT NO. 62417

,	FAP RTE.	SECTION				cou	′	TOTAL SHE SHEETS N			
	338	(113	&	114)	R-5	WI	LL		58	5 3	352
	STA.	3204	+0	0		TO STA.	32	218+0	00		
	FED. F	ROAD DEST	, NO.		ILLIN	ots F/	٩P	338	(IL	RTE.	59)





### EROSION CONTROL LEGEND

TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK V V V AND EROSION CONTROL BLANKET TEMPORARY DITCH CHECK INSTALLED TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) DRAINAGE STRUCTURE TO BE CLEANED PROPOSED STORM SEWER (SEE NOTE 5) SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE TEMPORARY PIPE CULVERT  $\boxtimes$ INLET FILTER TEMPORARY PIPE CULVERT INSTALLED IN PREVIOUS STAGE INLET FILTER INSTALLED IN PREVIOUS STAGE

### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 3 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- 6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPARATELY THE COST FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.





DATE MARCH 18, 2008

ILLINOIS DEPARTMENT OF TRANSPORTATION


DISTRICT NO. 1 SCHAUMBURG

CONTRACT NO. 62417 | The contract of the contr





### EROSION CONTROL LEGEND



### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 3 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPARATELY. THE COST FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.


ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
STAGES 3, 3A AND 3B
ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008

SCALE IN FEET

17	FAP RTL		SE	CTION		COUNTY			ZHEE	SHEET	
•	338	(113	&	114)	R-5	W	ILL		52:	5	354
	STA.	STA- 3232+00				TO STA	32	246+0	00		
	PED. I	FED, ROAD DIST, NO.		TLLTN	ots F	ΑP	338	(IL	RTE	E. 59)	





 $\boxtimes$ 

 $\boxtimes$ 

INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE

TEMPORARY EROSION CONTROL SEEDING TEMPORARY DITCH CHECK V V V AND EROSION CONTROL BLANKET TEMPORARY DITCH CHECK INSTALLED TEMPORARY EROSION CONTROL SEEDING IN PREVIOUS STAGE AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE FLOW DIRECTION (SEE NOTE 4) PERMANENT LANDSCAPING (SEE NOTE 3) PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5) PERMANENT SEEDING INSTALLED IN PREVIOUS STAGE PROPOSED STORM SEWER (SEE NOTE 5) PROPOSED STORM SEWER INSTALLED С DRAINAGE STRUCTURE TO BE CLEANED IN PREVIOUS STAGE TEMPORARY PIPE CULVERT SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2) TEMPORARY PIPE CULVERT INSTALLED SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE IN PREVIOUS STAGE

### NOTES


- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR
  TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE
  ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL
  COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED
  CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 3 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- 6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPARATELY. THE COST FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.

EROSION CONTROL PLAN
STAGES 3, 3A AND 3B

O 50 100
ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008

ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG



TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET

TEMPORARY EROSION CONTROL SEEDING
AND EROSION CONTROL BLANKET INSTALLED
IN PREVIOUS STAGE

PERMANENT LANDSCAPING (SEE NOTE 3)

DRAINAGE STRUCTURE TO BE CLEANED

SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2)

SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE

INLET FILTER

С

INLET FILTER INSTALLED IN PREVIOUS STAGE



TEMPORARY DITCH CHECK

TEMPORARY DITCH CHECK INSTALLED IN PREVIOUS STAGE

FLOW DIRECTION (SEE NOTE 4)

PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5)

PROPOSED STORM SEWER (SEE NOTE 5)


PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE

TEMPORARY PIPE CULVERT

TEMPORARY PIPE CULVERT INSTALLED
IN PREVIOUS STAGE


### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 3 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.



ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT NO. 1 SCHAUMBURG
EROSION CONTROL PLAN
STAGES 3, 3A AND 3B
ILLINOIS ROUTE 59


SCALE AS SHOWN
DATE MARCH 18, 2008



CONTRACT NO. 62417

| SECTION | COUNTY | SHEET | MOTAL | SHEET | S





### EROSION CONTROL LEGEND

TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET



TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE



PERMANENT LANDSCAPING (SEE NOTE 3)



DRAINAGE STRUCTURE TO BE CLEANED



SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2)



SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE



INLET FILTER



INLET FILTER INSTALLED IN PREVIOUS STAGE



TEMPORARY DITCH CHECK

FLOW DIRECTION (SEE NOTE 4)



TEMPORARY DITCH CHECK INSTALLED IN PREVIOUS STAGE



PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5)



PROPOSED STORM SEWER (SEE NOTE 5)



PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE


TEMPORARY PIPE CULVERT



TEMPORARY PIPE CULVERT INSTALLED IN PREVIOUS STAGE


### NOTES

- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 3 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.
- 6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPARATELY. THE COST FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.



ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGES 3, 3A AND 3B ILLINOIS ROUTE 59

SCALE AS SHOWN
DATE MARCH 18, 2008



V V V TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET

TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET INSTALLED IN PREVIOUS STAGE

PERMANENT LANDSCAPING (SEE NOTE 3)

PERMANENT LANDSCAPING INSTALLED IN PREVIOUS STAGE

DRAINAGE STRUCTURE TO BE CLEANED

SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2)

SEDIMENT CONTROL SILT FENCE INSTALLED IN PREVIOUS STAGE

 $\boxtimes$ INLET FILTER

INLET FILTER INSTALLED IN PREVIOUS STAGE



TEMPORARY DITCH CHECK INSTALLED IN PREVIOUS STAGE

FLOW DIRECTION (SEE NOTE 4)

PERMANENT DRAINAGE STRUCTURE NUMBER (SEE SEE NOTE 5)

PROPOSED STORM SEWER (SEE NOTE 5)

PROPOSED STORM SEWER INSTALLED IN PREVIOUS STAGE

TEMPORARY PIPE CULVERT

TEMPORARY PIPE CULVERT INSTALLED IN PREVIOUS STAGE

### NOTES


- THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR CHANGED CONSTRUCTION LIMITS.
- 2. SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT, AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS.
- 4. SEE STAGE 4 OF THE FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.

6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPERATELY. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.



ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGES 4 & 4A ILLINOIS ROUTE 59


SCALE AS SHOWN DATE MARCH 18, 2008



CONTRACT NO. 62417

7	RTE.		JL	CITOIS			000	13.4		SHE	ETS	N	ir)
	338	(113	&	114)	R-5		WI	LL		52	:5	36	0
	STA.	3302	2+0	00		TO:	STA.	3	316+0	00			
	FEO. I	ROAD UIST	, NO.		ILLIN	OLZ	F/	٩P	338	(IL	RTE.	. 5	9)





TEMPORARY DITCH CHECK

IN PREVIOUS STAGE

IN PREVIOUS STAGE

IN PREVIOUS STAGE

TEMPORARY DITCH CHECK INSTALLED

FLOW DIRECTION (SEE NOTE 4)

NUMBER (SEE SEE NOTE 5)

TEMPORARY PIPE CULVERT

PERMANENT DRAINAGE STRUCTURE

PROPOSED STORM SEWER (SEE NOTE 5)

PROPOSED STORM SEWER INSTALLED

TEMPORARY PIPE CULVERT INSTALLED

### EROSION CONTROL LEGEND

, , , , , ,

TEMPORARY EROSION CONTROL SEEDING AND EROSION CONTROL BLANKET

TEMPORARY EROSION CONTROL SEEDING
AND EROSION CONTROL BLANKET INSTALLED



PERMANENT LANDSCAPING (SEE NOTE 3)



PERMANENT LANDSCAPING INSTALLED IN PREVIOUS STAGE



DRAINAGE STRUCTURE TO BE CLEANED

SEDIMENT CONTROL, SILT FENCE (SEE NOTE 2)
SEDIMENT CONTROL SILT FENCE INSTALLED



INLET FILTER

IN PREVIOUS STAGE



INLET FILTER INSTALLED IN PREVIOUS STAGE

### NOTES

- 1. THE CONSTRUCTION LIMITS WILL BE STAKED BY THE ENGINEER
  PRIOR TO COMMENCING CONSTRUCTION. THE CONSTRUCTION LIMITS
  MAY BE ADJUSTED BY THE ENGINEER TO PRESERVE TREES AND NO
  ADDITIONAL COMPENSATION WILL BE PAID TO THE CONTRACTOR FOR
  CHANGED CONSTRUCTION LIMITS.
- SEDIMENT CONTROL, SILT FENCE SHALL BE ERECTED ADJACENT TO R.O.W., EASEMENT AND CONTRUCTION LIMITS AND AS DIRECTED BY THE ENGINEER.
- 3. SEE LANDSCAPING PLANS FOR SEEDING INFORMATION.
- 4. SEE STAGE 4 OF FINAL CROSS SECTIONS FOR GRADING INFORMATION.
- 5. SEE PROPOSED DRAINAGE PLANS FOR STORM SEWER INFORMATION.


6. ANY REQUIRED ADJUSTMENT AND/OR RECONSTRUCTION OF THE PROPOSED STRUCTURE TO FINAL RIM ELEVATION SHALL NOT BE PAID FOR SEPERATELY. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE COST OF THE PROPOSED STRUCTURE.





ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG EROSION CONTROL PLAN STAGES 4, & 4A ILLINOIS ROUTE 59


SCALE AS SHOWN
DATE MARCH 18, 2008


DRAWN BY BSB
CHECKED BY JCM














STORY COLOR	V-10-20-0-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	<u> </u>	SUMMAI	RY OF QUANTITIES				
County   Teach   Proceedings   1.1.   100   15	DESIGNATION	UNIT						PROPOSED INTERCONNEC
SOLID   T. 1900-1-2, P. D. 50-9000 C. 1975   100   1	SIGN PANEL - TYPE 1	SQ FT	102	45	31,5	25.5	-	_
20021   1 1970-   1 1971	CONDUIT IN TRENCH, 2" DIA., GALVANIZED STEEL	FOOT	6652	508	T700740.W7004404		-	5051
Company   Comp	CONDUIT IN TRENCH, 21/2" DIA., GALVANIZED STEEL	FOOT	322	32	82	208	_	-
Company   Print   Pr	CONDUIT IN TRENCH, 3" DIA., GALVANIZED STEEL	FOOT	38	38	V1	_		-
COUNTY   PRINTED   P. C., CO MARTEN STOT   150   46   1	CONDUIT IN TRENCH, 4" DIA., GALVANIZED STEEL				34	16	-	-
COUNTRY   PRINTS   COUNTRY   COUNT					49	78	-	562
CARREL FAMILY OF ALL SALVANIES STOCK    DOS   4-8   184							-	
MACHONE   12.50   5	· · · · · · · · · · · · · · · · · · ·							-
MONTH   MARCHEST   M								
CHANGE A SACRÉES   CO.   C.   C.   C.   C.   C.   C.   C								8
## BRICK MATERIAL FOR FLEETINGS, 1988   100   1720   155   15   29   508				· · · · · · · · · · · · · · · · · · ·				-
MANISTRANCE OF MANISTRANCE AND ACCOUNTS OF STORM MINISTRAL STORM MANISTRANCE OF STORM MANISTRANCE OF MANISTRANC								5051
PAGE   ACT   CORT   SCRIPP, PRICE	MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION		***					
MARCHARY - PRINC CRIEF   D.	FULL-ACTUATED CONTROLLER AND TYPE IV CABINET, SPECIAL	EACH		1	1	1	_	
ELOTING CASE, IN COORDIT, SOURCE NO. 19 30	TRANSCEIVER - FIBER OPTIC	EACH	3		1	1		-
LLCPRC CABLE PLOODUT, SIDNA, NO. 16 TC	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C	FOOT	1676.5	969	382	325.5	-	-
LLEATING CARRY IN COUNTY, 125-08, Mo. 6 TC	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C		3104.5	1660	770	674.5	-	-
	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C			<u> </u>	856	988		
REFIELD MANE DE CONTROL DE PARTE DE TEL DE		~~~~				635.5		-
TRAFFE SOME POST, DALWARDS STEEL 19 FT,  SERVEY SOME POST, DALWARDS STEEL 19 F							-	-
TRAFFIC SHOWN POST, GALVANIZED STEEL BY FT.   5.000   1								
SILE, MAST, RAW, ASSEMBLY, AND POLE, 22 FT.  STORE, MAST, RAW, ASSEMBLY, AND POLE, 23 FT.  STORE, MAST, RAW, ASSEMBLY, AND POLE, 25 FT.  STORE, MAST, RAW, AND POLE, 25 FT.  STORE, MAST, RAW, ASSEMBLY, AND POLE, 25 FT.  STORE, MAST, RAW, ASSEMBLY, AND POLE, 25 FT.  STORE, MAST, RAW, AND POLE, 25 FT.  STORE, MAST, RAW, ASSEMBLY, AND POLE, 25 FT.  STORE, MAST, RAW, ASSEMBLY, AND POLE, 25 FT.  STORE, MAST, RAW, AND POLE, 25 FT.  STORE, MAST, RAW, AND POLE, 25 FT.  STORE, MAST, RAW, AND						<del></del>	<del></del>	-
SIEL MET AND ASSEMBLY AND POLE, 30 FT.   SACH   1   -						· · · · · · · · · · · · · · · · · · ·		-
STEEL MAST ARM ASSEMBLY AND POLIC, 38 - 1.   .   .   .   .   .   .   .   .   .								-
STRE. MSST ARM SSERBLY AND PORE, 39 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 29 FT. MO 90 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 90 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 90 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARM SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARMS AND SSERBLY AND PORE STITL ONLY MSST ARMS, 39 FT. MO 94 FT.  SIEL MSST ARMS AND SSERBLY AND PORE STITL ONLY MSST ARMS AND STATE STITL ONLY MSST ARMS AND STATE STITL ONLY MSST ARMS AND STATE S								-
SIELE MAST ARM ASSEMBLY AND POLF, 52 FT.   SACH   1   1   1   1   1   1   1   1   1							<u> </u>	
STEEL MAST ARM ASSEMBLY AND POLIC WITH DUAL, MAST ARMS, 38 FT, AND 94 FT   EACH   1   1   -   -								
STEEL MAST ARM ASSEMBLY AND POLE WITH DUAL MAST ARMS, 38 FT, AND 44 FT	STEEL MAST ARM ASSEMBLY AND POLE WITH DUAL MAST ARMS, 28 FT. AND 50 FT.	EACH		1		_	-	
CONCRETE FOUNDATION, 179E E 30-10c1 DIAMETER	STEEL MAST ARM ASSEMBLY AND POLE WITH DUAL MAST ARMS, 38 FT. AND 44 FT	EACH	1			-		-
CONCRETE FOUNDATION, TYPE F. 30-DOW, DIAMETER   FOOT   45   50   50   15   5   5	CONCRETE FOUNDATION, TYPE A	FOOT	28	-	12	16		
CONCRETE SOUNDATION, LYPE E SE-INCH DAMPTER  FOOT  IDS  30  60  15	CONCRETE FOUNDATION, TYPE C	FOOT	12	4	4	4	-	
DRILL EXISTING NAMBHOUE  SIGNAL PEAD, 1-ACR, 3-SECTION, MAST ARM MOUNTED  SECULATED, 1-ACR, 3-SECTION, MAST ARM MOUNTED  SECULATED, 1-ACR, 3-SECTION, MAST ARM MOUNTED  EACH 11 4 4 4 3 3 - 2 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3	AND THE RESERVE TO THE PARTY OF							-
SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST ARM MOUNTED  EACH 11 4 4 6 3  SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED  EACH 2 2  SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED  EACH 10 1  SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED  EACH 11 1  SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED  EACH 11 1  SIGNAL HEAD, LED, 1-FACE, SACCTION, BRACKET MOUNTED  EACH 11 1  SIGNAL HEAD, LED, 1-FACE, SACCTION, BRACKET MOUNTED  EACH 11 1  SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED  EACH 6 2 2 2 2 2				<del> </del>	60		MA.	
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED							**	3
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED   EACH   1							-	
SIGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST ARM MOUNTED   EACH   11   6   4   1   -   -   -							-	***
SIONAL HEAD, LED, 2-FACE, 1-3 SECTION, 1-5 SECTION, BRACKET MOUNTED  EACH 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	No. 20 10 10 10 10 10 10 10 10 10 10 10 10 10						-	
PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED			1		4	1	-	-
PEDESTRAN SIGNAL HEAD, LED, 2-FACE, BRACKET MOUNTED	PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED		6		2	2	_	
RAFFIC SIGNAL BACKPLATE   EACH   12	PEDESTRIAN SIGNAL HEAD, LED, 2-FACE, BRACKET MOUNTED	EACH	2	-			_	
NOUTIVE LOOP DETECTOR	TRAFFIC SIGNAL BACKPLATE			_			#	
EACH   6   2   2   2   2   3   -   -   -   -   -   -   -   -   -	TRAFFIC SIGNAL BACKPLATE, LOUVERED, ALUMINUM	EACH	10	10	=		-	-
EACH   3	INDUCTIVE LOOP DETECTOR	EACH	29	10	12	7	-	
PEDESTRIAN PUSH-BUTTON	LIGHT DETECTOR	EACH	6	2	2	2	-	
TEMPORARY TRAFFIC SIGNAL INSTALLATION EACH 2 - 1 1 1	LIGHT DETECTOR AMPLIFIER	EACH	3	1	î	1	-	-
MODIFY EXISTING CONTROLLER				2	3	3	-	-
REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT  EACH 2 - 11 1 1 REMOVE EXISTING HANDHOLE  EACH 19 - 10 5 4 REMOVE EXISTING CONCRETE FOUNDATION  EACH 12 - 9 3 3								
REMOVE EXISTING HANDHOLE  REMOVE EXISTING CONCRETE FOUNDATION  EACH 19 - 10 5 4							-	1
REMOVE EXISTING CONCRETE FOUNDATION  EACH 12 - 9 3 3 7550  PREFORMED DETECTOR LOOP  FOOT 7550 7550  PREFORMED DETECTOR LOOP  FOOT 2583 887 1239 457 - FOOT 2583 887 1239 887 1239 457 - FOOT 2583 887 1239 887							-	-
FOOT   7550   -								-
REFORMED DETECTOR LOOP FOOT 2583 887 1239 457								7550
EMPORARY TRAFFIC SIGNAL TIMING  EACH 2 - 1 1 1								1000
ERVICE INSTALLATION - POLE MOUNTED  EACH 3 1 1 1 1					. 1	1		-
SACH   3				1	1	1		_
FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125, MM12F SM12F F00T 7628 7628  ELECTRIC CABLE IN CONDUIT, GROUNDING, NO. 6 IC F00T 2037.5 493 799 745.5  ELECTRIC CABLE IN CONDUIT NO. 20 3/C, TWISTED, SHIELDED F00T 873 290 313 270  TEMPORARY TRAFFIC SIGNAL INTERCONNECTION SYSTEM L SUM 1 1	DERVICE INSTREEATION TOLE MODIFIED					1		
ELECTRIC CABLE IN CONDUIT, GROUNDING, NO. 6 IC FOOT 2037.5 493 799 745.5	UNINTERRUPTIBLE POWER SUPPLY					-		7628
TEMPORARY TRAFFIC SIGNAL INTERCONNECTION SYSTEM L SUM 1 1 - 1 -		F 001	1020					
	UNINTERRUPTIBLE POWER SUPPLY FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125, MM12F SM12F ELECTRIC CABLE IN CONDUIT, GROUNDING, NO. 6 1C			493	799	745.5	-	-
RE-OPTIMIZE TRAFFIC SIGNAL SYSTEM - LEVEL II EACH 1 1	UNINTERRUPTIBLE POWER SUPPLY FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125, MM12F SM12F ELECTRIC CABLE IN CONDUIT, GROUNDING, NO. 6 IC ELECTRIC CABLE IN CONDUIT NO. 20 3/C, TWISTED, SHIELDED	FOOT	2037.5					
	UNINTERRUPTIBLE POWER SUPPLY FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125, MM12F SM12F ELECTRIC CABLE IN CONDUIT, GROUNDING, NO. 6 IC ELECTRIC CABLE IN CONDUIT NO. 20 3/C, TWISTED, SHIELDED TEMPORARY TRAFFIC SIGNAL INTERCONNECTION SYSTEM	FOOT FOOT L SUM	2037.5 873 1	290	313	270	ph.	-

\* 100% COST TO VILLAGE OF PLAINFIELD

GANDHI AND ASSOCIATES, INC.
ENGINEERS AND PLANNERS
6035 N. NORTHWEST HIGHWAY
SUITE 306
CHICAGO, ILLINOIS 60631TEL. (773) 774-5910

F.A.P. RTE.	SEC	TION	COUNTY	TOTAL	SHEET
338	(113 &	114)R-5	WILL	525	367
STA.			TO	STA.	
FED. ROAD DI	ST. NO. 1	ILLIN	OIS FED. AID	PROJECT:	

CONTRACT # 62417

ILLINOIS DEPARTMENT OF TRANSPORTATION

SUMMARY OF QUANTITIES TRAFFIC SIGNAL INSTALLATION ILLINOIS ROUTE 59 FROM FRASER RD./FEENEY DR. TO US ROUTE 30


SCALE: N.T.S. DATE: 03/18/2008

REVISIONS
NAME DATE

DRAWN BY: BB,KP DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM

- 1. EACH PAIR OF LOOP WIRES SHALL BE PLACED IN A SEPARATE UNIT DUCT FROM THE EDGE OF PAVEMENT TO THE HANDHOLE. SPACING BETWEEN THE HOLES DRILLED IN THE PAVEMENT SHALL NOT BE LESS THAN 6" (150 mm). UNIT DUCT SHALL BE INCLUDED IN THE COST OF THE LOOP WIRE.
- 2. THE NUMBER OF LOOP TURNS SHALL BE AS RECOMMENDED BY THE AMPLIFIER MANUFACTURER. ALL ADJACENT SIDES OF THE LOOPS SHALL BE INSTALLED IN SUCH A WAY THAT THE CURRENT FLOW IS IN THE SAME DIRECTION TO REINFORCE ITS MAGNETIC FIELDS FOR SMALL VEHICLE DETECTION.
- 3. EACH LOOP LEAD-IN SHALL BE IDENTIFIED AND PERMANENTLY TAGGED IN THE HANDHOLE. EACH LEAD-IN CABLE TAG SHALL INDICATE THE LOCATION OF THE LOOP, LOOP ROTATION (CLOCKWISE/COUNTERCLOCKWISE), LOOP LEAD-IN DIRECTION (IN OR OUT), LOOP CABLE NUMBER AND LOCATION IN CABINET, AND NUMBER OF TURNS IN THE DETECTOR LOOPS IN WATER PROOF INK AS INDICATED ON THE DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAIL. THE CONTRACTOR SHALL MARK LOOP LOCATIONS ON RECORD DRAWINGS AND PRESENT TO THE ENGINEER AFTER FINAL INSPECTION. LOOPS SHALL BE MARKED BY LANE AND LOOP NUMBER. SEE DETAIL BELOW.
- 4. ALL LOOP CABLE SHALL BE FASTENED WITH PLASTIC TIE WRAP TO THE HANDHOLE HOOKS.
- 5. IN ASPHALT PAVEMENT, LOOPS SHOULD BE PLACED IN THE BINDER AND DIVEHOLES MARKED AT THE CURB WITH A SAW-CUT. THE SAW-CUT SHALL BE CUT IN ACCORDANCE WITH LOCAL AND E.P.A. DUST CONTROL REQUIREMENTS. DETECTOR LOOP(S) SHALL NOT BE INSTALLED IN WET CONDITIONS AND THE SAW-CUTS MUST BE FREE OF DEBRIS AND RESIDUE SUCH AS DUST AND WATER WHICH IS TO BE ACHIEVED BY THE USE OF COMPRESSED AIR, WIRE BRUSHING AND HEAT DRYING ACCORDING TO SEALANT MANUFACTURER REQUIREMENTS. THE DETECTOR WIRE SHALL BE HELD IN PLACE BY THE USE OF FORM WEDGES. WEDGES SHALL BE SPACED NO MORE THAN 18" (450 mm) APART.
- 6. LOOP SPLICES SHALL BE SOLDERED USING A SOLDERING IRON. BLOW TORCHES OR OTHER DEVICES WHICH OXIDIZE COPPER CABLE SHALL NOT BE ALLOWED FOR SOLDERING OPERATIONS. SEE DETAIL BELOW RIGHT.
- 7. PREFORMED DETECTOR LOOPS SHALL BE USED, AS SHOWN ON THE PLANS, WHERE NEW CONCRETE PAVEMENT IS PROPOSED. THE INSTALLATION OF PREFORMED LOOPS SHALL BE IN ACCORDANCE WITH THE DISTRICT 1 SPECIFICATIONS OR AS DIRECTED BY THE ENGINEER.


### LOOP LEAD-IN CABLE TAG



- A. LANE 1 IS THE LANE CLOSEST TO THE CENTERLINE OF THE ROADWAY
- B. LOOP #1 IS THE LOOP IN THE LANE CLOSEST TO THE INTERSECTION.
- C. LABEL LOOP CABLE "IN" OR LOOP CABLE "OUT".
- D. LABEL LOOP CABLE CLOCKWISE OR LOOP CABLE COUNTERCLOCKWISE.


COUNTY SECTION 525 368 338 (113 & 114)R-5 WILL STA. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT

CONTRACT # 62417




### DETECTOR LOOP WIRING SCHEMATIC

- LOOPS SHALL BE SPLICED IN SERIES.
- SAW-CUTS SHALL BE A MINIMUM WIDTH OF 5/16" (8 mm).
- SAW-CUT DEPTHS SHALL BE 3" (75 mm), IF IN CONCRETE. THE SAW-CUT DEPTH SHALL BE TO THE TOP OF THE REINFORCEMENT.
- LOOP CORNERS SHALL BE DRILLED WITH A 2" (50 mm) DIAMETER CORE.



DETAIL "A" LOOP-TO-LOOP SPLICE



DETAIL "B" LOOP-TO-CONTROLLER SPLICE

### LOOP DETECTOR SPLICE


- (1) WESTERN UNION SPLICE SOLDERED WITH ROSIN CORE FLUX. ALL EXPOSED SURFACES OF THE SOLDER SHALL BE SMOOTH.
- (2) WCSMW 30/100 HEAT SHRINK TUBE, MINIMUM LENGTH 3" (75 mm), UNDERWATER GRADE.
- (3) WCS 200/750 HEAT SHRINK TUBE, MINIMUM LENGHT 6" (150 mm), UNDERWATER GRADE.
- (4) NO. 14 2/C TWISTED, SHIELDED CABLE.
- (5) LOOP CONDUCTOR WITH FLEXIBLE PLASTIC TUBE.

ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAILS DRAWN BY: RWP DESIGNED BY: DAD CHECKED BY: DAZ SHEET 1 OF 4 SCALE: VERT. NONE

DATE 1-01-02

# TRAFFIC SIGNAL MAST ARM AND POST MAST ARM MOUNTED SIGNAL IN PROPOSED & FUTURE SIDEWALK AREA. INTERSECTION SHOWN WITH PEDESTRIAN SIGNAL AND PUSHBUTTON DETECTOR CURB, SHOULDER, OR EDGE OF PAVEMENT (SEE PLANS) 5' (1.5m) MAX.

### PEDESTRIAN SIGNAL PUSHBUTTON



RECOMMENDED PUSHBUTTON LOCATIONS FOR ACCESSIBLE PEDESTRIAN SIGNALS SHALL BE IN ACCORDANCE WITH THE CURRENT MUTCD (SEE NOTE 1). TO MEET MUTCD REQUIREMENTS, PEDESTRIAN SIGNAL PUSHBUTTONS MAY HAVE TO BE MOUNTED ON A SEPARATE POST.

### 

CONTRACT # 62417

### NOTES:

 AT ACCESSIBLE PEDESTRIAN SIGNAL LOCATIONS WITH PEDESTRIAN ACTUATION, EACH PUSHBUTTON SHALL ACTIVATE BOTH THE WALK INTERVAL AND THE ACCESSIBLE PEDESTRIAN SIGNALS.


AT ACCESSIBLE PEDESTRIAN SIGNAL LOCATIONS, PUSHBUTTONS SHOULD CLEARLY INDICATE WHICH CROSSWALK SIGNAL IS ACTUATED BY EACH PUSHBUTTON. PUSHBUTTONS AND TACTILE ARROWS SHOULD HAVE HIGH VISUAL CONTRAST (SEE THE DEPARTMENT OF JUSTICE'S AMERICANS WITH DISABILITIES ACT STANDARDS FOR ACCESSIBLE DESIGN, 1991). TACTILE ARROWS SHOULD POINT IN THE SAME DIRECTION AS THE ASSOCIATED CROSSWALK. AT CORNERS OF SIGNALIZED LOCATIONS WITH ACCESSIBLE PEDESTRIAN SIGNALS WHERE PEDESTRIAN PUSHBUTTONS ARE PROVIDED, THE PUSHBUTTONS SHOULD BE SEPARATED BY THE DISTANCE OF AT LEAST 10 FT (3m). THIS ENABLES PEDESTRIANS WHO HAVE VISUAL DISABILITIES TO DISTINGUISH AND LOCATE THE APPROPRIATE PUSHBUTTON.

PUSHBUTTONS FOR ACCESSIBLE PEDESTRIAN SIGNALS SHOULD BE LOCATED AS FOLLOWS:

- A: ADJACENT TO A LEVEL ALL-WEATHER SURFACE TO PROVIDE ACCESS FROM A WHEELCHAIR, AND WHERE THERE IS AN ALL WEATHER SURFACE, WHEELCHAIR ACCESSIBLE ROUTE TO THE RAMP.
- B: WITHIN 5 FT (1.5m) OF THE CROSSWALK EXTENDED.
- C: WITHIN 10 FT (3m) OF THE EDGE OF CURB, SHOULDER, OR PAVEMENT.
- D: PARALLEL TO THE CROSSWALK TO BE USED (SEE MUTCD FIGURE 4E-2).
- E: NORMAL PEDESTRIAN PUSHBUTTON MOUNTING HEIGHT SHOULD BE 3.5 FT (1.05m) ABOVE ADJACENT SIDEWALK
- 2. PEDESTRIAN SIGNAL FACES SHALL BE MOUNTED WITH THE BOTTOM OF THE HOUSING NOT LESS THAN 8 FT (2.4m) NOR MORE THAN 10 FT (3.0m) ABOVE THE SIDEWALK LEVEL AND SO THERE IS A PEDESTRIAN INDICATION IN THE LINE OF PEDESTRIANS' VISION WHICH PERTAINS TO THE CROSSWALK BEING USED.
- 3. THE BOTTOM OF THE HOUSING OF A VEHICLE SIGNAL FACE, NOT MOUNTED OVER A ROADWAY, SHALL BE AT LEAST 10 FT (3.0m) BUT NOT MORE THAN 15 FT (4.5m) ABOVE THE SIDEWALK OR, ABOVE THE PAVEMENT GRADE AT THE CENTER OF THE HIGHWAY IF NO SIDEWALKS EXIST.
- 4. THE BOTTOM OF THE HOUSING OF A VEHICLE SIGNAL FACE, MOUNTED OVER A ROADWAY, SHALL BE ACCORDING TO CURRENT STATE STANDARDS 877001 AND 877006. (16 FT (5m) MIN., 18 FT (5.5m) MAX., FROM HIGHEST POINT OF PAVEMENT)

### PEDESTRIAN SIGNAL POST

PEDESTRIAN SIGNAL HEAD AND PEDESTRIAN PUSHBUTTON DETECTOR LOCATION




# TABLE I

TRAFFIC SIGNAL EQUIPMENT	COMBINATION CONCRETE CURB AND GUTTER (MIN. DIST. FROM BACK OF CURB)	SHOULDER/NON-CURBED AREA (MIN. DIST. FROM EDGE OF PAVEMENT)
TRAFFIC SIGNAL MAST ARM POLE	6 FT (1,8m)	SHOULDER WIDTH + 2FT(0.6m), MINIMUM 10FT(3.0m)
TRAFFIC SIGNAL POST	4 FT (1.2m)	SHOULDER WIDTH + 2FT(0.6m), MINIMUM 10FT(3.0m)
PEDESTRIAN SIGNAL POST	4 FT (1.2m)	SHOULDER WIDTH + 2FT(0.6m), MINIMUM 10FT(3.0m)
PEDESTRIAN PUSHBUTTON	SEE NOTE !	SEE NOTE 1

DISTRICT 1
STANDARD TRAFFIC SIGNAL
DESIGN DETAILS


SCALE: VERT. NONE HORIZ. NONE DATE 1-01-02 DRAWN BY: RWP DESIGNED BY: DAD CHECKED BY: DAZ SHEET 2 OF 4



(SEE ALL CABLE PLAN, FOR ALL CABLE SIZES)


### ELECTRICAL SERVICE - PANEL DIAGRAM (TYPICAL FOR POLE AND GROUND MOUNTED SERVICE) SERVICE INSTALLATION POLE MOUNT (SHOWN)

-1/C GROUND (GREEN COLOR CODED)




**CABINET - BASE BOLT PATTERN** (NOT TO SCALE)

- - CAST CORNER FRAME WEB-UL LISTED GROUND -COMPRESSION CONNECTOR ANTI-CORROSION COMPOUND SHALL BE APPLIED ON ALL BOLT/ CONNECTION ASSEMBLIES: DETAIL "A" -STAINLESS STEEL NUT AND 2 STAINLESS



### DETAIL "B"



### HANDHOLE COVER & FRAME - GROUNDING DETAIL

(NOT TO SCALE)

(2) 1/2" x 1 1/4" STAINLESS STEEL BOLT WITH SPLIT LOCK WASHER AND NYLON INSERT LOCKOUT WELDED TO —7 FRAME AND TO COVER, (TYPICAL) HEAVY DUTY COPPER COMPRESSION GROUNDING TERMINAL. (TYPICAL) EXISTING HANDHOLE FRAME AND COVER GROUNDING CABLE (PAID FOR SEPARATELY)

**EXISTING HANDHOLE COVER & FRAME - GROUNDING DETAIL** 

(NOT TO SCALE)

NOTES:

GROUNDING SYSTEM


525 370 338 (113 & 114)R-5 WILL STA. TO STA. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT


COUNTY

CONTRACT # 62417

SECT10N

- THE GROUNDING SYSTEM SHALL CONSIST OF AN INSULATED CONDUCTOR TYPE XLP, NO. 6 A.W.C., STRANDED COPPER TO BE INSTALLED IN RACEWAYS. THE GROUNDING CABLE SHALL BE INSTALLED IN A CONTINUOUS MANNER AS SHOWN ON THE CABLE PLAN PROVIDED. ALL GROUNDING CONDUCTORS SHALL BE BONDED TO METAL ENCLOSURE (HANDHOLE, POST, MAST ARM, CONTROLLER, ETC.). GROUND ROD SHALL BE 3/4" DIA, x 10'~0" (20mm x 3.0m) LONG: COPPER CLAD, ONE GROUND ROD SHALL BE INSTALLED AT ALL POST FOUNDATIONS, POLE FOUNDATIONS, CONTROLLER CABINET FOUNDATION AND ELECTRICAL SERVICE INSTALLATION AS INDICATED ON THE CABLE PLAN. IF THERE ARE ANY SPECIAL CONDITIONS SUCH AS SUB-SURFACE CONDITIONS OR INSTALLATION PROBLEMS. THE RESIDENT ENGINEER SHALL BE NOTIFIED OR CONTACT THE BUREAU OF TRAFFIC, ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT ONE AT (847) 705-4139.
- 2. THE NEUTRAL CONDUCTOR AND THE GROUND CONDUCTOR SHALL BE CONNECTED IN THE SERVICE INSTALLATION. AT NO OTHER POINT IN THE TRAFFIC SIGNAL SYSTEM SHALL THE NEUTRAL AND GROUND CONDUCTORS BE CONNECTED.
- 3. ALL EQUIPMENT GROUNDING CONDUCTORS SHALL TERMINATE AT THE GROUND BUS IN THE CONTROLLER CABINET.
- 4. THE CONTRACTOR SHALL PROVIDE A GROUND CABLE WITH CONNECTORS BETWEEN THE HANDHOLE COVER AND HANDHOLE FRAME.








3/4" (20mm) HEAVY-DUTY GROUND ROD CLAMP (BURNDY TYPE GRC OR APPROVED EUAL)

· ALL CLAMPS SHALL BE BRONZE OR COPPER, UL APPROVED. • GROUND CABLE SHALL BE LOOPED OVER HOOKS IN THE HANDHOLES 6.5' (2.0m) SLACK SHALL BE PROVIDED IN SINGLE HANDHOLES 13' (4.0m) OF SLACK SHALL BE PROVIDED IN DOUBLE HANDHOLES. 5' (1.4m) OF SLACK SHALL BE PROVIDED BETWEEN FRAME AND COVER.




### MAST ARM POLE / POST-GROUNDING DETAIL

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAILS

SCALE: VERT. NONE DATE 1-01-02

DRAWN BY: RWP DESIGNED BY: DAD CHECKED BY: DAZ SHEET 3 OF 4



525 371

WILL

TO STA.

## NOTES FOR TEMPORARY TRAFFIC SIGNALS

- ALL CONTROL EQUIPMENT INCLUDING EMERGENCY PRE-EMPTION AND COMMUNICATION DEVICES FOR THE TEMPORARY TRAFFIC SIGNAL(S) SHALL BE FURNISHED BY THE CONTRACTOR.
- 2. ONLY CONTROLLERS SUPPLIED BY ONE OF THE DISTRICT APPROVED CLOSED LOOP EQUIPMENT MANUFACTURERS WILL BE APPROVED FOR USE AT TEMPORARY SIGNAL LOCATIONS. ALL CONTROLLERS USED FOR TEMPORARY TRAFFIC SIGNALS SHALL BE FULLY ACTUATED NEMA MICROPROCESSOR BASED WITH RS232 DATA ENTRY PORTS COMPATIBLE WITH EXISTING MONITORING SOFTWARE APPROVED BY IDOT DISTRICT 1. INSTALLED IN A NEMA TS1 OR TS2 CABINET. ONLY ONE BRAND OF CONTROLLER WILL BE ACCEPTED FOR ANY ONE CONTRACT.
- 3. ALL TRAFFIC SIGNAL SECTIONS AND PEDESTRIAN SIGNAL SECTIONS SHALL BE 12". HEADS SHALL BE PLACED AS INDICATED ON THE TEMPORARY TRAFFIC SIGNAL PLAN OR AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL FURNISH ENOUGH CABLE SLACK TO RELOCATE HEADS TO ANY POSITION ON THE SPAN WIRE OR AT LOCATIONS ILLUSTRATED ON THE PLANS FOR CONSTRUCTION STAGING. THE TEMPORARY TRAFFIC SIGNAL SHALL REMAIN IN OPERATION DURING ALL SIGNAL HEAD RELOCATIONS. EACH TEMPORARY TRAFFIC SIGNAL HEAD SHALL HAVE ITS DWN CABLE FROM THE CONTROLLER CABINET TO THE SIGNAL HEAD.
- 4. ALL EXISTING STREET NAME AND INTERSECTION REGULATORY SIGNS SHALL BE REMOVED FROM EXISTING POLES. RELOCATED AND SECURELY FASTENED TO THE SIGNAL SPAN WIRE OR WOOD POLE AS DIRECTED BY THE FNGINFER.
- 5. ANY TEMPORARY SIGNAL WITHIN AN EXISTING CLOSED LOOP TRAFFIC SIGNAL SYSTEM SHALL BE INTERCONNECTED TO THAT SYSTEM USING SIMILAR BRAND CONTROL EQUIPMENT.
- 6. THE TEMPORARY TRAFFIC SIGNAL SHALL HAVE THE SIGNAL HEAD DISPLAYS, SIGNAL HEAD PLACEMENTS AND CONTROLLER PHASING MATCH THE EXISTING TRAFFIC SIGNAL, AT THE TIME OF THE TURN ON, IF NO TRAFFIC STAGING IS IN PLACE OR WILL NOT BE STAGED ON THE DAY OF THE TURN ON.

THE FOLLOWING ITEMS SHALL BE REMOVED BY THE CONTRACTOR AND SHALL BE DISPOSED OF BY THEM OUTSIDE THE RIGH-OF-WAY AT THEIR EXPENSE. THE SALVAGE VALUE OF THE REMOVED EQUIPMENT SHALL BE REFLECTED IN THE CONTRACOR'S BID PRICE.

1 EACH CONTROLLER AND CABINET COMPLETE
2 EACH SIGNAL HEAD, 1-FACE 3-SECTION, BRACKET MOUNTED
6 EACH SIGNAL HEAD, 1-FACE 3-SECTION, MAST ARM MOUNTED
2 EACH SIGNAL HEAD, 1-FACE 5-SECTION, BRACKET MOUNTED
4 EACH SIGNAL HEAD, 1-FACE 5-SECTION, MAST ARM MOUNTED
5 EACH TRAFFIC SIGNAL BACK PLATE
6 EACH TRAFFIC SIGNAL POST

4 EACH STEEL MAST ARM ASSEMBLY AND POLE (22 FOOT, 30 FOOT,

36 FOOT, 42 FOOT)

1 FACH SERVICE INSTALLATION

THE FOLLOWING EXISTING TRAFFIC SIGNAL EQUIPMENT SHALL BE REMOVED BY THE CONTRACTOR, SHALL REMAIN THE PROPERTY OF THE AGENCY LISTED BELOW. THE CONTRACTOR SHALL SAFELY STORE AND ARRANGE FOR PICK UP OF ALL EQUIPMENT TO BE RETURNED TO THE LISTED AGENCY AS PER THE TRAFFIC SIGNAL SPECIFICATIONS.

AGENCY:

VILLAGE OF PLAINFIELD

CONTACT INFORMATION: MR. RANDY JESSEN PLAINFIELD PUBLIC WORKS 14400 COIL PLUS DRIVE PLAINFIELD, ILLINOIS 60544 PHONE: (815) 436-3577

2 EACH LIGHT DETECTOR

1 EACH LIGHT DETECTOR AMPLIFIER MODEL 452

2 ICK STA. 3294+29 STA. 3292+88-49FT LEFT 52FT LEFT S2B S2D ILL. RTE. 59 S2A S2D S2B **(50**) <u>5</u>18 S24 \$2B →\_\_ PS1 S2B S2C S10-S2 S2C S2D S2A S2D S2A S2B IIS1A 51B SA2 S20 - NOTE 1 TEMPORARY RADIO INTERCONNECT TO FORT BEGGS DR. (SEE TEMPORARY INTERCONNECT PLAN) STA. 3292+85-64FT RIGHT LSTA. 3294+20 56FT RIGHT TEMPORARY TRAFFIC SIGNAL PLAN STAGES: PRE-STAGE 1, STAGE 1, STAGE 1A, STAGE 1B, STAGE 1C, STAGE 2, STAGE 2A STAGE 2B, STAGE 2C, AND STAGE 2D

NOTE 1: THE CONTRACTOR IS RESPONSIBLE FOR COORDINATION WITH COMED FOR THE PROPOSED SERVICE LOCATION, IF NECCESARY THE TEMPORARY TRAFFIC SIGNAL CONTROLLER CAN BE LOCATED AT A MORE CONVENIENT LOCATION WITH THE APPROVAL OF THE ENGINEER, THE COST OF WHICH SHALL BE INCIDENTAL TO THE PAY ITEM "TEMPORARY TRAFFIC SIGNAL INSTALLATION".

NOTE 2: ALL THE VIDEO DETECTION ZONES SHALL BE REDEFINED FOR EACH CONSTRUCTION STAGE. THIS WORK IS INCIDENTAL TO THE PAY ITEM "TEMPORARY TRAFFIC SIGNAL INSTALLATION".

NOTE 3: THE ORIGINAL SIGNAL HEAD PLACEMENT FOR ALL APPROACHES OF THE INTERSECTION IS FOR EXISTING PAVEMENT GEOMETRICS (PSI), ADDITIONAL CONSTRUCTION STAGES, WHERE ORIGINAL SIGNAL HEAD PLACEMENT IS UTILIZED, ARE SHOWN WITH SI THROUGH S2D FOR CONSTRUCTION STAGE 1 THROUGH CONSTRUCTION STAGE 2D.

NOTE 4: THE SECONDARY SIGNAL HEAD PLACEMENT IS FOR CONSTRUCTION STAGES AS MARKED.
NEXT TO THE SIGNAL HEAD, FOR APPLICABLE CONSTRUCTION STAGES FOR INDIVIDUAL APPROACH OF THE INTERSECTION.

# TEMPORARY TRAFFIC SIGNAL LEGEND

SECTION

(113 & 114)R-

COUNTY

WILL

ILLINOIS FED. AID PROJECT:

525 372

TEMPORARY TRAFFIC SIGNAL HEAD SPAN WIRE MOUNTED ORIGINAL LOCATION

EAP RTE

338

FED. ROAD DIST, NO. 1

CONTRACT # 62417

■ TEMPORARY TRAFFIC SIGNAL HEAD SPAN WIRE MOUNTED SECONDARY LOCATION

TEMPORARY CONTROLLER CABINET
TEMPORARY SPAN WIRE, TETHER WIRE,
AND CABLE

TEMPORARY SERVICE INSTALLATION

TEMPORARY PEDESTRIAN SIGNAL HEAD,
BRACKET MOUNTED

PEDESTRIAN PUSHBUTTON DETECTOR

€ EMERGENCY VEHICLE LIGHT DETECTOR

• CONFIRMATION BEACON

CT COMMON TRENCH UD UNIT DUCT

G.S. CONDUIT IN GROUND

H HEAVY DUTY HANDHOLE

WIRELESS INTERCONNECT (ANTENNA)

VIDEO CAMERA ASSEMBLY

## EXISTING EQUIPMENT TO BE REMOVED LEGEND

EXISTING SIGNAL TO BE REMOVED

EXISTING SERVICE INSTALLATION TO BE REMOVED

EXISTING SIGNAL POST AND FOUNDATION TO BE REMOVED.

EXISTING MAST ARM POLE AND FOUNDATION TO BE REMOVED

"E" EXISTING CONTROLLER AND FOUNDATION TO BE REMOVED

□ "E" EXISTING HANDHOLE TO BE REMOVED

VEV. EVICTIMO DOUBLE HANDIOLE

"E" EXISTING DOUBLE HANDHOLE
TO BE REMOVED

- PEDESTRIAN SIGNAL TO BE REMOVED

- TEDESTITIAN SIGNAL TO BE NUMBER

EXISTING PEDESTRIAN PUSH-BUTTON TO BE REMOVED

EMERGENCY VEHICLE LIGHT DETECTOR TO BE REMOVED

D-O CONFIRMATION BEACON TO BE REMOVED

"E" EXISTING HEAVY DUTY HANDHOLE
TO BE REMOVED

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "ECONOLITE" TO MATCH THE EXISTING ADJACENT SYSTEM.

## ILLINOIS DEPARTMENT OF TRANSPORTATION

TEMPORARY TRAFFIC SIGNAL
INSTALLATION AND REMOVAL PLAN
ILLINOIS ROUTE 59 AT RENWICK ROAD
(SHEET 1 OF 3)

-- SCALE: 1"=20" DATE: 03/18/2008

REVISIONS

DATE

05-01-08


NAME

PKG, MAA

DRAWN BY: BB,KP DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM


GAND ENGINEE 6035 N. SUITE 3 CHICAGO

GANDHIAND ASSOCIATES, INC. ENGINEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHCAGO, ILLINOIS 60631 TEL. (773) 774-5910




TEMPORARY PHASE DESIGNATION DIAGRAM STAGES: PRE-STAGE 1. STAGE 1. STAGE 1A. STAGE 1B, STAGE 1C, STAGE 2, STAGE 2A, STAGE 2B, STAGE 2C, AND STAGE 2D.

## EMERGENCY VEHICLE PREEMPTION SEQUENCE



STAGES: PRE-STAGE 1, STAGE 1, STAGE 1A, STAGE 1B, STAGE 1C, STAGE 2, AND STAGE 2A

	FFIC SIGNAL I				
ELECT	RICAL SERVICE	REQUIREM	ENTS		TOTAL
TASE	NO LAMPS	* WAT	)	%OPERATION	WATTAGE
CTOVILL (DED)		INCAND.	LED	2.50	47.7
SIGNAL (RED)	18	135	17	0.50	153
(YELLOW)	18	135	25	0.25	112.5
(GREEN)	18	135	15	0.25	67.5
ARROW	12	135	12	0.10	14.4
PED. SIGNAL		90	25	1.00	
CONTROLLER	1	100	100	1.00	100.0
ILLUM, SIGN				0.05	
		-			
FLASHER				0.50	
ENERGY COSTS	TO:			TOTAL =	447.4
201 WEST C	DEPARTMENT ENTER COURT , ILLINOIS 6019		SPORTA'	TION	
ENERGY SUPPLY		MS. BETT (815) 724			



STAGES: PRE-STAGE 1. STAGE 1. STAGE 1A. STAGE 1B, STAGE 1C, STAGE 2, STAGE 2A, STAGE 2B, STAGE 2C, AND STAGE 2D.

- NOTE 1: DURING CONSTRUCTION STAGES PRE-STAGE 1, STAGE 1, STAGE 1A, STAGE 1B, STAGE 1C, STAGE 2, STAGE 2A, SATGE 2B. STAGE 2C. AND STAGE 2D THE GREEN AND YELLOW LEFT ARROW INDICATION SECTIONS FOR EASTBOUND AND WESTBOUND DIRECTION OF TRAFFIC SHALL BE BAGGED AND DISCONNECTED AT THE CONTROLLER AND APPLICABLE PHASES SHALL BE DISABLED IN THE CONTROLLER.
- NOTE 2: THESE 3-SECTION CIRCULAR GREEN, YELLOW, AND RED INDICATION SIGNALS SHALL ONLY BE USED DURING CONSTRUCTION STAGE 1C FOR SOUTHBOUND RIGHT TURN LANE, THESE 3 SECTION SIGNAL HEADS SHALL BE DISCONNECTED AT THE CONTROLLER AND BAGGED DURING OTHER CONSTRUCTION STAGES OR SHALL BE REMOVED AS DIRECTED BY THE ENGINEER.
- NOTE 3: THESE 3-SECTION CIRCULAR GREEN, YELLOW, AND RED INDICATION SIGNALS SHALL ONLY BE USED DURING CONSTRUCTION STAGE 24 FOR NORTHBOUND RIGHT TURN LANE, THESE 3 SECTION SIGNAL HEADS SHALL BE DISCONNECTED AT THE CONTROLLER AND BAGGED DURING OTHER CONSTRUCTION STAGES OR SHALL BE REMOVED AS DIRECTED BY THE ENGINEER.

NOTE 4: ALL THE TEMPORARY TRAFFIC SIGNAL HEADS SHALL BE LED TYPE

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "ECONOLITE" TO MATCH THE EXISTING ADJACENT SYSTEM.

REVISIONS DATE PKG. MAA 05-01-08 ILLINOIS DEPARTMENT OF TRANSPORTATION


COUNTY

TEMPORARY CABLE PLAN. PHASE DESIGNATION DIAGRAM, AND EMERGENCY VEHICLE PREEMPTION SEQUENCE ILLINOIS ROUTE 59 AT RENWICK ROAD (SHEET 2 OF 3)

DATE: 03/18/2008

DRAWN BY: BB,KP DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM

GANDHIAND ASSOCIATES, INC. ENGINEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLWOIS 60631TEL (773) 774-5910 



### NOTES FOR TEMPORARY TRAFFIC SIGNALS

- ALL CONTROL EQUIPMENT INCLUDING EMERGENCY PRE-EMPTION AND COMMUNICATION DEVICES FOR THE TEMPORARY TRAFFIC SIGNAL(S) SHALL BE FURNISHED BY THE CONTRACTOR.
- 2. ONLY CONTROLLERS SUPPLIED BY ONE OF THE DISTRICT APPROVED CLOSED LOOP EQUIPMENT MANUFACTURERS WILL BE APPROVED FOR USE AT TEMPORARY SIGNAL LOCATIONS. ALL CONTROLLERS USED FOR TEMPORARY TRAFFIC SIGNALS SHALL BE FULLY ACTUATED NEMA
  MICROPROCESSOR BASED WITH RS232 DATA ENTRY PORTS COMPATIBLE
  WITH EXISTING MONITORING SOFTWARE APPROVED BY IDOT DISTRICT 1,
  INSTALLED IN A NEMA TS1 OR TS2 CABINET, ONLY ONE BRAND OF CONTROLLER WILL BE ACCEPTED FOR ANY ONE CONTRACT.
- 3. ALL TRAFFIC SIGNAL SECTIONS AND PEDESTRIAN SIGNAL SECTIONS SHALL BE 12". HEADS SHALL BE PLACED AS INDICATED ON THE TEMPORARY TRAFFIC SIGNAL PLAN OR AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL FURNISH ENOUGH CABLE SLACK TO RELOCATE HEADS TO ANY POSITION ON THE SPAN WIRE OR AT LOCATIONS ILLUSTRATED ON THE PLANS FOR CONSTRUCTION STAGING. THE TEMPORARY TRAFFIC SIGNAL SHALL REMAIN IN OPERATION DURING ALL SIGNAL HEAD RELOCATIONS. EACH TEMPORARY TRAFFIC SIGNAL HEAD SHALL HAVE ITS OWN CABLE FROM THE CONTROLLER CABINET TO THE SIGNAL HEAD.
- 4. ALL EXISTING STREET NAME AND INTERSECTION REGULATORY SIGNS SHALL BE REMOVED FROM EXISTING POLES, RELOCATED AND SECURELY FASTENED TO THE SIGNAL SPAN WIRE OR WOOD POLE AS DIRECTED BY
- ANY TEMPORARY SIGNAL WITHIN AN EXISTING CLOSED LOOP TRAFFIC SIGNAL SYSTEM SHALL BE INTERCONNECTED TO THAT SYSTEM USING SIMILAR BRAND CONTROL EQUIPMENT.
- 6. THE TEMPORARY TRAFFIC SIGNAL SHALL HAVE THE SIGNAL HEAD DISPLAYS, SIGNAL HEAD PLACEMENTS AND CONTROLLER PHASING MATCH THE EXISTING TRAFFIC SIGNAL, AT THE TIME OF THE TURN ON, IF NO TRAFFIC STAGING IS IN PLACE OR WILL NOT BE STAGED ON THE DAY OF THE TURN ON.

THE FOLLOWING ITEMS SHALL BE REMOVED BY THE CONTRACTOR AND SHALL BE DISPOSED OF BY THEM OUTSIDE THE RIGHT-OF-WAY AT THEIR EXPENSE. THE SALVAGE VALUE OF THE REMOVED EQUIPMENT SHALL BE REFLECTED IN THE CONTRACT BID PRICE.

1	EACH	CONTROLLER AND CABINET, COMPLETE
4	EACH	WOOD POLES
1	L SUM	CABLE, MESSENGER WIRE, TETHER WIRE AND DOWN GUYS
6	EACH	SIGNAL HEAD, 1-FACE 3-SECTION, SPAN WIRE MOUNTED
3	EACH	SIGNAL HEAD, 1-FACE 5-SECTION, SPAN WIRE MOUNTED
1	EACH	SIGNAL HEAD, 1-FACE 5-SECTION, BRACKET MOUNTED
3	EACH	TRAFFIC SIGNAL POST
2	EACH	PEDESTRIAN SIGNAL HEAD, 1-FACE, BRACKET MOUNTED
1	EACH	PEDESTRIAN SIGNAL HEAD, 2-FACE, BRACKET MOUNTED
3	FACH	PEDESTRIAN PUSH-BUTTON DETECTORS

THE FOLLOWING EXISTING TRAFFIC SIGNAL EQUIPMENT SHALL BE REMOVED BY THE CONTRACTOR, SHALL REMAIN THE PROPERTY OF THE AGENCY LISTED BELOW. THE CONTRACTOR SHALL SAFELY STORE AND ARRANGE FOR PICK UP OF ALL EQUIPMENT TO BE RETURNED TO THE LISTED AGENCY AS PER THE TRAFFIC SIGNAL SPECIFICATIONS.

SERVICE INSTALLATION

AGENCY: VILLAGE OF PLAINFIELD

CONTACT INFORMATION: MR. RANDY JESSEN PLAINFIELD PUBLIC WORKS 14400 COIL PLUS DRIVE PLAINFIELD, ILLINOIS 60544 PHONE: (815) 436-3577

LIGHT DETECTOR AND CONFIRMATION BEACON LIGHT DETECTOR AMPLIFIER FACH

P.  $\square$  $\alpha$  $\bigcirc$ INTERCONNECT TO US. RTE. 30 STA. 3319+52 52FT LEFT S4A (SEE TEMPORARY INTERCONNECT PLAN) ILL. RTE. 59 S4A 3320+00 3319 (-) R.O.W. PS1 INTERCONNECT TO RENWICK RD, AND US RTE. (SEE TEMPORARY INTERCONNECT PLAN) S4A STA, 3319+51 34FT RIGHT TEMPORARY TRAFFIC SIGNAL PLAN STAGES: PRE-STAGE 1, STAGE 1, STAGE 2,

STGAE 4, AND STAGE 4A

- NOTE 1: ALL THE VIDEO DETECTION ZONES SHALL BE REDEFINED FOR EACH CONSTRUCTION STAGE. THIS WORK IS INCIDENTAL TO THE PAY ITEM "TEMPORARY TRAFFIC SIGNAL INSTALLATION".
- NOTE 2: THE ORIGINAL SIGNAL HEAD PLACEMENT FOR ALL APPROACHES OF THE INTERSECTION IS FOR EXISTING PAVEMENT GEOMETRICS (PS1), ADDITIONAL CONSTRUCTION STAGES, WHERE ORIGINAL SIGNAL HEAD PLACEMENT IS UTILIZED, ARE SHOWN WITH SI THROUGH SZA FOR CONSTRUCTION STAGE 1 THROUGH CONSTRUCTION STAGE 2A.
- NOTE 3: THE SECONDARY SIGNAL HEAD PLACEMENT IS FOR CONSTRUCTION STAGES AS MARKED. NEXT TO THE SIGNAL HEAD, FOR APPLICABLE CONSTRUCTION STAGES FOR INDIVIDUAL APPROACH OF THE INTERSECTION.
- NOTE 4: DURING WINTER SHUTDOWN THE SIGNAL HEAD PLACEMNTS SHALL BE SIMILAR TO STAGE 3 OR AS DIRECTED BY THE ENGINEER.
- NOTE 5: WHEN FORT BEGGS DRIVE IS CLOSED TO VEHICLES TRAFFIC DURING STAGE 1A, THE CIRCULAR GREEN INDICATION ON THE SIGNAL HEADS FOR THE NORTHBOUND AND SOUTHBOUND DIRECTION OF TRAFFIC SHALL BE PROGRAMMED TO STAY ON THROUGHOUT THE DURATION OF STAGE 1A. THE SIGNAL H

EXISTING EQUIPMENT TO BE REMOVED LEGEND EXISTING SIGNAL TO BE REMOVED EXISTING SERVICE INSTALLATION  $\bigcirc$ FOUNDATION TO BE REMOVED EXISTING MAST ARM POLE AND FOUNDATION TO BE REMOVED EXISTING CONTROLLER AND FOUNDATION TO BE REMOVED ⊠′′E′′ □ "E" EXISTING HANDHOLE TO BE REMOVED EXISTING DOUBLE HANDHOLE TO BE REMOVED ₽₽,,Ę, PEDESTRIAN SIGNAL TO BE REMOVED EXISTING PEDESTRIAN PUSH-BUTTON TO BE REMOVED EMERGENCY VEHICLE LIGHT DETECTOR TO BE REMOVED CONFIRMATION BEACON TO BE REMOVED EXISTING HEAVY DUTY HANDHOLE TO BE REMOVED H "E" EXISTING STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED EXISTING WOOD POLE (CLASS 5 OR BETTER) 45 FOOT MINIMUM TO BE REMOVED (☎) EXISTING CABLE, MESSENGER WIRE AND TETHER WIRE TO BE REMOVED TEMPORARY TRAFFIC SIGNAL LEGEND TEMPORARY TRAFFIC SIGNAL HEAD SPAN WIRE MOUNTED ORIGINAL LOCATION TEMPORARY TRAFFIC SIGNAL HEAD SPAN WIRE MOUNTED SECONDARY LOCATION TEMPORARY WOOD POLE: (CLASS 5 OR  $\otimes$ BETTER) 45 FOOT (I3.7m) MINIMUM TEMPORARY CONTROLLER CABINET  $\boxtimes$ TEMPORARY SPAN WIRE, TETHER WIRE, -TEMPORARY SERVICE INSTALLATION TEMPORARY PEDESTRIAN SIGNAL HEAD, BRACKET MOUNTED 1---MICROWAVE VEHICLE SENSOR PEDESTRIAN PUSHBUTTON DETECTOR EMERGENCY VEHICLE LIGHT DETECTOR • ( CONFIRMATION BEACON VEHICLE DETECTOR, INDUCTION LOOP COMMON TRENCH UD LINIT DUCT G.S. CONDUIT IN GROUND HANDHOLE Н HEAVY DUTY HANDHOLE (·) WIRELESS INTERCONNECT (ANTENNA) VIDEO CAMERA ASSEMBLY SHALL BE "ECONOLITE" TO MATCH

F.A.P. RTE. SECTION

FED. ROAD DEST. NO. 1

CONTRACT # 62417

338 (113 & 114)R-5

COUNTY

ILLINOIS FED. AID PROJECT:

WILL

525 375

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT

THE EXISTING ADJACENT SYSTEM.


REVISIONS DATE PKG, MAA 05-01-08


ILLINOIS DEPARTMENT OF TRANSPORTATION


TEMPORARY TRAFFIC SIGNAL INSTALLATION AND REMOVAL PLAN ILLINOIS ROUTE 59 AT FORT BEGGS DRIVE (SHEET 1 OF 3)

SCALE: 1"=20" DATE: 03/18/2008 DRAWN BY: BB,KP DESIGNED BY: PKG/RR CHECKED BY: PKG/RRW


GANDHIAND ASSOCIATES, INC. ENGINEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY 0. ILLINOIS 60631 TEL. (773) 774-591







STAGES: STAGE 1A



4

PROPOSED EMERGENCY

VEHICLE PREEMPTORS

EMERGENCY VEHICLE

PREEMPTOR

MOVEMENT

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "ECONOLITE" TO MATCH THE EXISTING ADJACENT SYSTEM.

COUNTY

ILLINOIS FED. AID PROJECT;

TO STA.

525 376

SECTION 338 (113 & 114)R-5

FED. ROAD DIST. NO. 1

CONTRACT # 62417

## ILLINOIS DEPARTMENT OF TRANSPORTATION

TEMPORAY CABLE PLAN, PHASE DESIGNATION DIAGRAM, AND REVISIONS EMERGENCY VEHICLE PREEMPTION SEQUENCE ILLINOIS ROUTE 59 AT FORT BEGGS DRIVE (SHEET 2 OF 3)

> SCALE: N.T.S. DATE: 03/18/2008

DRAWN BY: BB,KP DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM

TEMPORARY CABLE PLAN NOTE:

 $\boxtimes$ 

 $\mathbb{V}^{\blacksquare}$ 

PKG, MAA

 $\longleftrightarrow$ 

NOTE 1: DURING CONSTRUCTION STAGES STAGE 1A THE YELLOW AND GREEN LEFT ARROW INDICATION SECTIONS FOR NORTHBOUND DIRECTION OF TRAFFIC SHALL BE BAGGED AND DISCONNECTED AT THE CONTROLLER AND APPLICABLE PHASES SHALL BE DISABLED IN THE CONTROLLER.

TEMPORARY CABLE DIAGRAM LEGEND

UNLESS OTHERWISE NOTED.

CONFIRMATION BEACON

VIDEO CAMERA ASSEMBLY

CO-AXIAL VIDEO CABLE

TEMPORARY CONTROLLER CABINET TEMPORARY SERVICE INSTALLATION

EMERGENCY VEHICLE LIGHT DETECTOR

VEHICLE DETECTOR, INDUCTION LOOP

PEDESTRIAN PUSHBUTTON DETECTOR

WIRELESS INTERCONNECT (ANTENNA)

12" (300mm) PEDESTRIAN SIGNAL SECTION

TEMPORARY TRAFFIC SIGNAL SECTION OR

PEDESTRIAN SIGNAL SECTION 12" (300mm)

INDICATES NUMBER OF CONDUCTORS IN CABLE. ALL CONDUCTORS TO BE NUMBER 14 AWG WIRE

NOTE 2: WHEN FORT BEGGS ROAD IS CLOSED TO VEHICULAR TRAFFIC DURING STAGE 1A, THE CIRCULAR GREEN INDICATION ON THE SIGNAL HEADS FOR THE NORTHBOUND AND SOUTHBOUND DIRECTION OF TRAFFIC SHALL BE PROGRAMMED TO STAY ON THROUGHOUT THE DURATION OF STAGE 1A. THE SIGNAL HEADS FOR THE EASTBOUND DIRECTION OF TRAFFIC AND THE EVP EQUIPMENT SHALL BE DISCONNECTED AND BAGGED DURING THIS CONSTRUCTION STAGE AS DIRECTED BY THE ENGINEER.

GANDHIAND ASSOCIATES, INC. SUITE 306 CHICAGO, ILLINOIS 6063I TEL. (773) 774-59I


EMERGENCY VEHICLE PREEMPTION SEQUENCE


STAGES: PRE-STAGE 1, STAGE 1,


STAGE 2, STAGE 4, AND STAGE 4A.


ILL. RTE. 59


**--**(3)--▶































7.5 Sq. Ft. each 3 Required Design Series\_D


# A B C 18" 2" 14"

<u>9.0</u> Sq. Ft. each 2 Required Design Series<u>C</u> SINGLE ARM

PANEL SIGN DESIGN TYPE 1








## GENERAL NOTES

- 1. WHERE MAST ARM MOUNTED STREET NAME SIGNS ARE SPECIFIED, THE MAST ARM ASSEMBLY AND POLES SHALL BE DESIGNED TO SUPPORT THE LOADINGS CALLED FOR ON STANDARDS 834001, 834006 AND 834011, AS APPLICABLE, PLUS TWO (2) SIGN PANELS 2'-6" X 6'-0" MOUNTED AS SHOWN. THE DESIGN SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE CURRENT "STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES, AND TRAFFIC SIGNALS" AS PUBLISHED BY THE AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS FOR 80 M.P.H. WIND VELOCITY.
- 2. ALL SIGNS SHALL HAVE A WHITE REFLECTORIZED LEGEND AND BORDER ON A GREEN REFLECTORIZED BACKGROUND, TYPE A SHEETING.
- 3, THE SIGN LENGTH SHOULD BE INCREASED IN 6-INCH INCREMENTS, BUT THE OVERALL LENGTH SHOULD NOT EXCEED 6'-0".
- 4. ALL BORDERS SHALL BE 3/4" WIDE AND CORNER RADIUS SHALL BE 2-1/4 ".
- 5. SIGNFIX ALUMINUM CHANNEL FRAMING SYSTEM SHALL BE USED FOR ALL SIGNS ATTACHED TO SIGNAL POLES AND POSTS. LOCAL SUPPLIERS OF THE SIGNFIX ALUMINUM CHANNEL FRAMING SYSTEM ARE:
- \* TUCKER COMPANY, INC. WAUWATOSA, WI
- \* A.K.T. CORPORATION SCHAUMBURG, IL
  - \* AMERICAN FABRICATION CO. CHICAGO HEIGHTS, IL \* WESTERN TRAFFIC CONTROL INC. CICERO, IL

PARTS LISTING: PART #HPN053 (MED. CHANNEL) SIGN CHANNEL 1/4" × 14 × 1" H.W.H. #3
SELF TAPPING WITH NEOPRENE WASHER SIGN SCREWS


BRACKETS PART \*HPN034 (UNIVERSAL)


CHANNEL CLAMPS WITH STAINLESS STEEL STRAPPING OTHER BRANDS OF MOUNTING HARDWARE ARE ACCEPTABLE, BASED UPON THE DEPARTMENT'S APPROVAL AND COMPATIBILITY WITH THE CHANNEL/BRACKET OF THE ABOVE PRODUCT.




SIGNFIX ALUMINUM CHANNEL FRAMING SYSTEM Shall be used. See Note #5.

## SUPPORTING CHANNELS





## SUPPORTING CHANNELS



Α	В	С
18''	2"	12''
30′′	2"	22''

F	Imnqu	16	17	22	24	16	$1^7$	12	14	14	1 <sup>5</sup>	14	15	16	1'	16	1'
R	bfkops	12	14	16	17	11	12	05	06	11	12	11	12	12	14	12	14
T	се	12	14	16	17	12	14	Oe	10	12	14	12	14	12	14	12	14
Ļ	r	06	10	12	14	06	10	03	03	05	06	05	06	0e	10	Oe	10
Ţ	† z	12	14	16	17	12	14	0e	10	11	12	11	12	12	14	12	14
Ė	v у	11	12	14	15	11	12	05	06	06	10	Oe	10	11	12	11	12
	W	11	12	14	15	11	12	05	06	11	12	11	12	11	12	12	14
	×	12	14	16	17	11	12	05	06	11	12	11	12	11	12	12	14

Lower Case To Lower Case

acde bhikl goq mnpru

CD

Spacing Chart 6 Inch Series "C & D"

Upper Case To Lower Case

acde bhikl god mnpru

11 12

SERIES

DOQR

HIMNJU

T

SERIES

A W X

Spacing Chart 8-6 Inch Series "C & D"

CDCDCDCD

SECOND LETTER

14 14 15 12 14 06 10 11 14 06 10 11 12 12 14

15 20 21 14 15 11 12 14 15 12 14 12 14 16 17

15 20 21 12 14 06 10 12 14 12 14 14 15 14 15

14 | 15 | 20 | 21 | 14 | 15 | 06 | 10 | 12 | 14 | 12 | 14 | 14 | 15 | 14 | 15

05 06 14 15 06 10 05 06 06 10 06 10 06 10 11 12

20 21 22 24 20 21 14 15 16 17 16 17 20 21 20 21

20 21 20 21 16 17 14 15 16 17 16 17 16 17 20 21

12 | 14 | 14 | 15 | 12 | 14 | 05 | 06 | 11 | 12 | 11 | 12 | 12 | 14 | 12 | 14

11 | 12 | 16 | 17 | 06 | 10 | 06 | 10 | 11 | 12 | 11 | 12 | 11 | 12 | 14

 $|\ 0\ 6\ |\ 1\ 0\ |\ 1\ 4\ |\ 1\ 5\ |\ 1\ |\ 1\ 2\ |\ 0\ 6\ |\ 1\ 0\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 4\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2\ |\ 1\ 2$ 05 06 14 15 06 10 05 06 05 07 05 06 06 10 11 12

SECOND LETTER

s t

V Y

Z

14 | 16 | 17 | 12 | 14 | 06 | 10 | 12 | 14 | 12 | 14 | 12 | 14 | 12 | 14

16 | 17 | 11 | 12 | 05 | 06 | 11 | 12 | 11 | 12 | 11 | 12 | 14

s t

νу

Z

## Number To Number Spacing Chart 8 Inch Series "C & D"

											SE	COI	ND	NL	ΙМВ	ER							
				(	)		1	2	2	-	3	_	4	Ī	5	(	ŝ	1	7	8	3	9	3
١		SE	RIES	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	
	F	0	9	16	17	1 <sup>6</sup>	17	14	15	12	14	14	15	14	15	16	17	12	14	16	17	16	17
	R	1		2 <sup>0</sup>	2 <sup>1</sup>	2 <sup>0</sup>	2 <sup>1</sup>	2 <sup>0</sup>	21	16	17	14	1 <sup>5</sup>	2 <sup>0</sup>	21	20	2 <sup>1</sup>	14	15	2 <sup>0</sup>	2 <sup>1</sup>	2 <sup>0</sup>	2 <sup>1</sup>
	Ť	2	3 4	14	1 <sup>5</sup>	14	1 <sup>5</sup>	14	1 <sup>5</sup>	1 <sup>2</sup>	14	12	14	14	1 <sup>5</sup>	1 <sup>4</sup>	1 <sup>5</sup>	11	12	1 <sup>6</sup>	17	14	15
	N U	5		14	1 <sup>5</sup>	14	1 <sup>5</sup>	14	1 <sup>5</sup>	11	1 <sup>2</sup>	11	1 <sup>2</sup>	14	1 <sup>5</sup>	1 <sup>4</sup>	1 <sup>5</sup>	1 <sup>1</sup>	1 <sup>2</sup>	14	1 <sup>5</sup>	14	15
	M B	6		16	17	14	1 <sup>5</sup>	14	15	12	15	1 <sup>2</sup>	14	14	1 <sup>5</sup>	14	1 <sup>5</sup>	11	1 <sup>2</sup>	14	1 <sup>5</sup>	14	1 <sup>5</sup>
	E R	7		12	14	12	14	14	1 <sup>5</sup>	12	15	0 <sup>5</sup>	06	1 <sup>2</sup>	14	14	1 <sup>5</sup>	11	1 <sup>2</sup>	14	1 <sup>5</sup>	12	14
İ	,,	8		16	17	16	17	14	1 <sup>5</sup>	12	1 <sup>5</sup>	12	14	14	15	16	17	12	14	1 <sup>6</sup>	17	14	15

SECTION COUNTY TOTAL SHEET NO. 525 387 338 (113 & 114)R-5 WILL TO STA. STA. FED. ROAD DIST. NO. 1 | ILLINOIS | FED. AID PROJECT CONTRACT # 62417

EXAMPLE,  $2^{3}$  DENOTES  $\frac{3}{8}$ 

UPPER AND LOWER CASE

## LETTER WIDTHS

L T E R S		UPPER ETTERS		4 UPPER LETTERS	E T E R S		LOWER ETTERS
ŤΕ	SER	IES	SEI	RIES	T <sub>E</sub>	SEF	RIES
R S	С	D	С	D	R S	С	D
А	36	50	5 0	6 <sup>5</sup>	a	35	42
В	32	40	4 3	5 <sup>3</sup>	Ф	35	4 <sup>2</sup>
С	3 <sup>2</sup>	40	43	5 <sup>3</sup>	С	35	<b>4</b> <sup>1</sup>
D	3 <sup>2</sup>	40	4 <sup>3</sup>	53	d	35	42
Е	3 0	35	40	4 7	ę	3 <sup>5</sup>	42
F	3 0	35	40	47	f	2 3	2 <sup>6</sup>
G	3 <sup>2</sup>	40	43	5 <sup>3</sup>	g	3 <sup>5</sup>	42
Н	3 <sup>2</sup>	40	43	53	h	3 <sup>5</sup>	42
I	0 7	o <sup>7</sup>	11	12	1	1 <sup>1</sup>	1 1
J	30	36	40	50	j	20	22
K	32	4 <sup>1</sup>	43	5 4	k	35	42
L	30	35	40	47	ı	1 1	11
М	3 7	45	51	61	m	60	70
N	32	40	43	5.3	n	35	42
0	34	42	4 5	55	0	36	43
Р	32	40	43	5 3	Р	35	42
a	3 <sup>4</sup>	42	45	55	q	35	42
R	32	40	43	5 3	r	26	32
\$	32	40	43	53	5	3 6	42
T	30	35	40	4 7	t	2 7	32
U	32	40	4 3	53	u	35	42
٧	35	44	4 7	60	v	42	4 7
W	44	52	6 <sup>0</sup>	70	w	55	64
Х	34	40	45	53	×	44	51
Y	36	50	5 0	66	У	46	53
Z	3 <sup>2</sup>	40.	43	53	z	36	43

N <sub>U</sub> ,	6 INCH	SERIES	8 INCH	SERIES
N <sub>UMBER</sub>	С	D	С	. D
1	12	1 4	15	20
2	3 <sup>2</sup>	40	43	53
3	32	40	43	5 3
4	3 <sup>5</sup>	4 <sup>3</sup>	4 7	57
5	32	40	43	53
6	32	40	43	53
7	3 <sup>2</sup>	40	43	5 <sup>3</sup>
8	3 <sup>2</sup>	40	43	53
9	3 <sup>2</sup>	40	43	53
0	3 4	42	45	55


NAME	DATE
D.A.Z./D.A.G.	11/90
	6/98
CADD	10/00

Illinois Department of Transportation
DISTRICT 1

MAST ARM MOUNTED STREET NAME SIGNS

SCALE: NONE DATE: April 3, 2003 DRAWN BY: RDB DESIGNED BY: JHE CHECKED BY: DAD

1:#PRQUECTS\*Projects 2003\*iL59\_Catan#2008\_renvick\_for+ beggs\*21-Signs1.dgn 3/12/2008 11:35:35 AM



SHEET OF




BRACKETS

PART \*HPNO34 (UNIVERSAL)
CHANNEL CLAMPS WITH STAINLESS STEEL STRAPPING

COMPATIBILITY WITH THE CHANNEL/BRACKET OF THE ABOVE PRODUCT.

OTHER BRANDS OF MOUNTING HARDWARE ARE ACCEPTABLE, BASED UPON THE DEPARTMENT'S APPROVAL AND



SIGNFIX ALUMINUM CHANNEL FRAMING SYSTEM

Shall be used. See Note #5.

Upper Case To Lower Case

**EXAMPLE** Spacing Chart 8-6 Inch Series "C & D"

		F.A.	SEC	TIC	N	(	COUNT	Y	TOTAL	SHEET NO.
		338	113	& :	14R	Г	WIL	L	525	389
3"		STA.				TO :	STA,			
DENOTES $\frac{1}{8}$		FED. ROA	D DIST.	NO.	ILLI	1012	FED.	AID	PROJECT	
	HDDCD AND	CONTI	RACT	N	).	62	417			

C THOU HODGO

UPPER AND LOWER CASE LETTER WIDTHS

							SEC	ONI	) L	ETT	ER						
			d e	b h m n i		f	w		İ	S	+	>	У	>	<b>‹</b>	2	z
	SERIES	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D
	AWX	12	14	14	15	12	14	06	10	11	14	06	10	11	12	12	14
	В	14	1 <sup>5</sup>	20	21	14	1 <sup>5</sup>	11	12	14	15	12	14	12	14	1 <sup>6</sup>	17
٠.	CEG	14	1 <sup>5</sup>	20	21	1 <sup>2</sup>	14	06	1 <sup>0</sup>	1 <sup>2</sup>	14	1 <sup>2</sup>	14	14	1 <sup>5</sup>	14	15
F	D 0 Q R	14	·1 <sup>5</sup>	20	21	14	1 <sup>5</sup>	06	10	12	14	12	14	14	15	14	15
FIRST	F	05	06	14	15	06	10	05	06	06	10	06	10	06	10	11	12
Ş	HIMN	20	2 <sup>1</sup>	22	24	20	2 <sup>1</sup>	14	1 <sup>5</sup>	16	17	16	17	20	2 <sup>1</sup>	20	2 <sup>1</sup>
1	JU	20	2 <sup>1</sup>	20	21	1 <sup>6</sup>	17	14	1 <sup>5</sup>	16	17	16	17	16	17	20	2 <sup>1</sup>
JEHTER	K L	11	12	16	17	11	12	05	06	1 <sup>1</sup>	12	1 <sup>1</sup>	12	1 <sup>1</sup>	12	12	14
Ţ	Р	1 <sup>2</sup>	14	14	15	1.2	14	05	06	1 <sup>1</sup>	12	11	1 <sup>2</sup>	1 <sup>2</sup>	14	12	14
E R	S	12	14	1.6	17	12	14	06	10	12	14	12	14	12	14	12	14
	Т	11	12	16	17	06	10	06	10	1 <sup>1</sup>	12	11	1 <sup>2</sup>	11	12	12	14
	٧	06	10	14	15	1 <sup>1</sup>	12	06	10	12	14	12	14	1 <sup>2</sup>	14	12	14
	Υ	05	06	14	15	06	10	05	06	05	07	05	06	06	10	11	12
	Z	16	17	22	24	16	17	12	14	16	17	16	17	16	17	20	2 <sup>1</sup>

Lower Case To Lower Case Spacing Chart 6 Inch Series "C & D"

							SE	CON	ND I	LET	TEF	?					
		a c		b h m n p		f	w	]		s	+	٧	У	,	<		z
	SERIES	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D
FIRS	adhgij Imnqu	16	17	22	24	16	17	12	14	14	15	14	15	16	17	16	17
S	bfkops	12	14	16	17	11	12	05	06	11	12	11	12	12	14	12	14
T	се	12	14	16	17	12	14	06	10	12	14	12	14	12	14	12	14
F	r	06	10	12	14	06	10	03	03	05	06	05	06	0e	10	06	10
Ē	† z	12	14	16	17	12	14	06	10	11	12	11	12	12	14	12	14
Ė	νу	11	12	14	15	11	12	05	06	06	10	06	10	11	12	11	12
K	w	11	12	14	15	11	12	05	06	11	12	11	12	11	12	12	14
	×	12	14	16	17	11	12	05	0e	11	12	11	12	1 <sup>1</sup>	12	12	14

Number To Number Spacing Chart 8 Inch Series "C & D"

										SE	СО	ND	NL	ΙМΒ	ER							
			(	)		1	2	2	-	3	4	4	5	5	(	5	7	7	8	3	9	€
	SE	RIES	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D	С	D
FI	0	9	16	17	16	17	14	1 <sup>5</sup>	1 <sup>2</sup>	14	14	1 <sup>5</sup>	14	1 <sup>5</sup>	16	17	1 <sup>2</sup>	14	1 <sup>6</sup>	17	16	17
R. S	1		20	21	20	21	2 <sup>0</sup>	2 <sup>1</sup>	16	17	14	15	20	21	20	21	14	15	20	21	20	21
T	2	3 4	14	1 <sup>5</sup>	14	15	14	1 <sup>5</sup>	12	14	1 <sup>2</sup>	14	14	15	14	1 <sup>5</sup>	11	12	16	17	14	15
N	5		14	1 <sup>5</sup>	14	15	14	1 <sup>5</sup>	1 <sup>1</sup>	12	1 <sup>1</sup>	12	14	15	14	15	1 <sup>1</sup>	12	14	1 <sup>5</sup>	14	15
M	6		16	17	14	15	14	1 <sup>5</sup>	1 <sup>2</sup>	1 <sup>5</sup>	1 <sup>2</sup>	14	14	15	14	1 <sup>5</sup>	11	1 <sup>2</sup>	14	1 <sup>5</sup>	14	15
E R	7		12	14	1 <sup>2</sup>	14	14	1 <sup>5</sup>	12	1 <sup>5</sup>	05	06	12	14	14	15	11	1 <sup>2</sup>	14	1 <sup>5</sup>	12	14
``	8		16	17	16	17	14	15	1 <sup>2</sup>	1 <sup>5</sup>	1 <sup>2</sup>	14	14	1 <sup>5</sup>	1 <sup>6</sup>	17	12	14	1 <sup>6</sup>	17	14	1 <sup>5</sup>

L T T E R S		UPPER ETTERS		H UPPER LETTERS	E T E R S	6 INCH CASE L	LOWER
T E	SEF	RIES	SE	RIES	T <sub>E</sub>	SEI	RIES
R S	С	D	С	D	R S	, C	D
A	36	50	5.0	6.5	a	35	42
В	3 <sup>2</sup>	40	43	53	Ь	35	42
С	32	40	43	53	С	35	41
D	32	40	43	53	d	35	42
Ε	30	3 <sup>5</sup>	40	47	е	35	42
F	3.0	35	40	47	f	23	26
G	32	40	43	53	g	35	42
Н	3 <sup>2</sup>	40	43	5 <sup>3</sup>	h	35	42
1	07	07	11	12	1	1 1	11
J	30	36	40	50	J	20	22
K	32	41	43	54	k	35	42
L	30	3 <sup>5</sup>	40	47	ı	11	1.1
М	37	45	5 <sup>1</sup>	6 <sup>1</sup>	m	60	70
N .	32	40	43	53	n	3.5	42
0	34	42	45	55	0	36	43
Р	32	40	43	53	P	35	42
Q	34	42	45	5 <sup>5</sup>	q	35	42
R	3 <sup>2</sup>	40	43	5.3	r	26	32
S	32	40	43	53	s	36	42
Т	30	3 <sup>5</sup>	40	47	+	27	32
U	32	40	43	53	u	35	42
٧	35	44	47	60	٧	42	47
W	44	5 <sup>2</sup>	60	70	W	55	64
х	3 4	40	45	53	×	44	51
Y	36	50	50	66	у	46	53
Z	3 <sup>2</sup>	40	43	53	z	36	43
				·			<u> </u>


NU <sub>M</sub>	6 INCH	SERIES	8 INCH SERIES		
NU <sub>MBER</sub>	С	D	C	D	
1	12	14	15	20	
2	3 <sup>2</sup>	40	43	53	
3	32	40	43	53	
4	3 <sup>5</sup>	43	47	57	
5	32	4.0	43	5.3	
6	3 <sup>2</sup>	40	43	53	
7	32	40	43	53	
8	3.2	40	43	53	
9	3 <sup>2</sup>	40	43	53	
0	34	42	45	55	




REVISION	NS .	ILLINOIS DEPARTMENT OF TRANSP
NAME	DATE	ILLINOIS DEPARTMENT OF TRANSP
	1//	
	//	STANDARD TRAFFIC SIG
	1//	
	1//	DESIGN DETAILS
	7/	
	11	

MENT OF TRANSPORTATION TRAFFIC SIGNAL


SCALE: VERT. NOT TO SCALE
HORIZ.
DATE 3/10/2008 DRAWN BY JLA DESIGNED BY KK/BPT CHECKED BY JTL/BPT





DATE NAME SCALE NAME P.C.T. P.C.T. USES

CONTRACT NO. 62417 | Mar. | SECTION | COUNTY | TOTAL | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | SECTION | S



## <u>LEGEND</u>

PCC SIDEWALK, 5"

PCC SIDEWALK, 8"

PCC DRIVEWAY PAVEMENT, 8"

PROPOSED CATCH BASIN (SEE NOTE 5)

PROPOSED INLET (SEE NOTE 5)

## NOTES:

- 1. (607.98) EXISTING ELEVATIONS
  607.94 PROPOSED ELEVATIONS
- 2. GAS STATION ENTRANCE AND PAVEMENT RECONSTRUCTION SHALL CONSIST OF 8" THICK PORTLAND CEMENT CONCRETE
- 3. SEE LANDSCAPING PLANS FOR LANDSCAPING REQUIREMENTS
- 4. SEE SIDEWALK PLANS FOR PROPOSED SIDEWALK DETAILS.
- 5. SEE DRAINAGE PLANS FOR DRAINAGE STRUCTURE INFORMATION.



ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG

IL59/RENWICK RD. GAS STATION PAVEMENT RECONSTRUCTION

DETAIL

SCALE AS SHOWN
DATE MARCH 18, 2008


DRAWN BY RTA
CHECKED BY PJO

CONTRACT NO. 62417

## GENERAL NOTES

PRECAST CONCRETE BOX CULVERT AND PRECAST CONCRETE BOX CULVERT END SECTIONS

- THIS WORK SHALL CONSISTS OF FURNISHING AND INSTALLING PRECAST BOX CULVERTS AND BOX CULVERT END SECTIONS AS SHOWN ON THE PLANS.
- CONSTRUCTION OF PRECAST BOX CULVERTS AND BOX CULVERT END SECTIONS SHALL CONFORM TO ALL APPLICABLE REQUIREMENTS OF SECTION 540 OF THE STANDARD SPECIFICATIONS AND AS SPECIFIED HEREIN.
- 3. THE PRECAST CONCRETE BOX CULVERT SECTIONS SHALL CONFORM TO THE REQUIREMENTS OF ASTM C1433 EXCEPT THAT THE AGGREGATE SHALL CONFORM TO THE REQUIREMENTS OF ARTICLES 1003.02 AND 1004.02 OF THE STANDARD SPECIFICATIONS.
- 4. JOINTS SHALL BE SEALED ACCORDING TO ARTICLE 540.06 OF THE STANDARD SPECIFICATIONS. THE MASTIC JOINT SEALER SHALL BE SPREAD A MINIMUM OF 1 FOOT WIDE ON EACH SIDE OF THE TOP AND SIDE JOINTS BEFORE PLACING THE EXTERNAL SEALING BANDS OR NONWOVEN GEOTECHNICAL FABRIC. THE COST WILL BE INCLUDED IN THE COST OF THE PRECAST CONCRETE BOX CULVERT.
- 5. SHOP PLANS FOR PRECAST CONCRETE BOX CULVERT SECTIONS WHICH SATISFY THE STANDARD SHAPES, REINFORCEMENT, AND DETAILING OF ASTM C1433 ARE NOT REQUIRED TO BE REVIEWED AND APPROVED BY THE ENGINEER.
- 6. THE COST OF THE PRECAST CONCRETE BOX CULVERT, OF THE SIZE SPECIFIED, INCLUDES THE COST OF EXCAVATION FOR THE POROUS GRANULAR BACKFILL, EXCEPT EXCAVATION OF ROCK AND/OR UNSTABLE OR UNSUITABLE MATERIAL BELOW BEDDING GRADE.
- 7. THE COST OF THE PRECAST CONCRETE BOX CULVERT END SECTIONS INCLUDES THE COST OF THE EXCAVATION, TOEWALL AND COLLARS.



## CROSS SECTION

\*ALL DIMENSIONS SHOULD BE VERIFIED WITH SUPPLIER

SPAN X RISE (FEET)	T <sub>†</sub> (INCHES)	T <sub>b</sub> (INCHES)	T <sub>s</sub> . (INCHES)	A (FTIN.)	B (FTIN.)	C (INCHES)	E (FTIN.)	F (FTIN.)	G (FTIN.)	H (FTIN.)	SLOPE (X:Y)
5 X 3	8	7	6	6-0	4-3	6	2-0	4-0	1-0	2-0	2:1

DIMENSIONS (FOR ASTM C1433)\*

ISOMETRIC VIEW

\*2:1 MAXIMUM SLOPE

PRECAST OR FIELD

POURED TOEWALL

SIDE VIEW

END CONNECTION TO FIT PRECAST
BOX CULVERT BELL OR SPIGOT MAY

BE OMITTED WHEN COLLARING TO AN EXISTING BOX OR HEADWALL

PLAN

SPAN

END VIEW

DISTRICT NO. 1 SCHAUMBURG

5' X 3' PRECAST CONCRETE


PAY LIMITS OF PRECAST CONCRETE BOX CULVERT

5' X 3' PRECAST CONCRETE BOX CULVERT AND END SECTIONS


ILLINOIS DEPARTMENT OF TRANSPORTATION

 SCALE
 NONE
 DRAWN BY
 TB

 DATE
 MARCH 18, 2008
 CHECKED BY
 WPM








ANGLE FASTENER DETAIL


NOTES:

1. ALL STEEL ANGLES ANDD PLATES TO BE GALVANIZED AFTER FABRICATION

2. ALL RESTRICTOR PLATES, ANGLES AND HARDWARE TO BE INCLUDED IN THE COST OF THE MANHOLE.

3. BASIS OF PAYMENT: "MANHOLES, TYPE A, TYPE I FRAME, CLOSED LID, RESTRICTOR PLATE" EACH, OF THE DIAMETER SPECIFIED





VALUES OF "C" FOR CIRCULAR AND SQUARE ORIFICES


ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN

ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT NO. 1 SCHAUMBURG


MANHOLE WITH RESTRICTOR PLATE DETAIL

SCALE NONE DATE MARCH 18, 2008


DRAWN BY JWM CHECKED BY PJO











AS SHOWN ON PLANS OUTLET PIPE

-2-600 (24) DIA. OPENINGS IN FLAT SLAB TOP

TOP OF GRATE LID ELEVATION

-MANHOLE, TYPE A

-75 X 75 (3 X 3) STEEL ANGLES

-OUTLET PIPE

(STD. 602406 OR 602411)

WITH 2 FRAMES AND

GRATES/LIDS

PLAN

SECTION A-A

16 (5/8) STEEL-

RESTRICTOR PLATE


INLET PIPE

RESTRICTOR TYPE AS NOTED-

B (24)

IN RESTRICTOR TABLE

INLET PIPE-



TYPICAL VERTICAL ANGLES LOOKING TOWARD MANHOLE WALL

2. VERTICAL ANGLES SHOULD EXTEND


3. HORIZONTAL ANGLES SHOULD EXTEND FROM VERTICAL ANGLE TO VERTICAL ANGLE


PLATE TO THE TOP


FROM THE BOTTOM OF THE RESTRICTOR


Rev. 05-01-08 JCM


STEEL ANGLE BOLTING DETAILS














## RURAL FIELD ENTRANCE (FE) HMA SURFACE COURSE, MIX "C", N50, 2 (50) MEASURED IN TONS (METRIC TONS)

AGGREGATE BASE CSE., TYPE A 8 (200) MEASURED IN SQ. YD. (m²).

## GENERAL NOTES:

DRIVEWAY SLOPES, LOCATIONS, & GEOMETRIC LAYOUT SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE "HANDBOOK FOR POLICY ON PERMITS FOR ACCESS DRIVEWAYS TO STATE HIGHWAYS". FOR FURTHER LAYOUT REQUIREMENTS, REFER TO ILLUSTRATIONS IN THE PERMIT HANDBOOK. DRIVEWAYS SHALL BE REPLACED IN KIND, UNLESS OTHERWISE NOTED ON THE PLANS.

COMMERCIAL DRIVEWAYS SHALL BE CONSTRUCTED WITH CONCRETE CURB, TYPE B RETURNS EXCEPT WHEN THE SIDEWALK EDGE IS 4 FEET (1.2 METERS) OR LESS FROM THE BACK OF CURB, CONSTRUCT A FLARE DRIVEWAY WITHOUT CURB.


THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC PERMIT OFFICE AT 847/ 705-4131 FOR ANY QUESTIONS ON DRIVEWAYS SHOWN IN THE PLANS; SPECIFICALLY IN REFERENCE TO ADDITIONAL AND/OR RELOCATION/REMOVAL OF A DRIVEWAY.

COMBINATION CONCRETE CURB & GUTTER SHALL BE MEASURED STRAIGHT ACROSS THE DRIVEWAY. NO ADDITIONAL COMPENSATION WILL BE ALLOWED FOR THE CURB & GUTTER TRANSITION.

1 (25) PREFORMED EXPANSION JOINT FILLER WILL NOT BE PAID SEPARATELY, BUT SHALL BE CONSIDERED INCLUDED IN THE COST OF THE P.C.C. DRIVEWAY PAVEMENT OR P.C.C. SIDEWALK.

WHEN THE P.C.C. SIDEWALK EXTENDS THROUGH THE DRIVEWAY, THE THICKNESS OF THE SIDEWALK IN THE DRIVEWAY AREA SHALL BE THE SAME AS THE DRIVEWAY THICKNESS. SIDEWALK WILL BE PAID FOR AS P.C.C. SIDEWALK OF THE THICKNESS SPECIFIED. SIDEWALK CROSS SLOPE THRU DRIVEWAY AREA TO BE A MAXIMUM OF 1:50. ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE NOTED

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION	
NAME	DATE	ILLINOIS DEFARINGNI OF TRANSFORTATION	
R. SHAH	11-04-95	DRIVEWAY DETAILS	
J. POLLASTRINI	08-12-96		
	12-14-96	DISTANCE BETWEEN R.O.W. AN	D
A. ABBAS	03-21-97	FACE OF CURB & EDGE OF	
	04-08-97	TACE OF COIND & EDGE OF	
M. GOMEZ	04-06-01	1 SHOULDER >= 15′(4.5 m)	
P. LaFLEUR	04-15-03		
R. BORO	01-01-07	SCALE: VERT. NONE DRAWN BY	
		HORIZ.	
*****		1 auguse ny	



WHEN THE DISTANCE BETWEEN R.O.W. AND THE BACK OF CURB IS EQUAL TO OR LESS THAN 8' (2.4 m), THE P.C.C. SIDEWALK SHALL EXTEND TO THE

BACK OF CURB.

01 DATE = 3/5/2007 LE NAME = Kidiststd/bd02.dgn 01 SCALE = 50.0000 '/ IN.

BD400-02 (BD-02)

DRAWN BY

CHECKED BY

DISTANCE BETWEEN ROW AND

FACE OF CURB < 15' (4.5 m)

A. ABBAS

T. HOLTZ M. GOMEZ P. LaFLEUR

R. BORO

04/08/97 04/06/01 04/15/03

01/01/07

SCALE: VERT. NONE


THE 1 (25) PREFORMED EXPANSION JOINT FILLER WILL NOT BE PAID

"W" VARIES FROM 36 (900) TO 5' (1.5 m) PROPORTIONAL TO THE

LENGTH (L), FROM 6' (1.8 m) TO 10' (3 m).


SEPARATELY, BUT SHALL BE CONSIDERED INCLUDED IN THE COST OF THE P.C.C. DRIVEWAY PAVEMENT OR P.C.C. SIDEWALK.


CONTRACT NO.



## DETAIL "A"

LATERAL CONNECTION TO EXISTING SEWER OF 27" (675) OR SMALLER






∽CLASS SI CONCRETE~

<u>DETAIL "B"</u> CLASS SI CONCRETE COLLAR

### CONSTRUCTION SEQUENCE

- CUT THE EXISTING END OF THE PIPE SO AS TO PRESENT A FLUSH BUTT JOINT. BRUSH AND CLEAN ALL PIPES.
- 2. APPLY THE MASTIC JOINT SEALANT TO THE FIRST. 6" (150) OF EACH PIPE.
- 3. BUTT THE PIPES TOGETHER LEAVING A MINIMUM OF 12' × 6' (300 × 150) DEEP EXCAVATION UNDER AND AROUND EACH PIPE END.
- 4. CUT A PIECE OF SHEET METAL GAGE NO. 19 1.1 (0.0418) 18" (450) WIDE BY THE OUTSIDE CIRCUMFERANCE OF THE PIPE PLUS 3" (75) LONG.
- 5. WRAP THE SHEET METAL AROUND THE PIPES, 9" (225) ON EACH SIDE OF THE JOINT, STARTING AT THE TOP OF THE PIPE.
- 6. LAP THE SHEET METAL AT LEAST 3" (75) AT THE TOP OF THE PIPE AND PLACE THE MASTIC JOINT SEALANT BETWEEN THE LAP.
- PLACE TWO METAL BANDS AROUND THE SHEET METAL AND TIGHTEN.
- 8. WIPE OFF ANY EXCESS MASTIC JOINT SEALANT THAT OOZES OUT FROM BETWEEN THE SHEET METAL AND THE PIPES.
- 9. PLACE CLASS SI CONCRETE AROUND THE



## DETAIL "C"

PROPOSED LATERAL
CONNECTION TO EXISTING SEWER
OF 30" (750) OR LARGER

## NOTES

#### MATERIA

MATERIAL USED FOR THE TEE OR WYE SECTION SHALL BE COMPATIBLE WITH THE EXISTING STORM SEWER OR THE PROPOSED STORM SEWER.

#### CONSTRUCTION METHODS

- THIS WORK SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE APPLICABLE PORTIONS OF SECTION 550 OF THE STANDARD SPECIFICATIONS.
- II. CONNECTION TO AN EXISTING STORM SEWER SHALL BE BY EITHER OF THE FOLLOWING METHODS:
  A) PROPOSED STORM SEWER CONNECTION TO EXISTING SEWER OF 27" (675) OR SMALLER SEE DETAIL "A" AND "B".
  - B) PROPOSED STORM SEWER CONNECTION TO EXISTING SEWER OF 30" (750) OR LARGER SEE DETAIL "C".

IF THE EXISTING SEWER PIPE IS CRACKED, BROKEN OR OTHERWISE DAMAGED BY THE CONTRACTOR IN MAKING THE CIRCULAR OPENING, THE CONTRACTOR SHALL REPLACE THAT SECTION OF PIPE WITH PIPE EQUAL AND SIMILAR IN ALL RESPECTS TO THE PIPE IN THE EXISTING SEWER, IN A CAREFUL WORKMANLIKE MANNER, WITHOUT EXTRA COMPENSATION.

## GENERAL

CARE MUST BE TAKEN TO PREVENT DEBRIS FROM ENTERING THE SEWER. ALL DEBRIS WHICH ENTERS THE SEWER MUST BE REMOVED. THE SEWER MUST BE LEFT CLEAN AND UNOBSTRUCTED UPON COMPLETION OF THE CONTRACT.

CARE MUST BE TAKEN TO PREVENT ANY PART OF THE NEW PIPE CONNECTION FROM PROJECTING INTO THE EXISTING SEWER.

#### BASIS OF PAYMENT

TEE OR WYE CONNECTIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR STORM SEWER TEE OR WYE OF THE TYPE AND SIZE SPECIFIED IN THE PLANS, THIS PRICE SHALL INCLUDE ALL EXCAVATION OF THE TRENCH, REMOVAL OF THE EXISTING STORM SEWER, FURNISHING AND INSTALLING THE RECUIRED CONCRETE COLLAR, AND ALL OTHER MATERIAL NECESSARY TO COMPLETE THIS WORK AS SHOWN AND SPECIFIED.

REMOVAL AND REINSTALLATION OF EXISTING STORM SEWER ADJACENT TO THE PROPOSED TEE OR WYE SECTION, FOR THE PURPOSE OF FACILITATING THE INSTALLATION OF THE TEE OR WYE SECTION, WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE UNIT PRICE BID FOR THE WORK.

TRENCH BACKFILL, EXCAVATION IN ROCK AND REMOVAL AND REPLACEMENT OF UNSUITABLE MATERIAL BELOW PLAN BEDDING GRADE WILL BE PAID FOR SEPARATELY.

CONCRETE COLLAR FOR CONNECTING A PROPOSED STORM SEWER TO AN EXISTING STORM SEWER
WILL NOT BE PAID PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE PROPOSED
STORMS SEWER

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

REVISIO		
NAME	DATE	
M. DE YONG	07/25/90	
M. DE YONG	02/05/92	
M. DE YONG	05/08/92	
R. SHAH	09/09/94	CC
R. SHAH	10/25/94	
R. SHAH	06/12/96	

ILLINOIS DEPARTMENT OF TRANSPORTATION


DETAIL OF STORM SEWER
CONNECTION TO EXISTING SEWER

SCALE: VERT. NONE

DRAWN BY CHECKED BY

OT DATE = 3/5/2007 LE NAME = Kindiststo OT SCALE = 50.000 ' / ER NAME = bowerdl

BD500-01 (BD-7)



## NOTES:

- 1. THE WIDTH OF THE FULL DEPTH PATCH OVER A TRENCH SHALL BE 12 (300) WIDER ON EACH SIDE OF THE TRENCH.
- 2. FOR METHOD OF MEASUREMENT AND BASIS OF PAYMENT, SEE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

## SEQUENCE OF CONSTRUCTION

- 1. REMOVE THE EXISTING HMA MATERIAL OVER THE AREA TO BE PATCHED.
- 2. REMOVE AND REPLACE FULL DEPTH PATCHES
- 3. REPLACE HMA MATERIAL OVER THE AREA TO BE PATCHED.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

REVISIO	ILL	
NAME	DATE	11.1.
R. SHAH	10/25/94	
R. SHAH	01/14/95	
R. SHAH	03/23/95	
R. SHAH	04/24/95	
A. HOUSEH	03/15/96	
A. ABBAS	03/21/97	
A. ABBAS	01/20/98	
ART ABBAS	04/27/98	SCALE: V
R. BORO	01/01/07	SCALE: H

INOIS DEPARTMENT OF TRANSPORTATION

PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT

VERT. HORIZ, NONE

CHECKED BY BD400-04 (BD-22)

NOTES: 1. THE HMA SHOULDER SHALL EXTEND UNDER THE TRAFFIC BARRIER TERMINAL

2. GUARD RAIL MAY BE PLACED AT THE BACK OF CURB WHEN DIRECTED BY THE ENGINEER.

BASIS OF PAYMENT: HMA SHOULDER 6 (150) WILL BE

PAID FOR AT THE CONTRACT UNIT PRICE
PER SQUARE YARD (SQUARE METER) FOR
"HOT-MIX ASPHALT SHOULDER 6" (150 mm)".

STEEL PLATE BEAM GUARD RAIL AND TRAFFIC BARRIER TERMINAL, OF THE TYPE SPECIFIED WILL BE PAID FOR SEPARATELY.

DETAILS FOR STEEL PLATE BEAM

GUARD RAIL ADJACENT TO CURB AND GUTTER

[FOR ROADWAY SPEED 35 MPH (60 kmh) TO 45 MPH (70 kmh)]

OFFSET BASED ON MANUFACTURERS'
SPECIFICATIONS

GUARDRAIL TBT TAPER OR FLARE
BASED ON MANUFACTURER'S SPECIFICATIONS

DISTANCE FROM FACE
OF RAIL 3'-0" (0.9 m)

EDGE OF PAVEMENT

EDGE OF SHOULDER STABILIZATION

DEPRESSED CURB FOR URBAN CROSS SECTION
WITH CURB AND GUTTER

BASED ON MANUFACTURER'S SPECIFICATIONS 37'-6" (11.4 m) MIN. 50'-0" (15.2 m) MAX.

EDGE OF SHOULDER OR | BACK OF CURB & GUTTER

> EDGE OF SHOULDER STABILIZATION —

1:10 MAX\_ CROSS SLOPE

> \_\_\_10'-0" (3.0 m) UNLESS OTHERWISE NOTED

VARIES

STABILIZATION AT TBT TY. 1 SPL.

TBT = TRAFFIC BARRIER TERMINAL

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

	REVISIONS		
	NAME	DATE	
٧.	DE YONG	09-22-90	
Μ.	DE YONG	07-14-92	
R.	SHAH	09/09/94	S
R.	SHAH	10/25/94	
R.	SHAH	02/23/95	A
Α.	ABBAS	03/21/97	l st
E,	GOMEZ	08/28/00	٠.
		01/01/07	SCAL
			. ⊃LAŁ

ILLINOIS DEPARTMENT OF TRANSPORTATION

DETAILS FOR STEEL PLATE BEAM GUARD RAIL ADJACENT TO CURB AND GUTTER STABILIZATION AT TBT TY 1 SPL.

CALE: VERT. NONE

DRAWN BY JIS CHECKED BY

CONTRACT NO.

525 399


COUNTY


TO STA.

SECTION

2'-6" (750 mm) SHOULDER

2'-9" (825 mm) CURB & GUTTER





SEQUENCE OF CONSTRUCTION:

- 1. CLOSE EXISTING VALVE.
- 2. REMOVE EXISTING HYDRANT.
- 3. INSTALL HYDRANT EXTENSION AND NEW VALVE.
- 4. RELOCATE EXISTING HYDRANT.
- 5. OPEN EXISTING VALVE, REMOVE BOX.
- 6. BACKFILL.
- 7. FLUSH AND TEST FOR CHLORIDE RESIDUAL AND PROVIDE TEST.

ALL WORK TO BE DONE IN ACCORDANCE WITH ARTICLE 564 OF THE STANDARD SPECIFICATIONS. NEW VALVE AND BOX SHALL BE SAME MAKE AND MODEL AS EXISTING.

FIRE HYDRANT TO BE MOVED

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS

		THERWISE SHOWN.	TOTIES TWIELING FERTS DIVELS			
REVISIO	ONS	ILLINOIS DEPARTMEN	NT OF TRANSPORTATION			
NAME	DATE	IELINOIS DEPARTMEN	NI OF TRANSPORTATION			
R. SHAH	09/09/94					
R. SHAH	10/25/94					
		FIRE	HYDRANT			
		TO RE	E MOVED			
		. 0 2	1110128			
		SCALE: VERT. NONE	DRAWN BY			
	_	HORIZ.	CHECKED BY			