



Adjustable door stay keeps door open during maintenance

Reinforced double hinged door with stainless steel hardware

LB-42-26-29-1B Base for concrete

LB-29-17-12-A Mounting Adapter

LB-5-15-36 Pedestal, 3 bolt, 36" high

LB-42-26-14 This cabinet is designed as an outdoor enclosure for panel mounted street lighting control equipment, traffic signal controllers and cable terminations. The inside dimensions are: 42" high x 26" wide x 14" deep. Typical wall thickness is .250". A reinforced hinged door comes equipped with a safe enclosure lock, when closed maintains a positive pressure against a neoprene gasket, making the cabinet weather resistant. An adjustable door stay holds the door open during maintenance. Added protection from the rain and dust is provided by a water-shed extending 1/4" from the face of the cabinet completely surrounding the door opening. A legend, as specified, can be integrally cast on the door in 1" letters raised 1/8" high. See the accessories page for optional mounting and venting methods.

LB-42-26-29-1B Base for concrete mounting of LB-42-26-14 cabinet. Dimensions are 29" long x 17" wide x 12" high. Four bolts secure the base to the foundation.

Important: This box is cast in one piece. No welded joints or seams that can leak. The wall thickness is .250" as compared to a fabricated box that has a thin wall of .125" typical.

STREET LIGHTING

CITY OF ELMHURST

LB-SSL Standard "Street Lighting" nameplate. Measures 5" tall x 9" long x .250" thick

LB-8CO "City of _____" nameplate. Made to order with specified name. Measures 5 1/2" tall x 9" long x .250" thick

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION F.A.U. YORK ROAD
NAME	DATE	
		LIGHTING DETAILS

SCALE: NTS
12/22/07

DRAWN BY: BCD
CHECKED BY: JDM