

I-80 PATCHING SCHEDULE CLASS A 15"									
MILE MARKER 105(819+51.05) TO 112(1200+73.48) EAST BOUND									
LOG MILE	DRIVING LANE	PASSING LANE	TYPE III	TYPE II	GEOTECH.	AGGREGATE			
STARTING AT 105 (STA)	(FT)	(FT)	(SY)	(SY)	FABRIC FOR	SUBGRADE	PATCH	SAW	TIE
			SQ YD	SQ YD	GROUND STABILIZ.	12"	REINF.	CUTS	BARS 3/4"
					SQ YD	SQ YD	SQ YD	FOOT	EACH
0.4 (840+63.05)	6			8.0	8.0	8.0	8.0	66	12
0.7 (856+47.05)	10			13.3	13.3	13.3	13.3	78	12
0.78 (860+69.45)	6			8.0	8.0	8.0	8.0	66	12
0.8 (861+75.05)	6			8.0	8.0	8.0	8.0	66	12
0.84 (863+86.25)	20		26.67		26.7	26.7	26.7	120	12
0.85 (864+39.05)	10	8		24.0	24.0	24.0	24.0	140	24
1.2 (882+87.05)	6			8.0	8.0	8.0	8.0	66	12
1.28 (887+09.45)	6			8.0	8.0	8.0	8.0	66	12
1.6 (903+99.05)	10			13.3	13.3	13.3	13.3	78	12
3 (977+91.05)	14		18.67		18.7	18.7	18.7	100	12
3.6 (1009+59.05)	6			8.0	8.0	8.0	8.0	66	12
4.1 (1035+99.05)	6			8.0	8.0	8.0	8.0	66	12
5.3 (1099+35.05)	6			8.0	8.0	8.0	8.0	66	12
5.4 (1104+63.05)	6			8.0	8.0	8.0	8.0	66	12
5.45 (1107+27.05)	6			8.0	8.0	8.0	8.0	66	12
5.45 (1107+27.05)	6			8.0	8.0	8.0	8.0	66	12
5.46 (1107+79.85)	6			8.0	8.0	8.0	8.0	66	12
5.8 (1125+75.05)	6			8.0	8.0	8.0	8.0	66	12
6.4 (1157+43.05)	8			10.7	10.7	10.7	10.7	70	12
6.5 (1162+54.86)	6			8.0	8.0	8.0	8.0	66	12
TOTAL			45.3	173.3	218.7	218.7	218.7	1510.0	252.0

PAVEMENT MARKINGS									
LOCATION	LENGTH	THERMOPLASTIC PAVEMENT MARKING		PREFORMED PVMT MK TAPE INLAID	TEMPORARY			SHORT TERM	WORK ZONE
		4"		6"	4"		6"	PVMT MK	PVMT MK REM
		WHITE LIN FT	YELLOW LIN FT	WHITE LIN FT	WHITE LIN FT	YELLOW LIN FT	WHITE LIN FT	LIN FT	SQ FT
GRUNDY COUNTY									
819+51.06 TO 1157+55.38	33804.3	33804.3	33804.3	8451	33804.3	33804.3	8451	3380.43	1125.7
1157+ 71.57 TO 1200+73.48	4301.91	4301.91	4301.91	1075	4301.91	4301.91	1075	430.191	143.3
PROJECT TOTAL		38106	38106	9526	38106	38106	9526	3811	1269

MAINLINE SCHEDULE							
LOCATION	LENGTH	WIDTH	AREA	ULTRA THIN BONDED WEARING SURFACE	POLYMER MODIFIED ASPHALT EMULSION	PCC SURFACE REMOVAL BUTT JT	TEMP. RAMP
	FEET	FEET	SQ YD	SQ YD	GALLON	SQ YD	SQ YD
STA. 819+51.05 TO STA. 1157+55.38	33804.33	24	90144.88	90144.88	15324.6	80	10
STA. 1157+71.57 TO STA. 1200+73.48	4301.91	24	11471.76	11471.76	1950.2	80	10
LINE TOTAL	38106.24		101617	101616.64	17274.8	160	20

RAISED REFLECTIVE MARKERS			
LOCATION		1 WAY CRYSTAL	REMOVAL
		EACH	EACH
STA. 819+51.05 TO STA. 1157+55.38	33804.3	845	845
STA. 1157+71.57 TO STA. 1200+73.48	4301.91	108	108
TOTAL		953	953