

CLASS B PATCHING 12"						
STA	SIDE	LENGTH	TYPE III	SAW CUTS	PAVEMENT FABRIC	DOWEL BARS
		FT	SQ YD	FT	SQ YD	EACH
406+95	NB	12	17.3	63	17.3	20
406+95	SB	12	17.3	51	17.3	20
TOTAL		24	34.6	114	34.6	40

MANHOLE AND WATER VALVE ADJUSTMENTS		
LOCATION	MANHOLE ADJUSTMENTS	WATER VALVE ADJUSTMENTS
	EA	EA
CHERRY	19	1
LADD	10	1
TOTAL	29	2

SIDE ROADS AND ENTRANCED SCHEDULE								
LOCATION	STA.	RT/LT	ENT. TYPE	HMA SURF.	INCIDENTAL	BIT. MAT'L	AGG.	TEMP
				REM.	HMA SURF.	(PR CT)	(PR CT)	RAMPS
				SQ YD	TONS	GAL	TONS	SC YD
PARK AVE.	404+60	RT	SR	43.9	5.5	3.5	0.1	13.8
PARK AVE.	404+60	LT	SR	37.8	4.8	3.0	0.1	12.4
CAMPBELL AVE.	408+82	RT	SR	87.3	11.0	7.0	0.2	11.6
CAMPBELL AVE.	408+82	LT	SR	85.7	10.8	6.9	0.2	11.6
CHERRY AVE.	412+41	RT	SR	80.8	10.2	6.5	0.2	11.6
CHERRY AVE.	412+41	LT	SR	84.7	10.7	6.8	0.2	11.6
MAPLE AVE.	416+02	RT	SR	76.2	9.6	6.1	0.2	11.6
MAPLE AVE.	416+05	LT	SR	80.8	10.2	6.5	0.2	11.6
LINCOLN AVE.	419+67	RT	SR	46.7	5.9	3.7	0.1	11.1
LINCOLN AVE.	419+67	LT	SR	34.7	4.4	2.8	0.1	11.1
LARSON AVE.	423+23	RT	SR	79.5	10.0	6.4	0.2	10.7
LARSON AVE.	423+23	LT	SR	85.7	10.8	6.9	0.2	12.0
	424+49	RT	PE	21.1	2.7	1.7	0.0	
	424+71	LT	PE	21.7	2.7	1.7	0.0	
MAIN ST.	425+79	LT	SR	85	10.7	6.8	0.2	11.1
SOUTH AVE.	428+60	LT	SR	91.7	11.6	7.3	0.2	11.1
FIRST ST.	430+10	RT	SR	100.6	12.7	8.0	0.2	
	430+12	LT	CE	74.4	9.4	6.0	0.1	
	432+77	RT	PE	26.1	3.3	2.1	0.1	
	434+57	RT	PE	34.8	4.4	2.8	0.1	
	438+40	RT	CE	22.2	2.8	1.8	0.0	
	439+80	LT	PE	76.1	9.6	6.1	0.2	
	440+91	RT	CE	53.3	6.7	4.3	0.1	
1900 N	442+45	RT	SR	158.3	19.9	12.7	0.3	14.2
3300 E	445+30	RT	SR	91.75	11.6	7.3	0.2	12.0
	469+94	RT	PE	17.7	2.2	1.4	0.0	
	470+55	RT	PE	48	6.0	3.8	0.1	
C.H. 33	497+07	RT	SR	NO WORK				
C.H. 33	497+07	LT	SR	NO WORK				
	504+44	RT	PE	25.6	3.2	2.0	0.1	
	504+57	LT	MBT	52.1	6.6	4.2	0.1	
	519+24	LT	PE	65	8.2	5.2	0.1	
1700 N	549+67	RT	SR	94.4	11.9	7.6	0.2	8.9
1700 N	549+67	LT	SR	102.8	13.0	8.2	0.2	8.9
	551+36	RT	PE	48.4	6.1	3.9	0.1	
	561+64	LT	PE	43.9	5.5	3.5	0.1	
	563+67	LT	CE	36.7	4.6	2.9	0.1	
	563+74	LT	PE	30	3.8	2.4	0.1	
	566+21	LT	CE	37.2	4.7	3.0	0.1	
	566+35	RT	PE	30	3.8	2.4	0.1	
	568+67	LT	PE	37.2	4.7	3.0	0.1	
	572+95	LT	CE	47.8	6.0	3.8	0.1	
	575+73	LT	CE	129	16.3	10.3	0.3	
	577+70	LT	CE	35	4.4	2.8	0.1	
	579+29	LT	PE	63.3	8.0	5.1	0.1	
	580+20	LT	PE	35	4.4	2.8	0.1	
	579+12	RT	CE	277.8	35.0	22.2	0.6	
WALNUT ST	582+40	RT	SR	57.3	7.2	4.6	0.1	15.6
CHESTNUT ST	585+99	RT	SR	67.7	8.5	5.4	0.1	15.6
CHESTNUT ST	585+99	LT	SR	77.3	9.7	6.2	0.2	15.1
CEDAR ST	589+67	RT	SR	57.3	7.2	4.6	0.1	14.7
CEDAR ST	589+67	LT	SR	63	7.9	5.0	0.1	14.7
ELM ST	593+18	RT	SR	70	8.8	5.6	0.1	16.0
ELM ST	593+18	LT	SR	56.7	7.1	4.5	0.1	15.6
PINE ST	596+80	RT	SR	60.7	7.6	4.9	0.1	16.0
PINE ST	596+80	LT	SR	67.9	8.6	5.4	0.1	16.0
LOCUST ST	600+42	RT	SR	63.8	8.0	5.1	0.1	14.2
LOCUST ST	600+42	LT	SR	50.7	6.4	4.1	0.1	11.6
CLEVELAND ST	602+88	RT	SR	114.7	14.5	9.2	0.2	13.3
CLEVELAND ST	602+88	LT	SR	39.6	5.0	3.2	0.1	11.3
	604+92	LT	PE	32.8	4.1	2.6	0.1	
	605+10	LT	PE	22.2	2.8	1.8	0.0	
	606+88	LT	CE	27.2	3.4	2.2	0.1	
	607+82	LT	CE	41.1	5.2	3.3	0.1	
	608+38	LT	CE	67.8	8.5	5.4	0.1	
	608+70	LT	CE	67.8	8.5	5.4	0.1	
TOTALS				4043.35	509.5	4552.8	8.1	402.6