

**PIPE UNDERDRAINS**

STATION	CONCRETE HEADWALL FOR PIPE DRAINS	PIPE UNDERDRAINS, 6"	PIPE DRAINS, 6"
STATION	EACH	FOOT	FOOT
43+00	•	25	0.0
44+00	1	25	34.6
45+00	1	25	42.0
46+00	1	25	52.0
47+00	1	25	58.8
48+00	1	25	61.8
52+00	1	25	62.8
53+00	1	25	59.5
54+00	1	25	53.8
55+10	1	25	50.0
56+00	1	25	40.2
56+96	•	25	0.0
<b>ACTUAL TOTAL</b>	<b>10</b>	<b>300</b>	<b>515.5</b>
<b>USED TOTAL</b>	<b>10</b>	<b>300</b>	<b>516.0</b>

• TO BE OUTLET INTO TYPE E SHOULDER INLET

**PIPE DRAINS, 12"**

LOCATION	PIPE DRAINS, 12"	TYPE D INLET BOX, STD. 609006	TYPE E INLET BOX, STD. 610001	CONCRETE TRUST BLOCKS	METAL END SECTION 12"
STATION	FOOT	EACH	EACH	EACH	EACH
43+00.0 LT & RT	34.8	0	2	2	2
45+00.0 LT & RT	65.2	0	2	2	2
46+76.5 LT & RT	93.8	0	2	2	2
48+76.5 LT & RT	112.0	2	0	2	2
51+23.5 LT & RT	118.0	2	0	2	2
53+23.5 LT & RT	103.7	0	2	2	2
55+00.0 LT & RT	76.3	0	2	2	2
56+96.0 LT & RT	38.2	0	2	2	2
<b>ACTUAL TOTAL</b>	<b>642.0</b>	<b>4</b>	<b>12</b>	<b>16</b>	<b>16</b>
<b>USED TOTAL</b>	<b>642.0</b>	<b>4</b>	<b>12</b>	<b>16</b>	<b>16</b>

**CULVERTS & INLETS**

LOCATION	PIPE CULVERTS			CONCRETE COLLAR	METAL END SEC. EQUIVALENT ROUND 15"	METAL END SECTIONS 15"	END SECTIONS 18"	MANHOLE TO BE ADJUSTED
	TYPE 1 ERS 15"	TYPE 1 15"	TYPE 1 RCCP 18"					
STATION	FOOT	FOOT	FOOT	CU. YD.	EACH	EACH	EACH	EACH
306+42 LT 306+63 RT 57+50.80 LT	30.0	47.0			2	2		1
RAMP B 299+28.2			7.5	0.35			1	
RAMP C 502+31.9			6.5	0.35			1	
RAMP D 99+21.0			5.9	0.35			1	
<b>ACTUAL TOTAL</b>	<b>30</b>	<b>47</b>	<b>19.9</b>	<b>1.1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>1</b>
<b>USED TOTAL</b>	<b>30</b>	<b>47</b>	<b>20.0</b>	<b>1.1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>1</b>

**CURBS & GUTTERS**

LOCATION	COMBINATION CONCRETE CURB & GUTTER	HMA SHOULDER CURB	CURB & GUTTER OUTLET SPECIAL
	TY. B-6.24	FOOT	EACH
RAMP A	248.1		4
RAMP B	230.3		4
RAMP C	217.9		4
RAMP D	211.1		4
42+97.3 LT TO 48+60.5 LT		563.2	
42+78.6 LT TO 48+60.5 LT		581.9	
51+39.5 LT TO 57+21.4 LT		581.9	
51+39.5 LT TO 56+96.4 LT		556.9	
<b>ACTUAL TOTAL</b>	<b>907.4</b>	<b>2,283.9</b>	<b>16</b>
<b>USED TOTAL</b>	<b>907.5</b>	<b>2,284.0</b>	<b>16</b>

**LIGHTING**

LOCATION	UNIT DUCT RUN LENGTH*	TRENCH & BACKFILL	LIGHT POLE FOUNDATION 30" DIAMETER	BREAKAWAY DEVICE, COUPLING, SS SCREEN	POLE FOUNDATION REMOVED	RELOCATE EXISTING LIGHTING UNIT
	FOOT	FOOT	FOOT	EACH	EACH	EACH
Ex. Citr						
110	234	178	5.25	4	1	1
109	299	293	5.25	4	1	1
108	296	290	5.25	4	1	1
107			5.25	4	1	1
106	261	255	5.25	4	1	1
105	315	309	5.25	4	1	1
105	28	22				
104	299	243				
<b>ACTUAL TOTAL</b>	<b>1732</b>	<b>1590</b>	<b>31.5</b>	<b>24</b>	<b>6</b>	<b>6</b>
<b>USED TOTAL</b>	<b>1732</b>	<b>1590</b>	<b>32.0</b>	<b>24</b>	<b>6</b>	<b>6</b>

\*Includes 6 feet of slack for each run. Lengths measured with CADD.

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

**SCHEDULE OF QUANTITIES**

SCALE: NONE  
DATE: 06/2003

DRAWN BY: FML  
CHECKED BY: YML