

Support Design Loads: See Base Sheet OS-A-1 for design and loading criteria.

Load combinations checked include deadload plus:

a) 100% wind normal to sign, 20% parallel to sign b) 60% wind normal to sign, 30% parallel to sign

(1) In lieu of fabricated handhole frame as shown, may cut from 2" plate (rolling direction vertical). All cut faces to be ground to ANSI Roughness of 500 μ in or less.

2 Galvanizing vent holes of adequate size shall be provided on underside at each end of bracing pipes. Alternately, holes may be provided in wall of pipe column. All vent holes shall be drilled and de-burred, typ.

3 Steel pipe, plate, carbon steel handhole covers and rolled sections shall be hot dip galvanized after fabrication. Painting is not permitted. See Base Sheet OS-A-1.

4) See General Notes for fasteners.

5 Dimensions shown are based on selection criteria in the Sign Structures Manual. Nonstandard applications must have dimensions verified or amended as appropriate.

(6) "H" based on 15'-0'' or actual sign height, whichever is greater.

END ELEVATION

SN-031 SN-031 SN-032 SN-032 SN-034 SN-034 SN-039

SN-039

| Structure Number | Station | Support | | Truss | Pipe Wall | Н | |
|---------------------|---------|---------|-------|-------|-----------|------------------------|------------------------|
| | | Left | Right | Туре | Thickness | 6 | A |
| 2S101I039R138.8 | | | Х | II- A | 0.500" | 32′-8 ³ 4" | |
| 2S101I039R138.8 | | Х | | II-A | 0.500" | 31'-3 ³ 4" | 23'-11" |
| 2S101I039R139.4 | | | Х | II-A | 0.500" | 34'-4 ⁵ 8" | 26'-11 ⁷ 8' |
| 2S101I039R139.4 | | Х | | II-A | 0,500" | 32'-6 ³ 8" | 25′-1 ⁵ 8" |
| 2S101U020R021.5 | | | Х | II-A | 0.365" | 29'-4 ⁵ 8" | 21'-11 ⁷ 8" |
| 2S101U020R021.5 | | Х | | II-A | 0.365" | 29'-11 ³ 8" | 22'-6 ⁵ 8' |
| 2S071I039L118.7 | | | Х | II-A | 0.365" | 30′-11 ⁵ 8" | 23'-678' |
| 2S071I039L118.7 | | Х | | II-A | 0.365" | 30′-3" | 22'-104' |
| | | | | | | | |

0S-A-6

6 - 1 - 12

Truss

Туре

II-A (5)

R

4'-6"

S

5'-5'2"

5'-3" | 6'-34"

| | USER NAME = jattanaseo | DESIGNED | - | NG | REVISED - | | |
|--------|---------------------------------|----------|---|-----|-----------|--|--|
| , inc. | | CHECKED | - | BWS | REVISED - | | |
| | PLOT SCALE = 0:2.0000 ':" / 10. | DRAWN | - | RD | REVISED - | | |
| | PLOT DATE = 1/31/2014 | CHECKED | - | BWS | REVISED - | | |

4'-0"

4'-6''

Dimensions

6'-434'

6'-11³4''

W

4"

434''

X

8'-3"

8'-3"

9"

912"

U

5'-6"

6'-1''

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

COUNTY SECTION **OVERHEAD SIGN STRUCTURES** 45 33 SUPPORT FRAME FOR ALUMINUM TRUSS D-2 OVD SIN STR REPL 14-27 CONTRACT NO. 46288 SHEET NO. S-14 OF S-26 SHEETS

•• WINNEBAGO & OGLE

10" \$\phi\$ PIPE TRUSS SUPPORT FRAME

support frame. If used, weld procedure must be pre-

** One butt welded joint is allowed only on one post per

approved by Engineer and joint shall receive 100%

RT or UT (tension criteria) at Contractor's expense.