

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BRS. form 137 (Rev. 8



SOIL BORING LOG

Page <u>2</u> of <u>2</u>

| ROUTE | FAS 1388 (IL 8 | 3) DE | ESCR | IPTION | 1 | | IL 8 Over Kickapoo C | reek | LOGGED | BY C. F |
|-------------------------------|--|-----------|-------------|-------------|-------------|--|--|--------------------|----------|---------|
| | • | | | | | SE 1/4, SEC. 24, TWP. 9N, RNG. 6E, 4 th PM, Latitude , Longitude | | | - | |
| COUNTY | Peoria | _ DRILLIN | G ME | THOD | _ | | HSA | _ HAMMER TY | PE | AUTO |
| STRUCT. NO. | . <u>072-004</u> 792+64.2 | 7 23 | D E P | B L O | U C S | M 0 1 | Surface Water Elev. Stream Bed Elev. | 489.04 488.00 | ît ît | |
| Station Offset | AE 802+67.1 30.0 ft L face Elev. 51 | 8 T | H | w s | Qu (tsf) | S T (%) | Groundwater Elev.: First Encounter Upon Completion After 24 Hrs. | 485.2 1 485.2 1 | t∇ | |
| Loose to Den | se, Tan Brown, ' | Very | . – | 12 22 | | | | | | |
| (continued) | | | - | 32 | | | | | | |
| Stiff to Hard, moist, CLAY | Dark Gray to Bla | ick, | _ | | | | | | | |
| | | | - | - | | | | | | |
| | | | _ | 1 | | | | | | |
| | | | _ | - | | | | | | |
| | | | -45 | | | | | | | |
| | | | | 50/0.3 | | | | | | |
| | | | _ | 1 | | | | | | |
| | | | _ | | | | | | | |
| | | | - | 1 | | | | | | |
| | | | _ | 50/0.3 | | | | | | |
| | | | _ | - | | | | | | |
| | | 460.24 | 4 -50 | | | | | | | |
| End of Boring | | | _ | | | | | | | |
| | | | _ | 1 | | | | | | |
| | | | _ | | | | | | | |
| | | | - | 1 | | | | | | |
| | | | _ | 1 | | | | | | |
| | | | _ | - | | | | | | |
| | | | -55 | 1 | | | | | | |
| | | | = | - | | | | | | |
| | | | _ | | | | | | | |
| | | | _ | | | | | | | |
| | | | - | 1 | | | | | | |
| | | | _ | 1 | | | | | | |
| | | | | | | l | | | | |

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, form 137 (Rev. 8-9

| FILE NAME = 0720229 | -68697-034-Soil Boring Logs.dgn |
|---------------------|--|
| REW | BACON FARMER WORKMAN ENGINEERING & TESTING, INC. |
| | 403 NORTH COURT STREET MARION, ILLINOIS 62959 PHONE - 618,997,9190 |

| USER NAME = | DESIGNED - | BWP | REVISED - |
|-----------------------|------------|-----|-----------|
| | CHECKED - | CMV | REVISED - |
| PLOT SCALE = | DRAWN - | BWP | REVISED - |
| PLOT DATE = 3/18/2014 | CHECKED - | CMV | REVISED - |



| SOIL BORING LOGS | F.A.S. RTE. | SECTION | COUNTY | TOTAL | SHEE NO. |
|---------------------------|----------------|---------------|---------------|-------|-------------|
| STRUCTURE NO. 072-0229 | 1388 | (Z-1D-BR-1)BR | PEORIA | 89 | 76 |
| 3111001011L NO. 072-0223 | | | CONTRACT | NO. (| 58697 |
| SHEET NO. 34 OF 34 SHEETS | | ILL INOIS FEE | . AID PROJECT | | |