

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	SIGNATURE SHEET
3	INDEX OF SHEETS, STANDARDS & MIXTURE REQUIREMENTS
4	GENERAL NOTES
5-6	SUMMARY OF QUANTITIES
7-9	TYPICAL SECTIONS
10	RESURFACING SCHEDULE
11	SIDEROADS RESURFACING SCHEDULE
12	ENTRANCES RESURFACING SCHEDULE
13-14	PAVEMENT MARKING SCHEDULE
15	SIDEROAD PAVEMENT MARKING SCHEDULE
16-34	PLAN SHEETS
35	DETAILS - BUTT JOINT & MILLING TRANSITION
36	DETAILS - SIDEROADS AND ENTRANCES
37	TEMPORARY HOT-MIX ASPHALT TRANSITIONS
38	DETAIL - UNEVEN LANES AND ROUGH GROOVED SURFACE SIGNS

STRUCTURE NO.	STRUCTURES WITHIN PROJECT LIMITS		POSTING	MTD USE
	OPERATING RATING	INVENTORY RATING		
064-0002	2.295	1.29	NONE	Empty
064-0003	1.745	1.05	NONE	Empty
064-7030	NA	NA	NONE	Empty
064-7031	NA	NA	NONE	Empty
064-7032	NA	NA	NONE	Empty
064-7033	NA	NA	NONE	Empty
064-7034	NA	NA	NONE	Empty
064-7035	NA	NA	NONE	Empty
067-7036	NA	NA	NONE	Empty
064-7037	NA	NA	NONE	Empty
064-7038	NA	NA	NONE	Empty

STANDARDS

000001-06	701306-03
406201-01	701311-03
442201-03	701336-06
701001-02	701901-03
701006-05	780001-04
701011-04	781001-03
701301-04	701426-06

MIXTURE REQUIREMENTS

Locations	Hot-Mix Asphalt Surface Course
Mixture Use(s):	Hot-Mix Asphalt Surface Course, Mix D, N90
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition (Gradation Mixture)	IL-9.5mm
Friction Aggregate:	D Surface
Quality Management Program:	QCP

Locations	Hot-Mix Asphalt Leveling Binder
Mixture Use(s):	Hot-Mix Asphalt Leveling Binder, N90, 9.5mm Fine Grade
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition (Gradation Mixture)	IL-9.5mm Fine Grade
Friction Aggregate:	None
Quality Management Program:	QCP

Locations	Class D Patching
Mixture Use(s):	Hot-Mix Asphalt Binder Course, N90, IL-19.0mm Fine Grade
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition (Gradation Mixture)	IL-19.0mm Fine Grade
Friction Aggregate:	None
Quality Management Program:	QC/OA

Locations	Incidental HMA Surface
Mixture Use(s):	Hot-Mix Asphalt Surface Course, Mix C, N90
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition (Gradation Mixture)	IL-9.5mm
Friction Aggregate:	C Surface
Quality Management Program:	QC/OA

FILE NAME =	USER NAME = *USER*	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS, MIXTURE REQUIREMENTS	F.A.S. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
c:\pwork\p1dot\holl\bl\0269923\78219	PLAN.dgn	DRAWN -	REVISED -			960	39RS-8, 40RS-10, 41RS-6	Massac	38	3	
PLOT SCALE = 100.0000' / 1"		CHECKED -	REVISED -			CONTRACT NO. 78219					
PLOT DATE = 3/20/2014		DATE -	REVISED -			SCALE:	SHEET NO.	OF	SHEETS	STA.	TO
ILLINOIS FED. AID PROJECT											