EXISTING:

- (A) EXISTING 9" CONTINUOUSLY REINFORCED PCC PAVEMENT
- B EXISTING HMA OVERLAY
- C EXISTING 4" STABILIZED SUBBASE
- D EXISTING TEMPORARY CONCRETE BARRIER WALL
- (E) EXISTING COMBINATION CONCRETE CURB AND GUTTER TYPE B-6.24
- (F) EXISTING CONCRETE CURB TYPE B
- G EXISTING GRASS MEDIAN
- (H) NOT USED
- I EXISTING 10" PCC BASE
- J NOT USED
- (K) EXISTING STABILIZED SHOULDERS, VARIES 12"-14"
- L EXISTING AGGREGATE SHOULDERS
- (M) EXISTING 9" PCC BASE
- (N) EXISTING STEEL GUARDRAIL
- O EXISTING TOPSOIL

PROPOSED:

- (1) POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "F", N90, 1 3/4 "
- (2) POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL-4.75, N50, 3/4 " & VARIES
- (3) HOT-MIX ASPHALT SHOULDERS, 10" POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "F", N90, 1 3/4 " HOT-MIX ASPHALT BINDER COURSE, IL 19.0, N70, 8 1/4
- (4) PCC PAVEMENT 9" (JOINTED)
- (5) AGGREGATE BASE COURSE, TYPE B 6"
- 6 AGGREGATE SUBGRADE IMPROVEMENT 60 3" CA-6 AGGREGATE CAP
 - (6b) 9" POROUS GRANULAR EMBANKMENT
- (7) AGGREGATE SHOULDERS, TYPE B, 6"
- (8) COMBINATION CONCRETE CURB AND GUTTER, B-6.18
- (9) PCC PAVEMENT 10 1/2" (JOINTED)
- (10) STABILIZED SUBBASE HOT-MIX ASPHALT, 4 1/2 "
- (11) STEEL PLATE BEAM GUARDRAIL, TY. A 6 FT POSTS
- (12) CONCRETE CURB, TYPE B
- (13) CONCRETE BARRIER, DOUBLE FACE, 42 IN. HEIGHT
- (14) PCC SHOULDERS 10 1/2"
- (15) BITUMINOUS MATERIALS (PRIME COAT)
- (16) REGRADING AND LANDSCAPING TOPSOIL EXCAVATION AND PLACE, 6" SEEDING, CLASS 2A
- (17) HMA SURFACE REMOVAL, 2 1/2 "
- (18) PAVED SHOULDER REMOVAL
- (19) PCC SHOULDERS 9"
- (D) DRILL AND GROUT NO. 6 TIE BARS AT 30" CTS (STAGGERED SIDE BY SIDE) INCLUDED IN COST OF CONCRETE BARRIER, DOUBLE FACE, 42 IN. HEIGHT

(27) LONGITUDINAL CONSTRUCTION JOINT. DRILL AND GROUT NO. 6 DEFORMED TIE BARS

10 1/2" OR 9")

(29) PIPE UNDERDRAINS 6"

24" LONG AT 24" C-C. (INCLUDED IN THE COST

OF POTLAND CEMENT CONCRETE SHOULDERS

(28) LONGITUDINAL SAWED OR CONSTRUCTION JOINT.

FOR LONGITUDINAL SAWED JOINT, POUR IN PLACE NO. 6 DEFORMED EPOXY TIE BARS 30" LONG AT

30" C-C. FOR LONGITUDINAL CONSTRUCTION JOINT.

DRILL AND GROUT NO. 6 DEFORMD EPOXY TIE BARS

24" LONG AT 24" C-C. INCLUDED IN COST OF PORTLAND

CEMENT CONCRETE PAVEMENT 10 1/2" OR 9" (JOINTED)

- (21) CONCRETE BARRIER, VARIABLE CROSS-SECTION, 42" HEIGHT
- (22) LEVELING BINDER (MACHINE METHOD), N70
- 23 HMA SURFACE REMOVAL, VARIABLE DEPTH
- (24) COMBINATION CONCRETE CURB AND GUTTER, B-6.24
- (25) EXCESS PAVEMENT REMOVAL
- (26) CONCRETE BARRIER BASE





EXISTING RAMP F2 STA 1206+40 TO STA 1209+58

LOOKING WEST/ NORTH

(1)

B

 \bigcirc

LOOKING NORTH





PROPOSED RAMP F2

STA 1206+40 TO STA 1209+58 LOOKING WEST/ NORTH



TO O" AT STA 309+48.53 EXISTING RAMP D STA 306+53.80 TO STA 309+48.53





LOOKING SOUTH







●						
FILE NAME =	USER NAME = default	DESIGNED - RTF	REVISED -			TYPICAL SECTIONS
\$FILEL\$		DRAWN - RTF	REVISED -	STATE OF ILLINOIS		DAMDE
	PLOT SCALE = \$SCALE\$	CHECKED - RR	REVISED -	DEPARTMENT OF TRANSPORTATION		RAIWF5
	PLOT DATE = 3/29/2013	DATE - 03/29/2013	REVISED -		SCALE: N/A	SHEET NO. 7 OF 7 SHEETS

 \bigcirc



LOOKING SOUTH