

Stage removal line

1'-10'2'

Stage construction line -

NOTES


Detail I - With Bar Splicer or Couplers: Connect one (1) I'' x 7' 'x ''W'' steel P to the top layer of couplers with $2^{-5}8'' \phi$ bolts screwed to coupler at approximate © of each barrier panel.

Detail II - With Extended Reinforcement Bars:

Connect one (I) I'' x 7" x "W" steel P to the concrete slab or concrete wearing surface with 2- 58 " ϕ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate © of each barrier panel.

Cost of anchorage is included with Temporary Concrete Barrier. The 1" x 7" x "W" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.

- *** Dimension shown is minimum required embedment into concrete. If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.
- **** If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.



→Stage removal line

"W" Top bars – Detail I spacing - Detail II $-Q 7_8'' \phi Holes$ *£ 1" x 1½" Notch

STEEL RETAINER P 1" x 7" x "W"

* Required only with Detail II

COUNTY

COOK 631 499

** Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

"W" = Top bars spacing + 4"

R-27

7-1-10

BOWMAN, BARRETT & ASSOCIATES INC. CONSULTING ENGINEERS Chicago, Illinois 312.228.0100 www.bbandain.com	

1	USER NAME =	DESIGNED - TL	REVISED -
l		CHECKED - BAK	REVISED -
l	PLOT SCALE =	DRAWN - TL	REVISED -
1	PLOT DATE = 03/29/2013	CHECKED - BAK	REVISED -

**Wood blocks

Top Layer Splicer

DETAIL I

2-58" \$ Bolts

with washers