
	CONFLICTING PAVEMENT MARKING REMOVAL	WHITE REI MARKING	FLECTORIZED TAPE				
		WEDIAN MARKING T	FLECTORIZED APE 1. CONES DAY O ARE B HEIGHI 2. STEAD OPERA 3. REFLEC THE B THAN				
			4. THIS A AND T LANE" 5. THESE				
		LEGEND	6.LONGI				
		WORK AREA	7.FORM 8.IF A [NCHRP THE B				
		LANE OPEN TO TRAFFIC	9. TRAFF SHALL ITEMS.				
		TYPE I OR II BARRICADE WITH STEADY BURN LIGHT					
	\mathbf{O}	DRUM WITH STEADY BURN LIGHT					
		DRUM WITH SIGN (WITH OPTIONAL FLASH) LIGHT) SEE DETAIL	NG				
	н	TYPE I OR II CHECK BARRICADE WITH FL	ASHING LIGH				
STATE OF I	LLINOIS	TRAFFIC CONTROL AN	D PROTECTION				

FILE NAME =	USER NAME = midyja	REVISED -T. RAMMACHER 09-08-94 REVISED - R. BORO 09-14-09		т	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.
c:\pw_work\pwidot\midyja\d0267284\DistS	td.dgn	REVISED - A. HOUSEH 11-07-95 REVISED -	STATE OF ILLINOIS			2845	3160A-RS&N	СООК	27 23
	PLOT SCALE = 100.0000 ' / in.	REVISED - A. HOUSEH 10-12-96 REVISED -	DEPARTMENT OF TRANSPORTATION	(TO REMAIN OPEN TO TRAFFIC)			TC-14	CONTRACT	NO. 60T99
	PLOT DATE = 3/27/2013	REVISED -T. RAMMACHER 01-06-00 REVISED -		SCALE: NONE	SHEET NO. 1 OF 1 SHEETS STA. TO STA.	FED. ROAD	D DIST. NO. 1 ILLINOIS FED. A	ID PROJECT	



ED PAV'T

ZED PAV'T

GENERAL NOTES

ES MAY BE SUBSTITUTED FOR BARRICADES OR DRUMS AT HALF THE SPACING DURING DEPENDING USED, THE "LEFT TURN LANE" SIGN MAY BE SKID MOUNTED AT A MINIMUM HT OF 5' (1.5 m).

ADY BURNING LIGHTS WILL NOT BE REQUIRED ON BARRICADES OR DRUMS FOR DAY RATIONS. ALL LIGHTS SHALL BE MONODIRECTIONAL.

LECTORIZED TEMPORARY PAVEMENT MARKING TAPE SHALL BE PLACED THROUGHOUT BARRICADED AREA OF EACH TURN BAY WHERE THE CLOSURE TIME IS GREATER N FOURTEEN DAYS.

APPLICATION ALSO APPLIES WHEN WORK IS BEING PERFORMED IN THE RIGHT LANE(S) THE RIGHT TURN BAY IS TO REMAIN OPEN. UNDER THIS CONDITION, "RIGHT TURN " R3-100 24 × 24 (600 × 600) AND M6-2R 21 × 15 (530 × 380) SHALL BE USED.

SE CONTROLS SHALL SUPPLEMENT MAINLINE TRAFFIC CONTROL FOR LANE CLOSURES.

ITUDINAL DIMENSIONS MAY BE ADJUSTED TO FIT FIELD CONDITIONS.

OPER 725 IS REQUIRED.

DRUM OR TYPE II BARRICADE WITH AN ATTACHED SIGN PANEL WHICH MEETS RP 350 REQUIREMENTS IS NOT AVAILABLE, THE SIGNS SHALL BE MOUNTED, ABOVE BARRICADES, ON SEPARATE SIGNS SUPPORTS THAT MEET NCHR 350 PREQUIREMENTS.

FFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) LL BE INCLUDED IN THE COST SPECIFIED TRAFFIC CONTROL STANDARDS OR 1S.

> All dimensions are in inches (millimeters) unless otherwise shown.

GHT