TRAFFIC SIGNAL LEGEND

								·	1.10.1.0		
ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET		\boxtimes		EMERGENCY VEHICLE LIGHT DETECTOR	\approx	\approx	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE		— <u>O</u> —	
AILROAD CONTROL CABINET			▶◀	CONFIRMATION BEACON	Ro–(I	o()	⊷ 1	GOLVEL AND E		~	
OMMUNICATIONS CABINET	(CC)	<u> </u>	cc	HANDHOLE	R 🖂	2	N	COAXIAL CABLE		<u> </u>	<u> </u>
ASTER CONTROLLER		EMC	MC	HEAVY DUTY HANDIOLE	R.	H	F	VENDOR CABLE FOR CAMERA		- -	(V)
MASTER MASTER CONTROLLER	R WPS	EMMC]	MMC UPS	HEAVY DUTY HANDHOLE	R N	<u>=</u>		COPPER INTERCONNECT CABLE.		,	•
ININTERRUPTIBLE POWER SUPPLY			[n-3]	DOUBLE HANDHOLE JUNCTION BOX	R (D)		<u> </u>	NO. 18 3 PAIR TWISTED, SHIELDED		<u> </u>	
ERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	-D-3	-D-	- 	GALVANIZED STEEL CONDUIT				FIBER OPTIC CABLE NO. 62.5/125. WM12F		<u>—(12F</u>)—	
ELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	R	P	P II	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	_≒			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F			(24F)
TEEL MAST ARM ASSEMBLY AND POLE	RO	O	•	AND CABLE				FIBER OPTIC CABLE NO. 62.5/125.			
LUMINUM MAST ARM ASSEMBLY AND POLE	R CI	<u> </u>		COMMON TRENCH			CT	(NUMBER OF FIBERS & TYPE TO BE		-	-
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH LUMINAIRE	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	○ 	●-*	COLLABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	CNC S	GROUND ROD AT (C) CONTROLLER,		°	^C il⊷
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH PTZ CAMERA	r rep	P173	₽TZ I	INTERSECTION ITEM		Ī	ΙP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		11 •	1
IGNAL POST	_	0	_	REMOVE ITEM	R			CONTROLLER CABINET AND	ROF		
EMPORARY WOOD POLE (CLASS 5 OR	^{P.} ○	8	∞	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
ETTER) 45 FOOT (13.7m) MINIMUM UY WIRE	⊗ > <u>*</u>	>	>	ABANDON ITEM 12" (300mm) TRAFFIC SIGNAL SECTION	Α	R	R	STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O.RMF		
	R		•	12 (SOURH) TRAFFIC STONAL SECTION			[7]	ALUMINUM MAST ARM POLE AND	RMF		
GNAL HEAD	- (>			12" (300mm) RED WITH 8" (200mm)		R		FOUNDATION TO BE REMOVED	U		
GNAL HEAD CONSTRUCTION STAGES JMBERS INDICATE THE CONSTRUCTION STAGE)	p		→ ²	YELLOW AND GREEN TRAFFIC SIGNAL FACE		A E	В	STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	RMF O-X 		
GNAL HEAD WITH BACKPLATE	+>	+6>	+-				Y				
GNAL HEAD OPTICALLY PROGRAMMED	- ° 'P"		ripu	SIGNAL FACE			G ∢ Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
ASHER INSTALLATION DENOTES SOLAR POWER)	R ○-▷>'F''	O-₹>>,,t:,,,	•="F"				← G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[IS]	IS
EDESTRIAN SIGNAL HEAD	7	[]					R	SAMPLING (SYSTEM) DETECTOR		[5]	S
EDESTRIAN PUSHBUTTON DETECTOR	R (6)	6	©	SIGNAL FACE WITH BACKPLATE. """ INDICATES PROGRAMMED HEAD		Ş	G ◆Y	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR	[P]	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	® APS	@APS	APS			(* Y) (* G) (* P)	4 C	EXISTING PREFORMED INTERSECTION LOOP DETECTOR		o — a	
LUMINATED SIGN	⊼€ SJ	R.S.				10 D11	"P"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR	PP:	
NO LEFT TURN"	⑤	Ø.	•	12" (300mm) PEDESTRIAN SIGNAL HEAD		(M) (M)		PREFORMED INTERSECTION AND SAMPLING		PIS	PIS
LUMINATED SIGN NO RIGHT TURN"	R S		®	WAŁK/DON'T WALK SYMBOL 12" (300mm) PEDESTRIAN SIGNAL HEAD		<u></u>		(SYSTEM) DETECTOR		dū	
ETECTOR LOOP, TYPE I		1		INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
Elector Eggi, . He i		·	••	12" (300mm) PEDESTRIAN SIGNAL HEAD			•	DAUBOAD	01/8/800		
REFORMED DETECTOR LOOP		\$ \$ \$ \$	Р	INTERNATIONAL SYMBOL, SOLID		F	¥	RAILROAD	2 A IMRO	L5	
ICROWAVE VEHICLE SENSOR	R (M)√J	(M)	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL. WITH COUNTDOWN TIMER		P C (5) D	₽ C			EXISTING	PROPOSED
IDEO DETECTION CAMERA		(V)1	(V) ■	RADIO INTERCONNECT	-H+F-O		- \$ - - \$ - - - - - - - - -	RAILROAD CONTROL CABINET			▶◀
DEO DETECTION ZONE					11.		."	RAILROAD CANTILEVER MAST ARM	¥		X eX X X
	Ŕ			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL	22		
AN, TILT, ZOOM CAMERA	शिद्री	(*************************************	PIZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		(5)				20 2	X ⊕ X
IRELESS DETECTOR SENSOR	RW	(W)	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED)		CROSSING GATE		X0X =-	X0 X-
IRELESS ACCESS POINT	R.			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)			(1)	CROSSBUCK		> <u></u> <	*
NAME = USER NAME = bound)		IGNED - DAG/BCK	REVISED -		OF 111151616			DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY TOTAL SHEETS
*_work\PW[007\84UERDL\d0]00315\ts25 dgn PLO7 SCALE = 50,0000 '/ jn	DRA	WN - BCK CKED - DAD	REVISED -	STATE DEPARTMENT	OF ILLINOIS			STANDARD TRAFFIC SIGNAL DESIGN DETAILS	363	10-00404-00-CH	KANE 59