## GENERAL NOTES

- Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
- 2. Reinforcement bars designated (E) shall be epoxy coated.
- 3. Bars noted thus, 3 x 2-#5 indicates 3 lines of bars with 2 lengths of bars per line.
- 4. All structural steel shall conform to AASHTO Classification M-270 Gr 36 (Spans 1 thru 6, 10 and 11) and Gr 50 (Spans 7 thru 9), unless otherwise noted.
- 5. All exposed concrete edges shall have a  $\frac{3}{4}$ " x 45° chamfer, except where shown otherwise.
- 6. If the analysis submitted to the Contractor for the jacking/temporary support system to be used shows temporary stiffeners are required to prevent web crippling or buckling, the stiffeners shall be steel and bolted to the web. If stiffeners are not required, hardwood timbers shall be installed tightly between the top and bottom flange to prevent flange rotation.
- 7. The Contractor shall take all necessary precautions for the protection of passing vehicles from falling objects and/or materials until completion of the work.
- 8. Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by method that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.
- 9. The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.
- 10. Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
- 11. Areas of deck repairs shown are estimated. The Engineer shall show actual locations of deck repairs on As-built Plans.
- 12. Joint openings shall be adjusted according to Article 520.04 of the Std. Specs. when the deck is poured at an ambient temperature other than 50 °F.
- 13. The Inorganic Zinc Rich Primer / Acrylic / Acrylic Paint System shall be used for shop and field painting of new structural steel except where otherwise noted. The color of the final finish coat for all interior steel surfaces shall be gray, Munsell No. 5B 7/1. The color of the final finish coat for the exterior and bottom flange of the fascia beams shall be interstate green.

## INDEX OF SHEETS

- SO1. General Plan and Elevation
- SO2. General Notes, Index of Sheets & Total Bill of Material
- SO3. Preliminary Stage & Stage I Construction
- S04. Stage II Construction & Final Deck Cross Section
- S05. Temporary Concrete Barrier S06. Bridge Deck Repair Plan (Sp
- SO6. Bridge Deck Repair Plan (Spans 1 thru 6) SO7. Bridge Deck Repair Plan (Spans 7 thru 11)
- SO8. Bridge Deck Final Cross Sections
- SO9. North Abutment Joint Removal and Replacement
- S10. South Abutment Joint Removal and Replacement
- S11. Pier 6 Joint Removal and Replacement
- S12. Pier 9 Joint Removal and Replacement
- S13. Preformed Joint Strip Seal
- S14. Drainage Plan & Details
- S15. Framing Plan
- SIG. Structural Steel Repair Sections & Details (Sheet I of II)
- S17. Structural Steel Repair Sections & Details (Sheet II of II)
- S18. Type I Elastomeric and Fixed Bearings Details
- S19. Type II Elastomeric Bearings Details
- S20. Type III Elastomeric Bearings Details
- S21. North Abutment Repairs
- S22. South Abutment Repairs
- S23. Pier 6 Repairs
- S24. Pier 8 Repairs
- S25. Pier 9 Repairs
- S26. Bar Splicer Assembly Details

TOTAL BILL OF MATERIAL									
ІТЕМ	UNIT	SUPER	SUB	TOTAL					
Concrete Removal	Cu. Yd.	23.0	-	23.0					
Floor Drains	Each	116	-	116					
Concrete Superstructure	Cu. Yd.	27.1	-	27.1					
Bridge Deck Grooving	Sq. Yd.	4,382	-	4,382					
Protective Coat	Sq. Yd.	915	-	915					
Furnishing and Erecting Structural Steel	Pound	9,830	-	9,830					
Cleaning and Painting Structural Steel, Location 1	L Sum	1	-	1					
Reinforcement Bars, Epoxy Coated	Pound	4,414	-	4,414					
Bar Splicers	Each	68	-	68					
Preformed Joint Strip Seal	Foot	189	-	189					
Elastomeric Bearing Assembly, Type I	Each	6	-	6					
Elastomeric Bearing Assembly, Type II	Each	18	-	18					
Elastomeric Bearing Assembly, Type III	Each	6	-	6					
Anchor Bolts, 1"	Each	-	72	72					
Anchor Bolts, 1 <sup>1</sup> 4"	Each	-	48	48					
Anchor Bolts, 1 <sup>1</sup> 2"	Each	-	24	24					
Concrete Sealer	Sq. Ft.	-	2,940	2,940					
Epoxy Crack Injection	Foot	-	49	49					
Jack and Remove Existing Bearings	Each	11	-	11					
Structural Steel Removal	Pound	9,170	-	9,170					
Structural Steel Repair	Pound	12,330	-	12,330					
Removal of Existing Bearings	Each	25	-	25					
Bridge Deck Latex Concrete Overlay, 2 <sup>1</sup> 4 Inches	Sq. Yd.	4,533	-	4,533					
Containment and Disposal of Lead Paint Cleaning Residues	L Sum	1	-	1					
Cleaning Bridge Seats	Sq. Ft.	-	532	5 <i>32</i>					
Bridge Deck Scarification, $\frac{3}{4}$ "	Sq. Yd.	4,533	-	4,533					
Structural Repair of Concrete (Depth Equal to or Less Than 5 Inches)	Sq. Ft.	-	459	459					
Structural Repair of Concrete (Depth Greater Than 5 Inches)	Sq. Ft.	23	60	83					
Plug Existing Deck Drains	Each	68	-	68					
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	51	-	51					
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	165	-	<i>1</i> 65					
Temporary Shoring and Cribbing	Each	-	25	25					



<u>SECTION THRU</u> EXISTING STONE RIPWRAP SLOPEWALL

(For information only, taken from existing plans)

HBM 4415 WEST HARRISON ST.		DESIGNED - LAK, MI CHECKED - MI	REVISED - REVISED -	STATE OF ILLINOIS	GENERAL NOTES, INDEX OF SHEETS &
CONSULTING & DESIGN HILL SIDE, IL GUIGZ INSPECTION & RATING PHONE: (708) 236-0900 DESEARCH & TESTING FAX: (708) 236-0901		DRAWN - LAK, JJS	REVISED -	DEPARTMENT OF TRANSPORTATION	EB US RUUTE ZU UVER PECATUNICA RI
	DATE - 03/13/2013	CHECKED - MAI, MI	REVISED -		SHEET NO. SO2 OF S20

& TOTAL BILL OF MATERIAL	F.A.P. RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
RIVER STRUCTURE NO. 089–0042		(177-4B-1)M	STEPHENSON	43	19
			CONTRACT	NO. 6	54J24
526 SHEETS	ILLINOIS FED. AID PROJECT				