

MAINLINE												
LOCATION STA. TO STA.	LENGTH	TEMP. PAVMT. MARKING LINE 6"	PVMT. MARKING REMOVAL	RAISED REFL PVMT MARKER REMOVAL	MIX FOR CRACKS, JOINTS, & FLANGEWAYS	FIBER MOD. ASH. CRACK SEALING	BITUMINOUS MATERIALS (PRIME COAT)	MICRO-SURFACING SINGLE PASS TYPE II MIX D	EPOXY PVMT. MARKING LINE 6"	RAISED REFLECTIVE PVMT. MARKER	WORK ZONE PVMT. MARKING REMOVAL	
	FT	FT	SQ FT	EACH	TON	FT	POUND	SQ YD	FT	EACH	SQ FT	
NORTHBOUND												
797+93	962+23.2	16430.2	4108	2055	411	10	16430	1643	3651	4108	411	2054
962+23.2	965+31.0	BRIDGE OMISSION							77			
965+31.0	1005+05.17	3974.1	994	495	99	3	3974	397	883	994	99	497
1005+05.17	1007+78.83	BRIDGE OMISSION							68			
1007+78.83	1167+53.53	15974.7	3994	1995	399	10	15975	1597	3550	3994	399	1997
SOUTHBOUND												
797+93	961+58.0	16365	4091	2045	409	10	16365	1637	3637	4091	409	2046
961+58.0	964+65.8	BRIDGE OMISSION							77			
964+65.8	1005+05.17	4039.37	1010	505	101	3	4039	404	898	1010	101	505
1005+05.17	1007+78.83	BRIDGE OMISSION							68			
1007+78.83	1167+53.53	15974.7	3994	1995	399	10	15975	1597	3550	3994	399	1997
TOTAL			18190	9090	1818	46	72758	7276	16168	18480	1818	9095