



NOTES:

SEE STANDARDS 701400 AND 701402 FOR DETAILS NOT SHOWN.

SEQUENCE OF OPERATIONS SN 054-0063, 0064

STAGE 2

1. REMOVE CONFLICTING PAVEMENT MARKINGS AND SHIFT TRAFFIC TO THE STAGE 2 LANES; PLACE TRAFFIC CONTROL ITEMS AS SHOWN ON THE STAGE 2 TRAFFIC CONTROL & PROTECTION DETAILS AND AS REQUIRED BY STANDARDS 701400 AND 701402.
2. REMOVE STAGE 2 PORTION OF EXISTING BRIDGE DECKS, SUPERSTRUCTURES, AND APPROACH SLABS.
3. CONSTRUCT STAGE 2 BRIDGE DECKS, SUPERSTRUCTURES, APPROACH PAVEMENTS, AND APPROACH CONNECTOR PAVEMENTS.
4. MILL BUTT JOINTS AND PLACE HMA SURFACE COURSE AND HMA SHOULDERS.
5. REMOVE AND REERECT GUARDRAIL AND TERMINALS.
6. REMOVE TRAFFIC CONTROL DEVICES AND TEMPORARY PAVEMENT MARKINGS; INSTALL SHORT TERM PAVEMENT MARKINGS, AND OPEN ALL LANES TO TRAFFIC.

LEGEND

- ↑ ARROW BOARD
- ⊥ SIGN
- ⬆ DIRECTION INDICATOR BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
- ⬇ TYPE II BARRICADE, DRUM, OR VERTICAL BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
- DRUMS
- ▬ IMPACT ATTENUATORS, TEMPORARY (FULLY REDIRECTIVE, NARROW) TEST LEVEL 3
- ▶ MONODIRECTIONAL BARRIER WALL / GUARDRAIL MARKER AT 25' CTRS.
- ▨ HMA SURFACE REMOVAL BUTT JOINT
- ▧ PAVED SHOULDER REMOVAL
- ▩ APPROACH SLAB REMOVAL
- ▤ PAVEMENT REMOVAL

