

PAVING SCHEDULE			LENGTH	PAVEMENT WIDTH	SHOULDER WIDTH	AREA	EXCAVATING AND GRADING EXISTING SHOULDER	AGGREGATE WEDGE SHOULDER, TYPE B	BITUMINOUS MATERIALS (PRIME COAT)	AGGREGATE (PRIME COAT)	HOT-MIX ASPHALT SURFACE REMOVAL (BUTT-JOINT)	HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"	HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH)	LEVELING BINDER (MACHINE METHOD), N70	LEVELING BINDER (MACHINE METHOD), N90	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90	INCIDENTAL HOT-MIX ASPHALT SURFACING	HOT-MIX ASPHALT SHOULDERS, 8"
STATION	TO	STATION	FEET	FEET	FEET	SQ YD	UNIT	TON	GALLON	TON	SQ. YD.	SQ. YD.	SQ. YD.	TON	TON	TON	TON	TON	TON
60+78.94	TO	66+57.49	578.6	Variable	10.0	2,026.7	0.0	16.6	262.5	5.2	0.0	2624.5	0.0	0.0	110.2	0.0	220.5	0.0	0.0
66+57.49	TO	68+50.66	193.2	24.0	6.0	515.1	3.9	11.0	51.5	1.0	0.0	515.1	0.0	0.0	21.6	0.0	47.8	0.0	0.0
68+50.66 BK	=	69+51.16 AH	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
69+51.16	TO	91+89.55	2,238.4	24.0	6.0	5,969.0	37.3	84.8	596.9	11.9	0.0	5969.0	0.0	0.0	250.7	0.0	553.6	0.0	0.0
91+89.55	TO	104+17.17	1,227.6	27.0	3.0	3,682.9	8.6	35.0	409.2	8.2	0.0	4092.1	0.0	0.0	171.9	0.0	372.3	0.0	409.2
104+17.17 BK	=	104+64.50 AH	0.0	0.0	3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
104+64.50	TO	106+77.87	213.4	24.0	3.0	569.0	1.4	6.1	64.0	1.3	0.0	640.1	0.0	0.0	26.9	0.0	58.7	0.0	71.1
106+77.87	TO	109+49.00	271.1	24.0	6.0	723.0	2.1	2.5	72.3	1.4	0.0	723.0	0.0	0.0	30.4	0.0	67.1	0.0	0.0
109+49.00	TO	113+93.00	444.0	Variable	6.0	1,233.3	8.2	21.0	123.3	2.5	0.0	1233.3	0.0	0.0	51.8	0.0	113.9	0.0	0.0
113+93.00	TO	120+00.00	607.0	38.0	6.0	2,562.9	7.0	5.3	256.3	5.1	0.0	2562.9	0.0	0.0	107.6	0.0	229.4	0.0	0.0
120+00.00	TO	123+52.00	352.0	Variable	6.0	977.8	7.0	20.0	97.8	2.0	0.0	977.8	0.0	0.0	41.1	0.0	90.3	0.0	0.0
123+52.00	TO	123+87.00	35.0	24.0	6.0	93.3	0.7	2.0	9.3	0.2	0.0	0.0	93.3	3.9	0.0	0.0	8.7	0.0	0.0
123+87.00	TO	143+26.80	1,939.8	24.0	6.0	5,172.8	34.6	91.3	517.3	10.3	0.0	0.0	5172.8	217.3	0.0	479.7	0.0	23.8	0.0
143+26.80	TO	165+88.00	2,261.2	24.0	6.0	6,029.9	41.0	109.6	603.0	12.1	0.0	0.0	6029.9	253.3	0.0	559.2	0.0	0.0	0.0
165+88.00	TO	166+91.00	103.0	24.0	6.0	274.7	0.0	5.9	37.8	0.8	0.0	0.0	378.5	15.9	0.0	34.2	0.0	0.0	0.0
166+91.00	TO	167+26.00	35.0	24.0	0.0	93.3	0.0	0.0	15.6	0.3	155.6	0.0	0.0	6.5	0.0	13.9	0.0	0.0	0.0
167+26.00	TO	169+26.00	200.0	24.0	0.0	533.3	0.0	0.0	53.3	1.1	0.0	0.0	533.3	22.4	0.0	0.0	0.0	0.0	0.0
169+26.00	TO	169+61.00	35.0	24.0	0.0	93.3	0.0	0.0	15.6	0.3	155.6	0.0	0.0	6.5	0.0	13.9	0.0	0.0	0.0
169+61.00	TO	170+71.00	110.0	24.0	6.0	293.3	0.0	6.3	40.3	0.8	0.0	0.0	403.3	16.9	0.0	36.4	0.0	0.0	0.0
170+71.00	TO	228+39.00	5,768.0	24.0	6.0	15,381.3	113.4	319.1	1,538.1	30.8	0.0	0.0	15381.3	646.0	0.0	1,426.4	0.0	9.2	0.0
228+39.00	TO	229+16.00	77.0	24.0	6.0	205.3	0.8	4.4	25.7	0.5	0.0	0.0	257.3	10.8	0.0	23.4	0.0	0.0	0.0
229+16.00	TO	230+49.00	133.0	24.0	4.0	354.7	0.0	5.0	60.3	1.2	0.0	0.0	603.2	25.3	0.0	53.8	0.0	0.0	0.0
230+49.00	TO	230+84.00	35.0	24.0	0.0	93.3	0.0	0.0	16.3	0.3	163.3	0.0	0.0	6.9	0.0	14.5	0.0	0.0	0.0
230+84.00	TO	232+23.00	139.0	24.0	0.0	370.7	0.0	0.0	37.1	0.7	0.0	0.0	370.7	15.6	0.0	0.0	0.0	0.0	0.0
232+23.00	TO	232+58.00	35.0	24.0	0.0	93.3	0.0	0.0	16.3	0.3	163.3	0.0	0.0	6.9	0.0	14.5	0.0	0.0	0.0
232+58.00	TO	233+97.00	139.0	24.0	4.0	370.7	0.0	5.3	62.4	1.2	0.0	0.0	623.7	26.2	0.0	55.6	0.0	0.0	0.0
233+97.00	TO	235+09.00	112.0	24.0	6.0	298.7	1.1	6.4	38.6	0.8	0.0	0.0	385.7	16.2	0.0	35.0	0.0	0.0	0.0
235+09.00	TO	249+71.00	1,462.0	24.0	6.0	3,898.7	29.0	75.3	389.9	7.8	0.0	0.0	3898.7	163.7	0.0	361.6	0.0	7.6	0.0
249+71.00	TO	272+44.00	2,273.0	24.0	6.0	6,061.3	45.2	129.4	606.1	12.1	0.0	0.0	6061.3	254.6	0.0	562.1	0.0	0.0	0.0
272+44.00	TO	272+79.00	35.0	24.0	6.0	93.3	0.7	2.0	9.3	0.2	0.0	0.0	93.3	3.9	0.0	8.7	0.0	0.0	0.0
272+79.00	TO	273+41.00	62.0	24.0	6.0	165.3	1.2	3.5	16.5	0.3	0.0	165.3	0.0	6.9	0.0	15.3	0.0	0.0	0.0
273+41.00	TO	273+76.00	35.0	24.0	6.0	93.3	0.7	2.0	9.3	0.2	0.0	0.0	93.3	3.9	0.0	8.7	0.0	0.0	0.0
273+76.00	TO	295+45.05	2,169.1	24.0	6.0	5,784.1	42.1	116.3	578.4	11.6	0.0	0.0	5784.1	242.9	0.0	536.4	0.0	7.9	0.0
295+45.05	TO	295+80.05	35.0	24.0	6.0	93.3	0.7	2.0	9.3	0.2	0.0	0.0	93.3	3.9	0.0	8.7	0.0	0.0	0.0
295+80.05	TO	296+20.10	40.0	24.0	6.0	106.8	0.8	2.3	10.7	0.2	0.0	106.8	0.0	4.5	0.0	9.9	0.0	0.0	0.0
SHEET TOTALS			17,282			64,308	387	1,090	6,650	133	638	19,610	46,257	1,981	812	4,272	1,762	49	480

FILE NAME =	USER NAME = \$USER\$	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	SCHEDULE OF QUANTITIES				F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
\$FILEL\$		DRAWN -	REVISED -		SCALE: NA	SHEET NO. 1 OF 7 SHEETS	STA.	TO STA.	116	(124,125,126)RS-3	RICHLAND	60	14
		CHECKED -	REVISED -						CONTRACT NO. 74409				
		DATE -	REVISED -						ILLINOIS FED. AID PROJECT				