

POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, STONE MATRIX ASPHALT, N80

LOCATION	TON
I-55	
SB STA. 519+00 TO STA. 521+50	74.7
NB STA. 519+00 TO STA. 521+50	74.7
SB STA. 546+00 TO STA. 553+50	224
NB STA. 547+50 TO STA. 555+00	224
SB STA. 640+00 TO STA. 648+00	253.9
NB STA. 640+00 TO STA. 649+00	268.8
IL 4 RAMP	
RAMP 1 STA. 100+27 TO STA. 101+37	73.0
STA. 101+37 TO STA. 113+06	232.8
STA. 113+06 TO STA. 115+28	41.4
STA. 115+28 TO STA. 124+60	121.8
RAMP 2 STA. 200+00 TO STA. 205+33	102.8
STA. 205+33 TO STA. 212+92	151.1
RAMP 3 STA. 300+26 TO STA. 301+27	68.0
STA. 301+27 TO STA. 312+80	229.6
STA. 312+80 TO STA. 315+03	41.6
STA. 315+03 TO STA. 324+50	123.7
RAMP 4 STA. 400+13 TO STA. 405+32	100.1
STA. 405+32 TO STA. 412+60	145.0
TOTAL =	2,551

BRIDGE APPROACH PAVEMENT CONNECTOR (FLEXIBLE)

LOCATION	SO. YD.
SB RT. STA. 546+00 TO RT. STA. 546+06	16
NB LT. STA. 547+50 TO LT. STA. 547+56	16
SB RT. STA. 553+44 TO RT. STA. 553+50	16
NB LT. STA. 554+94 TO LT. STA. 555+00	16
SB RT. STA. 640+00 TO RT. STA. 640+06	16
NB LT. STA. 640+00 TO LT. STA. 640+06	16
SB RT. STA. 648+44 TO RT. STA. 648+50	16
NB LT. STA. 648+94 TO LT. STA. 649+00	16
TOTAL =	128

CONTINUOUSLY REINFORCED PORTLAND CEMENT CONCRETE PAVEMENT 12" PAVEMENT REINFORCEMENT SUBGRADE REINFORCEMENT

LOCATION	CRPCC (SO. YD.)	PAVEMENT REIN. (SO. YD.)	SUBGRADE REIN. (SO. YD.)
IL 4			
SB RT. STA. 546+00 TO RT. STA. 553+50	2,000	2,000	2,000
NB LT. STA. 547+50 TO LT. STA. 555+00	2,000	2,000	2,000
CHURCH RD			
SB RT. STA. 640+00 TO RT. STA. 648+50	2,267	2,267	2,267
NB LT. STA. 640+00 TO LT. STA. 649+00	2,400	2,400	2,400
TOTAL =	8,667	8,667	8,667

MEDIAN REMOVAL COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.06 COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.24 CONCRETE MEDIAN SURFACE, 4 INCH PRISMATIC CURB REFLECTOR

LOCATION	MEDIAN REMOVAL (SQ. FT.)	CC&G M-6.06 (FOOT)	CC&G M-6.24 (FOOT)	CONC. MED. SURF., 4" (SQ. FT.)	CURB REFLECTOR (EACH)
IL 4 RAMP					
RAMP 2					
RT. STA. 214+10	174	10	14	94	8
RAMP 4					
RT. STA. 413+75	436	22	32	264	10
TOTAL =	610	32	46	358	18

CONCRETE STRUCTURES REINFORCEMENT BARS, EPOXY COATED BAR SPLICERS

LOCATION	CONCRETE (CU. YD.)	REIN. BARS (POUND)	SPLICERS (EACH)
SB RT. STA. 546+03 TO RT. STA. 546+09	4.5	766.25	24
NB LT. STA. 547+53 TO LT. STA. 547+59	4.5	766.25	24
SB RT. STA. 553+41 TO RT. STA. 553+47	4.5	766.25	24
NB LT. STA. 554+91 TO LT. STA. 554+97	4.5	766.25	24
SB RT. STA. 640+03 TO RT. STA. 640+09	4.5	766.25	24
NB LT. STA. 640+03 TO LT. STA. 640+09	4.5	766.25	24
SB RT. STA. 648+41 TO RT. STA. 648+47	4.5	766.25	24
NB LT. STA. 648+91 TO LT. STA. 648+97	4.5	766.25	24
TOTAL =	36.0	6,130	192

PORTLAND CEMENT CONCRETE PAVEMENT 10" PROTECTIVE COAT HOT-MIX ASPHALT SHOULDERS, 8"

LOCATION	PCC PAVEMENT 10" (SQ. YD.)	PROT. COAT (SQ. YD.)	HMA SHOULDERS 8" (SQ. YD.)
IL 4 RAMP			
RAMP 2			
STA. 212+95.14 TO STA. 214+27.87	567	567	62
RAMP 4			
STA. 412+60.17 TO STA. 413+95.25	570	570	60
TOTAL =	1,137	1,137	122



△ REVISED 6-6-13