

CONTRACT NO. 64D04			
F.A. RTE.	SECTION	COUNTY	TOTAL SHEET NO.
			9 2
STA.		TO STA.	
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	

GENERAL NOTES

The final top 100 mm (four inches) of soil in any right-of-way area disturbed by the Contractor must be capable of supporting vegetation. The soil must be from the A horizon (zero to 2' deep) of soil profiles of local soils.

The Contractor shall seed all disturbed areas within the project limits. Seeding Class 4 or 2A shall be used, except in front of properties where the grass will be mowed, then use Seeding, Class 1. Class 2A shall be used on front slopes and ditch bottoms. Class 4 shall be used behind Type A gutter, on all backslopes and areas behind the backslope, and beyond the toe of front slope on fill sections without ditches. This work will be included in the contract unit price per Lump Sum for PAVEMENT JACKING.

Mulch Method II shall be applied over all seeded areas. This shall be included in the cost of the PAVEMENT JACKING.

INDEX OF SHEETS

1. Cover Sheet
2. General Notes, Index of Sheets, Standards
3. Summary of Quantities
4. Existing Typical Sections - IL 76
5. Existing Typical Sections - I-39
6. Plan and Profile - IL 76
7. Plan & Profile - I-39
8. - 9. Bridge Approach Pavement Details - IL 76

STANDARDS

- 701006-02 Off-Road Operations, 2L, 2W, 4.5 m (15') to 600 mm (24*) From Pavement Edge
- 701201-02 Lane Closure, 2L, 2W, Day Only, for Speeds > 45 MPH
- 701301-02 Lane Closure, 2L, 2W, Short Time Operations
- 701400-02 Approach to Lane Closure, Freeway/Expressway
- 701406-04 Lane Closure, Freeway/Expressway, Day Operations Only
- 702001-06 Traffic Control Devices