

F.A.S. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
2701	0101T	EFFINGHAM	7	2
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

GENERAL NOTES

THIS SECTION SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE PLANS, THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", ADOPTED JANUARY 1, 2007; THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS" INDICATED ON THE CHECK SHEET, AND "THE SPECIAL PROVISIONS" INCLUDED IN THE PROPOSAL.

THE WORK INCLUDED IN THIS SECTION CONSISTS OF REMOVAL OF APPROXIMATELY 840 LINEAL FEET OF STORM SEWER AND INSTALLATION OF 964 LINEAL FEET OF STORM SEWER AND ANY OTHER WORK NECESSARY TO COMPLETE THIS SECTION.

EXCAVATION THROUGH SIDEROADS SHALL BE INCLUDED IN THE COST OF THE STORM SEWER.

ANY CURB AND GUTTER, PAVEMENT OR SHOULDERS THAT ARE DAMAGED WHILE REMOVING AND INSTALLING STORM SEWER AND DRAINAGE STRUCTURES, SHALL BE RECONSTRUCTED AS DIRECTED BY THE ENGINEER. THIS WORK SHALL BE INCLUDED WITH THE COST OF THE STORM SEWER.

ANY FIELD TILES OR OTHER UNKNOWN SUB-SURFACE DRAINAGE STRUCTURES THAT ARE DAMAGED DURING THE INSTALLATION OF THE STORM SEWER SHALL BE REPAIRED AS DIRECTED BY THE ENGINEER. THIS WORK SHALL BE PAID FOR AS PER ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS.

CONSTRUCTION AT ENTRANCES SHALL BE COORDINATED IN ORDER TO MAINTAIN ACCESS AT ALL TIMES.

THE MATERIAL USED FOR AGGREGATE SURFACE COURSE, TYPE B SHALL BE CRUSHED STONE OR CRUSHED CONCRETE.

ALL AREAS DISTURBED DURING CONSTRUCTION SHALL BE SEEDED WITH CLASS 2 SEEDING ACCORDING TO SECTION 250 OF THE STANDARD SPECIFICATIONS AND THE SPECIAL PROVISIONS. THE COST SHALL BE INCLUDED IN THE COST OF THE STORM SEWER.

THE CONTRACTOR SHALL PROVIDE INTERNET ACCESS TO THE BITUMINOUS PLANT QUALITY CONTROL LAB SO THAT BITUMINOUS PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK SHALL BE INCLUDED IN THE COST OF THE BITUMINOUS ITEM.

THE LOCATIONS AND /OR DPETHS OF UNDERGROUND UTILITIES SHOWN HAVE BEEN TAKEN FROM INFORMATION FURNISHED BY THE UTILITY OWNERS AND MUST BE CONSIDERED APPROXIMATE. FIELD MARKINGS OF FACILITIES IN CRITICAL AREAS MAY BE OBTAINED BY PROVIDING A MINIMUM OF 96 HOURS ADVANCE NOTICE THROUGH THE J.U.L.I.E. SYSTEM BY CALLING 800-892-0123.

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

MIXTURE USE(S): INCIDENTAL BITUMINOUS SURFACE (DRIVEWAYS)
 AC/PG: PG 64-22
 RAP% (MAX): 15% MAX.
 DESIGN AIR VOIDS: 4.0% @ NDESIGN = 50
 MIXTURE COMPOSITION: 1L-9.5
 (GRADATION MIXTURE)
 FRICTION AGGREGATE: MIXTURE C

FACTOR: 112 LB/IN/50 YD

INDEX OF SHEETS

SHEET NO.	TITLE
1	COVER SHEET
2	GENERAL NOTES, INDEX OF SHEETS & LISTS OF STANDARDS & BENCHMARK INFORMATION
3	SUMMARY OF QUANTITIES
4	SCHEDULE
5-6	PLAN AND PROFILE SHEETS
7	STORM SEWER OVERVIEW

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED AFTER SHEET NO. 7:

- 000001-04 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
- 001001-01 AREAS OR REINFORCEMENT BARS
- 001006 DECIMAL OF AN INCH AND OF A FOOT
- 280001-03 TEMPORARY EROSION CONTROL SYSTEMS
- 542301-01 PRECAST REINFORCED CONCRETE FLARED END SECTION
- 602301-01 INLET TYPE A
- 602306-01 INLET TYPE B
- 602401-01 MANHOLE, TYPE A
- 602601-01 PRECAST REINFORCED CONCRETE FLAT SLAB TOP
- 602701-01 MANHOLE STEPS
- 604006-02 FRAME AND GRATE, TYPE 3
- 604021-01 BASE, FRAME AND LIDS TYPE 5
- 604036-01 GRATE, TYPE 8
- 606001-03 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
- 701006-02 OFF ROAD OPERATIONS, 2L, 2W, 15' TO 24" FROM PAVEMENT EDGE
- 701501-03 URBAN LANE CLOSURE, 2L, 2W UNDIVIDED
- 702001-06 TRAFFIC CONTROL DEVICES

BENCHMARK INFORMATION

BM1

CHISELED "X" ON TOP OF SW BOLT, BASE OF WEST LEG "FAST STOP" GAS STATION SIGN.
 ± STA 1229+20, 37.5' RT. ASSUMED ELEV. 100.432

PLOT DATE = #DATE#
 PLOT SCALE = #SCALE#
 USER NAME = #USER#

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

**GENERAL NOTES
&
INDEX OF SHEETS**

SCALE: VERT. HORIZ.
DATE

DRAWN BY
CHECKED BY