

MANHOLES										
MH NO.	STATION	OFFSET	LT/RT	QUANTITY (EACH)					FILL	TEMPORARY
				TYPE A, 5' DIAMETER, TYPE 1 FRAME, CLOSED LID	TYPE A, 6' DIAMETER, TYPE 1 FRAME, CLOSED LID	TYPE A, 7' DIAMETER, TYPE 1 FRAME, OPEN LID	TYPE A, 7' DIAMETER, TYPE 1 FRAME, CLOSED LID			
STAGE 1										
101	3958+45	62.5'	LT	1						
102	3958+73	83.5'	LT		1					
103	3962+96	73'	LT			1				
104	3963+04	92'	LT						1	
105	3963+60	107.5'	LT						1	
106	3964+09	107.5'	LT						1	
107	3964+22	107.5'	LT						1	
108	3964+25	70.4'	LT						1	
STAGE 2										
200	3958+53	58.3'	LT	1						
201	3958+76	75.9'	LT	1						
202	3963+05	65'	LT	1						
203	3963+37	89.5'	LT	1						
204	3963+77	34.1'	LT			1				
205	3964+08	34'	LT			1				
STAGE 3										
301	3963+60	115'	LT			1				
302	3963+98	80.7'	LT			1				
300	3963+30	95.8'	LT				1			
303	3965+67	79'	LT				1			
	3964+08	60.4'	LT					1		
PROJECT TOTAL				5	1	5	2	1	5	

TEMPORARY INFORMATION SIGNING					
STATION	LT/RT	SIGN DIM. (IN)	DESCRIPTION	QUANTITY	AREA (SQ FT)
3987+00	LT	45x68	ARTERIAL ROAD INFO.	1	25
3947+00	RT	45x68	ARTERIAL ROAD INFO.	1	25
PROJECT TOTAL				50	

PLUG EXISTING STORM SEWERS			
STATION	OFFSET	LT/RT	QUANTITY (EACH)
STAGE 2			
3963+68	35.1'	LT	1
PROJECT TOTAL			1

CHAIN LINK FENCE, ATTACHED TO STRUCTURE, SPECIAL				
FROM		TO		QUANTITY (FOOT)
STATION	O/S	STATION	O/S	
24+04	18' RT	25+08	25' RT	105
PROJECT TOTAL				105

CHAIN LINK GATES, (SPECIAL)				
STATION	OFFSET	LT/RT	QUANTITY (EACH)	
			8' X 12' SLIDE	8' X 10.5' SLIDE
24+16	4'	RT		2
25+00	24'	RT	1	
PROJECT TOTAL			3	

BARRIER WALL MARKERS, TYPE C			
FROM STA	TO STA	LT/RT	QUANTITY (EACH)
3959+50	3967+00	LT	60
Contingency Quantity For Repairs:			20
PROJECT TOTAL			80

CHAIN LINK FENCE, 8' (SPECIAL)				
FROM		TO		QUANTITY (FOOT)
STATION	O/S	STATION	O/S	
24+04	18' RT	24+11	9' RT	12
25+05	24' LT	25+07	24' RT	50
24+19	3' LT	24+94	24' LT	81
PROJECT TOTAL				143

FILL EXISTING STORM SEWERS			
FROM STA	TO STA	LT/RT	QUANTITY (CU YD)
STAGE 2			
3964+08	3964+08	LT	2
3964+08	3964+08	LT	3
3964+25	3965+64	LT	62
PROJECT TOTAL			67

AGGREGATE SUBGRADE 8"			
FROM STA	TO STA	LT/RT	QUANTITY (SQ YD)
20+57	25+07		943
PROJECT TOTAL			943

HOT-MIX ASPHALT DRIVEWAY PAVEMENT 6"			
FROM STA	TO STA	LT/RT	QUANTITY (SQ YD)
20+10	20+57		194
20+96	21+33		25
22+35	24+12	RT	137
PROJECT TOTAL			356

CURB REMOVAL (PARTIAL)			
FROM STA	TO STA	LT/RT	QUANTITY (FT)
3966+30	3968+00	LT	170
PROJECT TOTAL			170

NOTE:  
THIS INCLUDES TEMPORARY GRADING OF FLAT AREA REQUIRED FOR THE INSTALLATION OF TEMPORARY CONCRETE BARRIER AND IMPACT ATTENUATOR.

IMPACT ATTENUATORS (NON-REDIRECTIVE), TEST LEVEL 2		
STATION	LT/RT	QUANTITY (EACH)
3970+00	LT	1
PROJECT TOTAL		1

CONTROLLED LOW-STRENGTH MATERIAL			
FROM STA	TO STA	LT/RT	QUANTITY (SQ YD)
25+04	25+29	LT	129
PROJECT TOTAL			129

NOTE:  
CONTROLLED LOW-STRENGTH MATERIAL TO BE USED TO FILL WET WELL OF EXISTING PUMP STATION WHICH REMAINS BELOW ELEVATION 691.00

TEMPORARY DRAINAGE CONNECTION			
STATION	OFFSET	LT/RT	QUANTITY (EACH)
3964+08	53.3'	LT	1
PROJECT TOTAL			1