

	PROPOSED LEGEND							
1	PROP. PROCESSING MODIFIED SOIL 12"							
<u> </u>	PROP. HOT-MIX ASPHALT PAVEMENT (FULL-DEPTH), 13 3/4"							
(<u>3</u>)	PROP. BITUMINOUS MATERIALS (PRIME COAT)							
<u>(4)</u>	PROP. SUB-BASE GRANULAR MATERIAL, TYPE C							
(5)	PROP. HOT-MIX ASPHALT SHOULDERS, 8" (W - W/O RUMBLE STRIP)							
<u>6</u>	PROP. AGGREGATE SHOULDERS, TYPE A							
7	PROP. AGGREGATE SHOULDERS, TYPE A, 8"							
8	PROP. PIPE UNDERDRAINS, 4"							
9	PROP. SEEDING CLASS 2, WITH MULCH METHOD 2							
0	PROP. TOPSOIL PLACEMENT, 4"							
11)	PROP. LANE STRIPING (SEE PAVEMENT MARKING PLAN)							
(2)	PROP. AGGREGATE BASE COURSE, TYPE A, 10"							
(13)	NOT USED							
(14)	PROP. A-3 BITUMINOUS SURFACE TREATMENT							
(15)	PROP. HOT-MIX ASPHALT PAYEMENT (FULL-DEPTH), 9 1/2"							
(E)	PROP. REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL							
\mathfrak{V}	PROF. PAVEMENT REMOVAL							
(18)	NOT USED							
(19	NOT USED							
9	NOT USED							
(21)	NOT USED							
83	FOG TACK COAT PER ENGINEER (ART. 407.13)							
(3)	NOT USED PROP. HOT MIX ASPHALT SURFACE REMOVAL, VARIABLE (1/2" TO 3/4")							
29	PROP. HOT MIX ASPHAL! SURFACE REMOVAL, VANIABLE 172 TO 574 7							
(S)	PROP. INTERSEEDING, CLASS 5 (MODIFIED)							
8	PROP. STORM SEWER, 18"							
6	PROP. TOPSOIL EXCAVATION (SPECIAL), 12"							
69	PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2"							
8	PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50, 1 1/2"							
3	PROP. HOT-MIX ASPHALT SHOULDERS, 2" (W - W/O RUMBLE STRIP)							
3	PROP. HOT-MIX ASPHALT LEVELING BINDER (MACHINE METHOD), N50, 3/4"							
Ğ	PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50, 1 1/2"							
(のののののののののののののののののののののののののののののののののののの	PROP. HOT-MIX ASPHALT BINDER COURSE, IL 19.0, N50, 2 1/2"							

		CONTRA								
F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.						
75	84-12; 11-3	•	729	25						
STA. N/A TO STA. N/A										
FED. ROAD DIST. NO. 5 ILLINOIS FED. AID PROJECT										
SANGAMON AND CHRISTIAN										

EXISTING LEGEND

1	EXISTING	P.C.C.	CONCRETE	(9"-6"-9")	WITH	BASE	COURSE
	WIDENING	AND B	SUONIMUTIS	OVERLAY			

(2) EXISTING STABILIZED SUB-BASE (12")

(3) EXISTING BITUMINOUS CONCRETE PAVEMENT, 1334"

4 EXISTING BASE COURSE WIDENING (9")

5 EXISTING BITUMINOUS CONCRETE OVERLAY (21/4" TO 51/4")

FXISTING SHB-BASE GRANHLAR MATERIAL (7) EXISTING BITUMINOUS CONCRETE SHOULDER (8")

(8) EXISTING BITUMINOUS CONCRETE SHOULDER (91/2")

(9) EXISTING AGGREGATE SHOULDER (6")

10 EXISTING AGGREGATE SHOULDER (8")

II) EXISTING PIPE UNDERDRAIN, 4" 2 EXISTING OIL AND CHIP PAVEMENT (VARIES)

ILLINOIS DEPARTMENT OF TRANSPORTATION TYPICAL SECTIONS SIDEROADS - DETAILS SCALE: NONE DRAWN BY: B.J.D. CHECKED BY: J.M.M. DATE: 03/06/2012

TYPICAL SECTIONS - STANDARD DETAILS