

F. A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO
693	15 RS-2, 118 RS-4	TAZEWELL	28	4

ENGINEERS FIELD OFFICE

Add the following sentence to the end of paragraph 670.02 (i) and 670.04 (e):
All of the telephone lines provided shall have unpublished numbers.

CONTRACT NO. 68375

BITUMINOUS CONCRETE MIXTURE REQUIREMENTS

Mixture Use(s):	POLYMERIZED SURFACE CSE SUPERPAVE	PATCHING
AC/PG:	SBS OR SBR PG 70-22	PG 64-22
RAP % (Max.):**	0	25%
Design Air Voids:	4.2% @ N=70	4.2% @ N=70
Mixture Composition: (Gradation Mixture)	IL-12.5 OR IL-9.5	IL 19.0
Friction Aggregate:	MIXTURE E	N/A

** If the RAP is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer

PAVING SURFACE COURSE

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the bituminous surface. No interruptions for side roads, entrances, turn lanes, etc. will be allowed

JOB SPECIFIC NOTES

Milling at the gutter may vary 1 1/2" to 3" +/- . This shall be paid for as "Bituminous Surface Removal 2".

COMMITMENTS

NO COMMITMENTS HAVE BEEN MADE FOR THIS PROJECT

ILLINOIS DEPARTMENT OF TRANSPORTATION

GENERAL NOTES