

F. A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO
693	15 RS-2, 118 RS-4	TAZEWELL	28	15

SCHEDULE OF RESURFACING QUANTITIES

CONTRACT NO. 68375

LOCATION	LENGTH	WIDTH	AREA	BIT. SURFACE REMOVAL 2"	BIT. MATERIAL PRIME COAT	AGGREGATE PRIME COAT	PBCSC SUPER "E" N 70 2"
	FEET	FEET	SQ. YD.	SQ. YD.	TON	TON	TON
STA. 68+82 TO 70+20	138	52	797.3	739.5	0.32	1.60	89.3
STA. 70+20 TO 71+33	113	52-57	684.3	684.3	0.27	1.37	76.7
STA. 71+33 TO 72+60	127	57-63	846.7	846.7	0.34	1.69	94.8
STA. 72+60 TO 74+65	205	63	1435	1435	0.57	2.87	160.7
STA. 74+65 TO 75+51	86	63 & VAR.	749.5	749.5	0.30	1.50	84.0
STA. 75+51 TO 76+73	122	75	1016.7	1016.7	0.41	2.03	113.9
STA. 76+73 TO 77+73	100	75-63	766.7	766.7	0.31	1.53	85.9
STA. 77+73 TO 78+99	126	63-57	840	840	0.34	1.68	94.1
STA. 78+99 TO 80+23	124	57-52	750.9	750.9	0.30	1.50	84.1
STA. 80+23 TO 105+67.5 (BK)	2544	52	14698.7	14698.7	5.88	29.4	1646.3
STA. 62+86.7 (AH) TO 67+50	463	52-64	2983.8	2983.8	1.19	5.97	334.2
STA. 67+50 TO 71+80	430	64-86	3615	3615	1.45	7.23	404.9
STA. 71+80 TO 74+00	220	72	1760	1760	0.70	3.52	197.1
STA. 74+00 TO 80+00	600	76+65	4339	4339	1.74	8.68	486.0
STA. 80+00 TO 86+00	600	48-65	3780	3780	1.51	7.56	423.3
STA. 86+00 TO 87+75	175	60-72	1283	1207.4	0.51	2.57	143.7
GRAND TOTALS				40213.0	17.0	81.0	4519.0

PRIME COAT CONVERSION FACTORS	
SURFACE TYPE	BITUMINOUS (PRIME COAT)
COLD MILLED SURFACE	0.1 GAL./SQ. YD.
	0.004 TON/GAL.

SURFACE TYPE	AGGREGATE (PRIME COAT)	P BCSC SUPER "E" N70
COLD MILLED SURFACE	4 LB./SQ.YD.	112 LB./SQ.YD./IN.

ILLINOIS DEPARTMENT OF TRANSPORTATION

RESURFACING
QUANTITIES